



DECLARATION OF PERFORMANCE

No. 01061

- | | |
|---|---|
| 1. Unique identification code of the product-type: | TEROSON SE 20 (01061) |
| 2. Intended use/es: | Sealant for facade for interior and exterior application (F-EXT-INT) |
| 3. Manufacturer: | Henkel AG & Co. KGaA
D-40191 Düsseldorf |
| 4. Authorised representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3
Reaction to fire: System 3 |
| 6a. Harmonised standard/s: | EN 15651-1:2012 |
| Notified body/ies: | Type-testing: SKZ-TeConA GmbH, 1213
Reaction to fire : SKZ-TeConA GmbH, 1213 |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified body/is: | Not relevant |
| 7. Declared performance/s: | |

Conditioning: Method B

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 30 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Durability			
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		

- | | |
|---|--------------|
| 8. Appropriate Technical Documentation and/or Specific Technical Documentation: | Not relevant |
|---|--------------|



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley
Global Head of Marketing ACG I

(name and function)

(signature)


Dr. Michael Frank
Director Global Product Development

(name and function)

(signature)

Düsseldorf, 17.5.2024
(place and date of issue)

Attachment

 1213	
Henkel AG & Co. KGaA D-40191 Düsseldorf 14 01061 TEROSON SE 20 (01061)	
EN 15651-1:2012 Sealant for facade for interior and exterior application	
Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 30 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
Durability	
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
www.henkel-dop.com	