



DECLARATION OF PERFORMANCE

No. 01373

- | | |
|---|---|
| 1. Unique identification code of the product-type: | TEROSON SE 108 XLT Transparent / Eiche |
| 2. Intended use/es: | Sealant for facade for interior and exterior application (F-EXT-INT) Sealant used for sealing glazing applications (G) Sealant for joints in sanitary areas (S) |
| 3. Manufacturer: | Henkel AG & Co. KGaA |
| 4. Authorised representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3 Reaction to fire: System 3 |
| 6a. Harmonised standard/s: | EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012 |
| Notified body/ies: | Type-testing: SKZ - Testing GmbH, 1213 Reaction to fire : SKZ - Testing GmbH, 1213 |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified body/ies: | Not relevant |
| 7. Declared performance/s: | |
| Conditioning: Method A | |
| Substrate: Aluminium; without primer | |

| Essential characteristics | Performance | System/s of assessment and verification of constancy of performance | Harmonised technical specification |
|--|-------------|---|------------------------------------|
| Reaction to fire | Class E | System 3 | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | System 3 | |
| Water tightness and air tightness | | | |
| Resistance to flow | ≤ 3 mm | | |
| Loss of volume | ≤ 10 % | | |
| Tensile properties (i.e. elongation) at maintained extension after water immersion | NF | | |
| Durability | pass | | |

Conditioning: Method A
Substrate: Glass; without primer

| Essential characteristics | Performance | System/s of assessment and verification of constancy of performance | Harmonised technical specification |
|---|-------------|---|------------------------------------|
| Reaction to fire | Class E | System 3 | EN 15651-2:2012 |
| Release of chemicals dangerous to the environment and health | NPD | System 3 | |
| Water tightness and air tightness | | | |
| Loss of volume | ≤ 10 % | | |
| Resistance to flow | ≤ 3 mm | | |
| Adhesion/cohesion properties after exposure to heat, water and artificial light | NF | | |
| Elastic recovery | ≥ 60 % | | |
| Durability | pass | | |

Conditioning: Method A
Substrate: Aluminium; without primer

| Essential characteristics | Performance | System/s of assessment and verification of constancy of performance | Harmonised technical specification |
|--|-------------|---|------------------------------------|
| Reaction to fire | Class E | System 3 | EN 15651-3:2012 |
| Release of chemicals dangerous to the environment and health | NPD | System 3 | |
| Water tightness and air tightness | | | |
| Resistance to flow | ≤ 3 mm | | |
| Loss of volume | ≤ 20 % | | |
| Tensile properties (i.e. elongation) at maintained extension after water immersion | NF | | |
| Microbiological growth | 1 | | |
| Durability | pass | | |

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager

(name and function)

(signature)


Dr. Bernhard Schöttmer
Director Global Product Development

(name and function)

(signature)

Düsseldorf, 21.06.2017

(place and date of issue)

| | |
|---|---------------------------|
|  1213 | |
| Henkel AG & Co. KGaA 17 01373 TEROSON SE 108 XLT Transparent / Eiche | |
| EN 15651-1:2012 Sealant for facade for interior and exterior application | |
| - Type | F-EXT-INT |
| - Conditioning: | Method A |
| - Substrate: | Aluminium; without primer |
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| Resistance to flow | ≤ 3 mm |
| Loss of volume | ≤ 10 % |
| Tensile properties (i.e. elongation) at maintained extension after water immersion | NF |
| Durability | pass |
| EN 15651-2:2012 Sealant used for sealing glazing applications | |
| - Type | G |
| - Conditioning: | Method A |
| - Substrate: | Glass; without primer |
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| Loss of volume | ≤ 10 % |
| Resistance to flow | ≤ 3 mm |
| Adhesion/cohesion properties after exposure to heat, water and artificial light | NF |
| Elastic recovery | ≥ 60 % |
| Durability | pass |
| EN 15651-3:2012 Sealant for joints in sanitary areas | |
| - Type | S |
| - Conditioning: | Method A |
| - Substrate: | Aluminium; without primer |
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| Resistance to flow | ≤ 3 mm |
| Loss of volume | ≤ 20 % |
| Tensile properties (i.e. elongation) at maintained extension after water immersion | NF |
| Microbiological growth | 1 |
| Durability | pass |