

Controller 97160 provides precise application of 2-part Loctite® products, such as MMAs, Epoxies and Silicones.

Applications include drop or bead dispensing or potting.

In line manufacturing or other automated workplace environments, the following messages can be analyzed by a higher ranking controller:

- the **Ready** signal,
- the **Empty** signal from the product reservoir,
- all other **Fault** signals as a collective signal.



Do not operate the controller in an explosive atmosphere. Controller 97150 offers a wide range of options for adjusting the desired quantity of product to be dispensed. All production related values can be stored on an SD card, and can be retrieved and modified at any time. The controller has a graphical user interface for intuitive operator guidance and operation.

Technical Data

Power supply (wall power supply included):	100-240 VAC, 47-63 Hz
Power supply controller:	24 VDC
Power consumption:	100 VA
Dispense start:	Pushbutton, footswitch, 24 V signal
Operating modes:	Timed dispense program, quantity, start-stop
Interface:	RS232 / USB
Operating pressure control:	0 to 7 bar (optional sensor required)
Dispensing pressure control:	0 to 40 bar max. (optional sensor required)
Data analysis:	Dispensing pressure curve graphically displayed, maximum pressure alert by controller
External memory card:	MM C/SD-Card, min. 64 MB max. 24 dispense programs
Storage and operating temperature:	+10°C to +40°C (+50°F to +104°F), dry and dust free
Dimensions (WxHxD):	240 mm x approx..115 mm x 260 mm
Weight:	approx. 1,3 kg
Order no.:	1533495

Note:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel AG & Co. KGaA specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel AG & Co. KGaA's products. Henkel AG & Co. KGaA specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel AG & Co. KGaA patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.