

# EQ MX Mobile Mixer Item No. 2717051 / 2717052 (110V / 230V)

## **Product Description**

The Loctite® EQ MX Mobile Mixer is an electric motor driven pail mixing system compatible with various MRO protective coatings, grouts, and other products. The Loctite® EQ MX is specifically designed to mix 5-gallon, 3-gallon, and 2-gallon kits of product in a simple and efficient process. The EQ MX utilizes a rotating basket and a stationary mixing paddle which provides axial and radial action to the product. The mixing paddle scrapes the sides and bottom of the pail, causing the product to fold in on itself to provide a complete mix. With easy to swap out baskets and paddles as well as adjustable mix angles, the EQ MX will cater to dozens of mixing applications commonly encountered in the field.



## **Product Features**

- 1/2 HP electric motor
- Easy to change baskets & mixing paddles
- 60 RPM
- 8" semi-pneumatic wheels
- Variety of baskets and paddles
- On-Off switch and fuse protection

## Benefits

- Adjustable mix angles to ensure a uniform mix.
- Mounted protected switch to prevent unnecessary damage.
- Convenient for solo operation.
- Easy to transport.
- Interchangeable baskets and paddles allow for a variety of configurations from one system.
- Properly sized baskets to prevent pail slipping during operation.



## **Technical Data**

Technical Specification	<u>110V</u>	<u>230V</u>
Total Weight	26.3 kg	40 kg
Dimensions	31 in. x 19 – ¼ in. x 32 in.	35 in. x 19 – ¼ in. x 36 in
Torque	54.2 N.m (480 in.lbs.)	54 N.m (478 in.lbs.)
Нр	1/2	1/2
Voltage	110V	230V
Amps	7.8	2.8
Phase	Single	Single
Max Ambient Temp	40°C	40°C

## **Items Supplied**

- Loctite® EQ MX Mobile Mixer (110V / 230V), IDH 2717051 / 2717052
- Equipment Manual

#### **Accessories and Spare Parts**

- Loctite® EQ MX 2 Gal Basket Kit (110V / 230V), IDH 2717053 / 2717057
- Loctite® EQ MX 3 Gal Basket Kit (110V / 230V), IDH 2717054 / 2717058
- Loctite® EQ MX 5 Gal M Basket Kit (110V / 230V), IDH 2717055 / 2717059
- Loctite® EQ MX 5 Gal P Basket Kit (110V / 230V), IDH 2717056 / 2717060
- Loctite® EQ MX 2 Gal Paddle, IDH 2717474
- Loctite® EQ MX 5 Gal Metal Paddle, IDH 2717475
- Loctite® EQ MX 3 Gal Plastic Paddle, IDH 2717476
- Loctite® EQ MX 5 Gal Plastic Paddle, IDH 2717477

#### Note



The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

#### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. 

denotes a trademark registered in the U.S. Patent and Trademark Office.

#### Document # 9001312, Rev. B, Date: 10/26/2018

Henkel Americas 1-800-LOCTITE www.equipment.loctite.com Henkel Europe +49.89.320800.1800 www.henkel.com/industrial Henkel Asia Pacific +86.21.2891.8863 www.henkel.com/industrial

For most direct access to local support sales and technical support visit: www.henkel.com/industrial