



Rail Depot Maintenance Guide

LOCTITE & TEROSON Solutions

Improve your track Maintenance and Repair everyday with Henkel total solutions!

Manufacturers and users of rail equipment face daily challenges – reducing costs, improving efficiency, and increasing innovation, to name just a few. While there are many adhesive suppliers to choose from, they're not all created equal. You need a supplier with a broad product portfolio, a global footprint, and the engineering and application know-how to solve your challenges.











Your supplier for more reliability and more safety.

Henkel's LOCTITE® brand offers an extensive line of high performance adhesives, sealants, and dispensing/curing systems – all available from a single supplier. LOCTITE® products are used to build everything from automobiles to dishwashers to tractors – and the trains that deliver them. LOCTITE® products help make these machines and sub-assemblies less expensive, more reliable and longer lasting.



SOLUTIONS RANGE

Product name	Description	Rail Cat. No	Picture
LOCTITE 243	<ul style="list-style-type: none"> • Medium strength threadlocker that can be used on ,as received' parts. • Resists vibration loosening. • Parts can be dismantled with normal hand tools. • Threads are completely sealed. 	007/056118	
LOCTITE 268 STICK	<ul style="list-style-type: none"> • For LOCTITE 268 is a high strength threadlocker. • For use on track, signalling and overhead applications. • Resistance to heavy shock, vibration, and stress. 	007/076024	
LOCTITE 406	<ul style="list-style-type: none"> • Rapid bonding of rubber and plastics. • Bonds polyolefins, silicone rubber and PTFE when used with primer 770. • For all interior smoke resistant rubbers. 	007/0005857 LOCTITE PC 770 PRIMER 007/046122	
LOCTITE 518	<ul style="list-style-type: none"> • LOCTITE 518 Gasket Maker is a non-corrosive anaerobic sealer primarily for use on aluminium, iron, and steel flanged mating surfaces. • Forms a flexible, solvent-resistant seal that will not tear or decay. • Parts will disassemble easily even after extended service. 	057/118001	
LOCTITE 577	<ul style="list-style-type: none"> • Replaces tapes, pastes and hemp. • Instant low pressure seal, high pressure seal when fully cured. • Use on door gear and brakes. • Resists vibration. 	007/060725	
LOCTITE 638	<ul style="list-style-type: none"> • High strength retainer. • For bonding cylinder liners, bearings and shafts. • Prevents fretting and corrosion. 	007/060544	
LOCTITE 641	<ul style="list-style-type: none"> • Medium strength LOCTITE 641 Bearing Fit is recommended for parts that need subsequent dismantling. • Retained bearings and bushes can be easily removed from shafts or housings using ordinary tools and methods. • Prevents fretting and corrosion. 	007/060416	
LOCTITE SF 7039	<ul style="list-style-type: none"> • Contact cleaner spray that does not affect insulating varnishes. • For cleaning electrical contacts, relays, switchgear etc. • Displaces moisture and forms a water repellent film. 	007/007421	

SOLUTIONS RANGE

Product name	Description	Rail Cat. No	Picture
LOCTITE SF 7063	<ul style="list-style-type: none"> • General purpose industrial aerosol cleaner for all grease and oil removal prior to the use of LOCTITE adhesives, greases and sealants. • Ready-to-use formula dries residue free and is compatible with metal, glass, rubber, most plastics and painted surfaces. • Contains no ozone depleting compounds. 	007/025032	
LOCTITE LB 8008	<ul style="list-style-type: none"> • Copper Anti-Seize brush top. • Clean and easy to apply. • For use on screws, nuts, pipes, hinges and door gear. • Typical applications: exhaust bolts, brake caliper bolts. 	007/000132	
PLASTIC PADDING ULTIMA	<ul style="list-style-type: none"> • Universal filler for all purposes. • For all repair jobs on all surfaces including galvanised, zinc coated, aluminium, mild steel, glass fibre and polycarbonate. • For use on screws, nuts, pipes, hinges and door gear. • Typical applications: exhaust bolts, brake caliper bolts. 	064/9601	



For more information on LOCTITE Rail products, contact us on

📞 01442 278100 or via 📧: technicalservice.loctite@henkel.com

Henkel Limited
Technologies House,
 Wood Lane End,
 Hemel Hempstead, Hertfordshire HP2 4RQ
www.henkel-adhesives.com

