



LOCTITE® HELPS DECREASE SLURRY BUILDUP IN PIPES

**LOCTITE® PC 7255™ Nordbak®
Sprayable Ceramic**



Situation:

An Oil & Gas company was having trouble with slurry build up in their pipes. Because they were not using any coatings inside their pipes, they did not have any slickness to avoid the slurry build up. This caused long lead times and high replacement costs. The company was looking for a solution that would decrease the slurry build up, was easy to apply and showed return on investment.

LOCTITE Solution:

The local LOCTITE Expert came in and recommended PC 7255™, a sprayable wear resistant coating. PC 7255™ protects against turbulence, abrasion and corrosion providing lasting protection. The pipes were cleaned, sandblasted, and prepared for PC 7255™ to be applied.

Benefits:

After testing, PC 7255™ provided the slickness and protection needed in the pipes to avoid slurry buildup for extended periods of time. This showed value to the company by improving reliability, therefore saving time and maintenance costs. LOCTITE was able to give this company a great return on the investment because of the solution that was used.



Product	Size	IDH
PC 7255™	1.125L	2462905

All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S., Germany and elsewhere. © 2023 Henkel Corporation. All rights reserved. DSGN0027568_C



Henkel Adhesive Technologies