



## WATERSLIDE SHINE RESTORED ALL SEASON WITH ONE COAT OF LOCTITE®

### SITUATION

A water park needed a labor efficient method to restore and maintain gel coat waterslides. Because of labor shortages it was not feasible to continue to manually clean and wax the slides weekly during the season. The company was actively looking for a better way to maintain and protect their most critical asset.

### LOCTITE SOLUTION

A LOCTITE® Technical Sales Engineer reviewed the requirements and recommended a total solution. Clean the slide surface with Frekote PMC, then apply LOCTITE® PC 4400™ with a HVLP spray gun. LOCTITE® PC 4400™ is a clear one-part polyurethane/polyurea hybrid coating. It dries tack-free in an hour. Within 24 hours it forms an extremely hard and high-gloss flexible coating that provides strong corrosion, abrasion, chemical and UV resistance.

### BENEFITS

LOCTITE® PC 4400™ reduced labor by 75% for the first season. It required less labor for the initial application and no re-application was needed the rest of the season. In addition, LOCTITE® PC 4400™ restored the color and gloss of the faded, weathered slides and maintained this high-quality appearance through-out the season. It also protected the gel coat from cracking, a safety risk for users. LOCTITE® PC 4400™ is expected to deliver years of protection, a dramatic improvement in performance and reduction in labor.



Product	Size	IDH
LOCTITE® PC 4400™	1 liter	2573885
	1 gallon	2573975



\*Representative images used to maintain customer confidentiality.

All marks used are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere. ® = registered in the U.S. Patent and Trademark Office. © 2023 Henkel Corporation. All rights reserved.DSGN0027688 (02/23)



Henkel Adhesive Technologies