

DON'T DOUBT YOUR GROUT FILL YOUR HOLE WITH LOCTITE®



SITUATION

A company had problems maintaining critical alignment of heavy, high vibration equipment bolted to cement floors. They determined the root cause of this problem was their grouting was not strong enough to maintain the high torque applied to the ¾ inch floor studs. They needed to find a grout that would reliably maintain the high torque required to keep equipment in position.



LOCTITE® SOLUTION

The company developed a test plan to rigorously evaluate commercially available grouting compounds. The goal was to find a product that was easy for equipment installers to apply and consistently maintained 250 ft-lbs of torque on ¾" threaded mounting studs. Of the twenty products evaluated, LOCTITE® EA 7363™ was selected as the best product for ease of use and delivered high performance. The LOCTITE® solution decreased overall repair frequencies and increased production rates.



BENEFITS

LOCTITE® EA 7363™ is easy for equipment installers to use. Screw the mix nozzle on the cartridge and it is ready to dispense. The product flows well and can be leveled to provide a smooth surface. Once cured, LOCTITE® EA 7363™ delivers best in class performance.

Product	Size	IDH
LOCTITE® EA 7363™	8.6 fl oz	1108757

***Representative images used to maintain customer confidentiality.**

All marks used are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere. ® = registered in the U.S. Patent and Trademark Office.
© 2025 Henkel. All rights reserved. DSGN0046673 (09/25)