


Epoxy Flooring Coatings

Standard Colours



RAL 9016 - Traffic white



RAL 7032 - Pebble grey




RAL 7035 - Light Grey



RAL 7042 - Traffic Grey




RAL 5012 - Light Blue



RAL 6032 - Signal Green



RAL 7037 - Dusty Grey



RAL 7012 - Basalt Grey

All the above colours are for representation only. Actual color may vary vs actual coated sample

Polyoxy FC

Solvent free epoxy resin coating

Polyoxy FC is a versatile, two component solvent free epoxy resin based floor and wall coating that provides a durable and impervious coating which is easy to clean and have excellent resistance to a wide range of chemicals.

Key Benefits

- Easy to apply
- Durable and hardwearing
- Excellent resistance to a wide range of chemicals
- Hygienic. Provides an impervious and seamless surface which is easy to clean

Uses

- Showrooms
- Pump & generator rooms
- Warehouses and factory floors
- Workshops and fabrication units
- Food and pharmaceutical industries
- Internal lining of water retaining structures
- Parking decks, garages and car wash areas



Polyoxy SL Range

Epoxy resin based self levelling floor topping



SL 20

Polyoxy SL 20 is a three component, solvent free, epoxy resin based self levelling floor topping which provides a seamless, tough, chemical resistant and hygienic floor surface. It can be applied in the thickness of 1mm to 4mm, giving a glossy floor finish.



SL 40

Polyoxy SL 40 is a three component, solvent free, epoxy resin based self levelling floor topping which provides a seamless, tough, chemical resistant and hygienic floor surface. It can be applied in the thickness of 2mm to 4mm, giving a matt floor finish.



SL 50

Polyoxy SL 50 is a three component, solvent free, epoxy resin based self levelling floor topping which provides a seamless, tough, chemical resistant and hygienic floor surface. It can be applied in the thickness of 4mm to 7mm.


Polyoxy SL Range Key Benefits

- Self Levelling
- Good resistance to a wide range of chemicals.
- Seamless floor, which helps in keeping the microbial count low
- Provides a hygienic floor which can be cleaned easily
- Provides a good abrasion resistance and dense, impervious flooring
- 100% reactive system totally free of solvents




Polyurethane Flooring Coatings


Standard Colours



RAL 9016 - Traffic white



RAL 7032 - Pebble grey




RAL 7035 - Light Grey




RAL 7042 - Traffic Grey




RAL 5012 - Light Blue



RAL 6032 - Signal Green



RAL 7037 - Dusty Grey



RAL 7012 - Basalt Grey

All the above colours are for representation only. Actual color may vary vs actual coated sample

Polypur TC 20

UV stable, PU car park deck coating

Polypur TC 20 is a two component high quality UV stable polyurethane car park deck coating system. The coating provides a seamless, abrasion resistant floor coating system for both internal and external areas.

Key Benefits

- Good chemical resistance
- Excellent abrasion resistance
- Highly durable and UV stable
- Excellent surface finish with different colors
- Can be applied on many different substrates and on cured epoxy systems

Uses

- Plant rooms
- Industrial floors
- Factory warehouses
- Trafficable flat roofs
- Terraces and balconies
- Car park decks and ramps
- Chemical processing areas




Line marking paint for roads and parking




Polypur LMP


Polypur LMP is a specially formulated high build line marking paint based on a modified acrylic/chlorinated rubber hybrid.




RAL 9016 - Traffic white



RAL 1023 - Traffic Yellow



RAL 9017 - Traffic Black



RAL 3020 - Traffic Red



Henkel Polybit Industries Ltd.
PO Box: 293, Umm Al Quwain, UAE
Phone: +971 (6) 76 70 777, Fax: +971 (6) 76 70 197
henkelpolybit@henkel.com
www.henkelpolybit.com

Henkel Polybit Industries Ltd.
PO Box: 5911, Dammam - 31432
Industrial Area - II, Kingdom of Saudi Arabia
Phone: +966 13 808 4061 / 62, Fax: +966 13 812 1164
polybitdammam@henkel.com