



# CONCRETE REPAIR SOLUTIONS

## REDUCE DOWNTIME AND LABOR COSTS

### LOCTITE PC 9410 Magna-Crete & LOCTITE PC 9620 Magna-Grout\*

- Two component kit
- Fast setting working time of 5-20 minutes depending on temperature
- Bonds to new and old concrete, as well as most construction materials including wood, glass and steel
- Can be mixed easily and applied from -15°F to 115°F (-26°C to 46°C)
- Chemically resistant to most common liquids and chemicals
- High impact resistance and compression strength
- 1/2 Hour: Pedestrian ready

### TYPICAL APPLICATIONS

Manufacturing floors, shipping floors, ramps, loading docks, roadways, highways, highway dividers, parking lots, parking garages, airplane runways, commercial freezers, beam and column repairs.

Name	IDH No.	Pkg Size
LOCTITE® PC 9410	235573	5 gal
	235572	1 gal
LOCTITE® PC 9620	1476710	5 gal



ADDITIONAL PRODUCTS				
Name	Features	IDH No.	Pkg Size	
LOCTITE® PC 7257™ Activator	Extra Activator	424216	10 lb. bottle	
LOCTITE® PC 7257™ Winter Additive	Speed cure time by 10 min. when winter temp is below 45°F (72°C)	708253	1 lb tub	
LOCTITE® PC 7257™ Summer Additive	Slows cure time by 10 min. when summer temp is above 85°F (129°C)	708252	1 lb tub	
LOCTITE® PC 7257™	For large applications	976786	55 gal. activator	
		831304	2,475 lb. aggregate	

\*Magna-Grout can be used under ¼ in. of thickness





## ADDITIONAL CONCRETE REPAIR SOLUTIONS



### LOCTITE® PC 6231™ Crack Filler SL

- Two-component, self-leveling, flexible formula in coaxial cartridge.
- Can be used indoors or outdoors.
- Bonds concrete, block, brick, stone, wood and metal.

IDH	Package Size
1291113	8.6 fl. oz. coaxial cartridge



### LOCTITE® PC 9416™ Floor Fill

- Three-component, self-leveling, non-shrinking epoxy.
- 100% solid, epoxy-based system for repairs.
- Stronger than concrete, bonds to almost any clean substrate and provides corrosion and chemical resistance.

IDH	Package Size
235632	10 lb. kit
235633	40 lb. kit



### LOCTITE® PC 7319™

- Smooth, glossy, low-friction finish
- Protects against turbulence, abrasion, cavitation, chemical attacks and corrosion.
- Low viscosity that can be applied by brush.

IDH	Package Size
209816	12 lb. kit

## SUCCESS STORY



### SITUATION

A Food and Beverage company encountered corroded and deteriorating concrete, due to chemicals and other elements. It was causing chronic shutdowns in that area, resulting in downtime.

### SOLUTION

LOCTITE® PC 9410 Magna-Crete had stronger chemical resistance than their previous method, and bonded better to typical floor repair materials like concrete, brick, and tiles.

### RESULTS

The company saved over \$51,000 in downtime and labor costs, and were able to increase uptime and productivity due to the usage of LOCTITE® PC 9410 Magna-Crete.

