

## **DECLARATION OF PERFORMANCE**

No. 0004

1. Unique identification code of the product-type: Ceresit CM 16 Flex

2. Intended use/es: All internal and external tiling

Manufacturer: 3.

Henkel Building Chemicals Georgia LLC.

4. Authorised representative: N/A

5. System/s of assessment and verification of System 4

constancy of performance:

6a. Harmonised standard/s: EN 12004:2007 + A1:2012

Notified body/ies:

N/A

6b. **European Assessment Document:**  N/A

European Technical Assessment:

N/A

Technical Assessment Body:

N/A

Notified body/is:

N/A

Declared performance/s: 7.

Essential characteristics	Performance	Harmonised technical specification
Bond strength expressed as: Initial tensile adhesive strength Early tensile adhesion strength	≥ 1,0 N/mm²	
Durability of bond strength against climate/heat ageing action expressed as: Tensile adhesion strength after heat aging	≥ 1,0 N/mm²	
Durability of bond strength against water/humidity action expressed as: Tensile adhesion strength after water immersion	≥ 1,0 N/mm²	EN 12004:2007 + A1:2012
Durability of bond strength against freeze-thaw cycles expressed as: Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²	
Release of dangerous substances	NDP	

Appropriate Technical Documentation and/or Specific Technical Documentation: 8. N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Nugzar Jankarashvili	Khatuna Shermadini
Site Manager • AOE/Plant Tbilisi	Lab Assistant • AOE/QM AC Ukraine
(name and function)	(name and function)
J- 18 0 18 18 18 18 18 18 18 18 18 18 18 18 18	6. 3gh grang
(signature) Tbillisi, 24.	(signaturé)
ტეგზარ ჯანყარ შვილა	07.2024
Nug Jankaras hvili (place and da	ate of issue)