

LOCTITE®
TEROSON®

RETAIL CATALOGUE



Henkel

Contents

3 All Purpose Retail Adhesives	8 Gasketing & Sealing	11 Body Filler	13 Cleaners
15 Workshop -Professional Adesive	20 Workshop Aerosol and Lubricants	23 Tapes	

YouTube
Visit our YouTube channel to see our latest videos!

All Purpose Retail Adhesives

LOCTITE® Super Glue is a fast bonding, super strength, instant adhesive with specially engineered formulas and applicators to bond any material. Super Glue Liquids are ideal for penetrating hard-to-bond cracks on non-porous surfaces. Super Glue Gels for vertical surfaces and clean repairs

- Easy-to-use and practical, these glues work on a variety of materials – from wood, rubber, plastic and more – it even works as a leather glue.
- This adhesive not only withstands heavy loads but is also shock resistant and serves as a waterproof glue and heatproof glue, for a huge range of requirements and users.



LOCTITE Super Glue Control Liquid

- This multi-purpose adhesive helps to easily handle any kind of small daily repair job around the house! Providing instant strength, transparent drying technology and an anti-clog cap, LOCTITE Universal ensures durable, long-lasting and invisible repairs.
- Thanks to its self-piercing anti-clog cap, the repair glue is super easy to use and does not dry out any more, ensuring long-term reusability.
- When ready to use ensure surfaces to be joined are clean, completely dry and close fitting. Twist cap clockwise until it locks, then unscrew in an anti-clockwise direction to open. Carefully squeeze a small drop onto one surface. Press the surfaces together and hold until set.
- Replace the cap immediately and store upright in a cool dry place.

IDH No.	Product Description	Pack Size	Box Qty
1620715	LOCTITE Super Glue Control Liquid	3g Tube	24



LOCTITE Super Glue Precision

- This convenient repair adhesive with its extra long nozzle is especially suited for precise applications on hard to reach surfaces. Providing instant strength, transparent drying technology and an anti-clog cap, LOCTITE Precision ensures durable, long-lasting and invisible repairs with an accurate delivery.
- When you are ready to glue, ensure the surfaces you want to bond are clean, dry and close-fitting. Lightly dampen porous surfaces. Simply remove the cap and apply a small quantity of the liquid glue to one surface, press both surfaces together immediately and hold them in place until the bond sets.

IDH No.	Product Description	Pack Size	Box Qty
1621293	LOCTITE Super Glue Precision	5g Bottle	24



LOCTITE Super Glue PowerFlex Gel

- Formulated with cyanoacrylate rubber-infused gel formula, this instant glue allows powerful bonds that are extremely precise even on vertical surfaces and materials that require high flexibility. This transparent glue comes in 3 doses of 1g which make them ideal for unique applications.
- Thanks to its anti-clog cap, the repair glue is easy to use and does not dry out any more, ensuring long-term reusability.
- Before starting, just ensure the surfaces you want to bond are clean, dry and close-fitting. Simply remove the cap and apply a small quantity of the power glue gel to one surface, press both surfaces together immediately and hold them in place until the bond sets.

IDH No.	Product Description	Pack Size	Box Qty
1621078	LOCTITE Super Glue PowerFlex Gel	3g Tube	24



LOCTITE Super Glue Liquid Matic

- The Universal Instant adhesive from the original name in super glue
- High performance, instant power
- Thousands of applications around the car, home, workshop, farm, caravan and boat
- Bonds metals, rubber, wood, leather, china and most plastics

IDH No.	Product Description	Pack Size	Box Qty
1623037	LOCTITE Super Glue Liquid Matic	3g Tube Dispenser	12



LOCTITE Super Glue Easy Brush

- Enables you to easily spread the glue over small and irregular shaped surfaces
- Comes in a spill resistant bottle for safe storage with a built-in brush applicator ensuring ease of application and glue free handling
- Proven superior performance over ordinary super glues, as it sets in seconds with no clamping required and holds stronger on more surfaces
- The liquid formula works well on a variety of porous and non-porous surfaces. It's also resistant to moisture, most chemicals and freezing temperatures. Its powerful formula has been developed to form resilient bonds that then dry transparent to form long lasting invisible bonds.
- When ready to use ensure surfaces are clean, completely dry and close fitting. Twist cap clockwise until it locks, then unscrew in an anti-clockwise direction to open. Carefully squeeze a small drop onto one surface, Press surfaces together and hold until set. Replace the cap immediately and store upright in a cool dry place.

IDH No.	Product Description	Pack Size	Box Qty
1621074	LOCTITE Super Glue Easy Brush	12	12

Key Characteristics

- High Strength
- Health and Safety Product
- Quick Dry
- Non Drip

All Purpose Retail Adhesives



LOCTITE Super Glue All Plastics

- Revolutionary adhesive system that can stick all plastics
- High performance adhesive system for rapid bonding
- 2 part system including primer and adhesive

IDH No.	Product Description	Pack Size	Box Qty
1610142	LOCTITE Super Glue All Plastics	2g Tube & 4ml Pen	12



LOCTITE Glue Remover Gel

- Simple, convenient and effective glue and stain remover
- Removes most household glues including LOCTITE super glue
- Gel formulation for use on vertical surfaces

IDH No.	Product Description	Pack Size	Box Qty
1623766	LOCTITE Glue Remover Gel	5g Tube	12



LOCTITE Super Glue Glass

- High strength transparent adhesive
- Permanently bonds glass to glass and glass to metal
- Dries with clear bond line when exposed to daylight

IDH No.	Product Description	Pack Size	Box Qty
1628817	LOCTITE Super Glue Glass	3g Tube	12



LOCTITE All Purpose Adhesive

- Strong multi-purpose transparent adhesive for larger areas
- Dries with a clean, clear glue line and bonds a wide variety of materials

IDH No.	Product Description	Pack Size	Box Qty
2675783	LOCTITE All Purpose Adhesive	20ml Tube	10



LOCTITE AA 319 Rear View Mirror Bonder

- Unique bonding system for rear view mirrors, car telephone and all window mounted material
- Bonds metal and glass (not plastic) in 30 seconds

IDH No.	Product Description	Pack Size	Box Qty
194088	LOCTITE AA 319 Rear View Mirror Bonder	1 Shot Tube	12



Pritt Blistercard

- The No.1 branded glue stick for paper and card
- Washable, non-toxic and solvent free

IDH No.	Product Description	Pack Size	Box Qty
1456074	Pritt Blistercard	20g Pack	12



Key Characteristics

All Purpose Retail Adhesives



Hot Melt Glue Gun Kit & Sticks

- For instant bonding on larger repairs, DIY jobs and craft/hobby work
- One stick for all jobs
- Suitable for wood, metal, fabric, leather, ceramics and most plastics

IDH No.	Product Description	Pack Size	Box Qty
2675526	Hot Melt Glue Gun Kit & Sticks	Kit	6



Hot Melt Glue Sticks

- For instant bonding on larger repairs, DIY jobs and craft/hobby work
- One stick for all jobs
- Suitable for wood, metal, fabric, leather, ceramics and most plastics


IDH No.	Product Description	Pack Size	Box Qty
2675732	Hot Melt Glue Sticks	Large Sticks	6



No More Nails Kiwi Pack

- High Strength adhesive which eliminates the need for nails or screws
- Bonds wood, plastic, brick, metal, glass, ceramics and plaster
- Solvent-free adhesive that fills minor gaps, dries white and can be overpainted

IDH No.	Product Description	Pack Size	Box Qty
2675563	No More Nails Kiwi Pack	200ml can	12



No More Nails Cartridge Ultra

- High Strength adhesive which eliminates the need for nails or screws
- Bonds wood, plastic, brick, metal, glass, ceramics and plaster
- Solvent-free adhesive that fills minor gaps, dries white and can be overpainted


IDH No.	Product Description	Pack Size	Box Qty
1963628	No More Nails Cartridge Ultra	310ml Cartridge	12



No More Nails Tube Ultra

- High Strength adhesive which eliminates the need for nails or screws
- Bonds wood, plastic, brick, metal, glass, ceramics and plaster
- Solvent-free adhesive that fills minor gaps, dries white and can be overpainted

IDH No.	Product Description	Pack Size	Box Qty
2729908	No More Nails Tube Ultra	Standard Tube	12



No More Big Gaps

- High performance expanding foam filler, Perfect for all types of big gaps, suitable for interior and exterior use
- 360 application. Suitable for filling, bonding, sealing and insulation large, awkward and irregular gaps

IDH No.	Product Description	Pack Size	Box Qty
2675758	No More Big Gaps	500ml Can	12



Key Characteristics

All Purpose Retail Adhesives



LOCTITE 243 - Medium Strength Threadlocker (locks and seals)

- General purpose threadlocker that provides a medium strength bond allowing disassembly using everyday tools
- Works on all metals, including passive substrates such as stainless steel, aluminium and plated surfaces
- It is proven to be tolerant of minor contamination due to industrial oils, e.g., motor oils, corrosion prevention oils and cutting fluid
- Prevents loosening on any vibrating assemblies, e.g. pumps, gear boxes

IDH No.	Product Description	Pack Size	Box Qty
2648156	LOCTITE 243 - Medium Strength Threadlocker (locks and seals)	5ml Blister card	12



LOCTITE 2400 Health & Safety Friendly (locks and seals) Medium Strength Threadlocker

- Medium Strength allowing disassembly using everyday tools
- No Health and safety labels
- Works on all metals, including passive substrates such as stainless steel, aluminium and plated surfaces
- Prevents loosening on any vibrating assemblies, e.g. pumps, gear boxes


IDH No.	Product Description	Pack Size	Box Qty
1960969	LOCTITE 2400 Health & Safety Friendly (locks and seals) Medium Strength Threadlocker	5ml Bottle	12



LOCTITE 2700 Health & Safety Friendly (stud and bearing) High Strength Threadlocker

- High strength
- Permanent locking removal by heat only
- No Health and safety labels
- Works on all metals, including passive substrates such as stainless steel, aluminium and plated surfaces
- Prevents loosening on any vibrating assemblies, e.g. pumps, gear boxes

IDH No.	Product Description	Pack Size	Box Qty
1960972	LOCTITE 2700 Health & Safety Friendly (stud and bearing) High Strength Threadlocker	5ml Bottle	12



UniBond Repair Extreme

- Resists shock, water and temperature extremes
- Ideal for a multitude of surfaces
- Transparent and odourless
- Flexible multi purpose adhesive with patented FLEXTEC™ technology, UniBond Repair Extreme will repair and bond virtually all surfaces and withstand the most extreme weather, whilst providing an outstanding bond even when applied in damp conditions

IDH No.	Product Description	Pack Size	Box Qty
743676	UniBond Repair Extreme	20g Tube	12



Plastic Padding Super Steel Epoxy-Weld

- Suitable for metal, wood, china, stone, glass and leather
- Working time 5 min, cure time 10 min
- Max. temperature 315°C (<100 continuous)
- Ideal for general emergency repairs around the car, home, garden, farm and boat
- Sets like steel
- Seals, repairs, bonds, fixes and replaces

IDH No.	Product Description	Pack Size	Box Qty
638167	Plastic Padding Super Steel Epoxy-Weld	2 x 25g Tubes	12



Key Characteristics

All Purpose Retail Adhesives



Plastic Padding FASTSET EPOXY

- Amber coloured, dual cartridge fast cure epoxy
- Suitable for use on wood, china, stone, glass, metal and rubber

IDH No.	Product Description	Pack Size	Box Qty
360331	Plastic Padding FASTSET EPOXY	50ml Tube	6



LOCTITE SF 7503 Rust Remedy

- Converts rust to a safe, stable compound and prevents further spreading paintable once set
- Powerful industry-proven formulation
- For automotive and household use

IDH No.	Product Description	Pack Size	Box Qty
231051	LOCTITE SF 7503 Rust Remedy	90ml Bottle	12



Key Characteristics

Gasketing and Sealing



LOCTITE SI 5980 Silicone Black Gasket Oil Resistant

- Flange sealant for flexible flanges, typical applications Oil Sump and timing gear covers
- Good glycol resistance
- Excellent oil resistant
- Black colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED
1718284	LOCTITE SI 5980 Silicone Black Gasket Oil Resistant	40ml Blister	12	



LOCTITE SI 5990 Silicone Copper Gasket High Temp' Resistant

- Suitable for all kinds of surfaces including metals, • plastics
- High temperature resistance
- Electrical insulating product
- Oil resistant
- Copper colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED
1716588	LOCTITE SI 5990 Silicone Copper Gasket High Temp' Resistant	40ml Blister	12	



LOCTITE SI 5940 S/Flex Black - Silicone Sealant

- Fully Waterproof, permanently flexible silicone sealant
- Suitable for windscreen sealing, weatherproofing and insulating electrical connections

IDH No.	Product Description	Pack Size	Box Qty
1123347	LOCTITE SI 5940 S/Flex Black - Silicone Sealant	40ml Blister	12



LOCTITE SI 595 S/Flex Clear - Silicone Sealant

- Fully Waterproof, permanently flexible silicone sealant
- Suitable for windscreen sealing, weatherproofing and insulating electrical connections

IDH No.	Product Description	Pack Size	Box Qty
1123422	LOCTITE SI 595 S/Flex Clear - Silicone Sealant	40ml Blister	12



LOCTITE MR 5922 Gasket Dressing

- Improves the sealing performance of old and new pre-cut compression gaskets made from paper, cork, felt etc.
- Slow curing paste.
- Sets to a permanently flexible, non hardening film.
- Suitable for parts that require disassembly.
- Resistant to gasoline, kerosene, lubricants, hot and cold water, antifreeze mixtures, weak acids, alkalis and vapours.
- Temperature resistant -55°C to +200°C. Resistant to high pressures.
- Applications; on engine and gearbox. For sealing/dressing flanges with old and new pre-cut compression gaskets.
- Ideal for part assembly after repairs.

IDH No.	Product Description	Pack Size	Box Qty
142274	LOCTITE MR 5922 Gasket Dressing	60ml Tube	12



Key Characteristics

Gasketing and Sealing



LOCTITE SI 5660 Silicone Grey Water & Glycol Resistant

- Flange sealant for flexible flanges typical applications, water pumps , transmissions and cast metal housings
- Excellent glycol resistance
- Oil resistant
- Grey colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED
2064521	LOCTITE SI 5660 Silicone Grey Water & Glycol Resistant	100ml Tube	12	



LOCTITE SI 5660 Silicone Grey Water & Glycol Resistant

- Flange sealant for flexible flanges typical applications, water pumps , transmissions and cast metal housings
- Excellent glycol resistance
- Oil resistant
- Grey colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED
2326228	LOCTITE SI 5660 Silicone Grey Water & Glycol Resistant	100ml Power Can	6	



LOCTITE SI 5926 Instant Gasket Blister Card - Blue

- Multi-purpose flexible silicone sealant. Can be used on metal, plastic and painted parts, typical applications include valve covers, timing gear covers, differential covers, oil pans, transmission pans, water pumps, and thermostat housings
- Resists vibration, thermal expansion and contraction
- Operating temperature range of -54 °C to +150 °C
- Blue colour

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED
1123349	LOCTITE SI 5926 Instant Gasket Blister Card - Blue	40ml Tube	12	



LOCTITE SI 5660 Silicone Gasket Grey Water & Glycol Resistant

- Flange sealant for flexible flanges, typical applications, water pumps, transmissions and cast metal housings
- Excellent glycol resistance
- Oil resistant
- Grey colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED
1718240	LOCTITE SI 5660 Silicone Gasket Grey Water & Glycol Resistant	40ml Blister 40ml Tube	12 12	



LOCTITE SI 5980 Silicone Black Oil Resistant

- Flange sealant for flexible flanges typical applications Oil Sump and timing gear covers
- Good glycol resistance
- Excellent oil resistant
- Black colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED
2064235	LOCTITE SI 5980 Silicone Black Oil Resistant	100ml Tube	12	



Key Characteristics

Gasketing and Sealing



LOCTITE SI 5980 Silicone Black Oil Resistant

- Flange sealant for flexible flanges typical applications Oil Sump and timing gear covers
- Good glycol resistance
- Excellent oil resistant
- Black colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED	+
2327036	LOCTITE SI 5980 Silicone Black Oil Resistant	100ml Power Can	6	+	+



LOCTITE SI 5990 Silicone Copper High Temp' Resistant

- Suitable for all kinds of surfaces including metals, • plastics OEM Specs
- High temperature resistance
- Electrical insulating product
- Oil resistant
- Copper colour
- Leading in health & safety features

IDH No.	Product Description	Pack Size	Box Qty	O.E.M. SPECIFIED	+
2064108	LOCTITE SI 5990 Silicone Copper High Temp' Resistant	100ml Tube	12	+	+



LOCTITE SI 595 Silicone Clear Tube

- An excellent adhesive sealant for mechanical assemblies.
- Typical applications include electrical insulation, protection of leads from mechanical shock, trim bonding, and sealing of ductwork, vents, flues, doors, and windows.

IDH No.	Product Description	Pack Size	Box Qty	+
2061823	LOCTITE SI 595 Silicone Clear Tube	100ml Tube	12	+



LOCTITE SI 5130 Silicone White Tube - Silicone Paste

- Silicone paste designed for superior bonding and sealing properties to most surfaces (not recommended for concrete).
- It resists ageing, weathering and thermal cycling without hardening, shrinking or cracking.
- It is formulated to withstand extreme temperature cycling, UV light and ozone.

IDH No.	Product Description	Pack Size	Box Qty	+
2053643	LOCTITE SI 5130 Silicone White Tube - Silicone Paste	80g Tube	12	+



LOCTITE MR 3020 High Tack - Gasket adhesive

- Adhesive Sealant for holding pre-cut gaskets in place during assembly
- Use with cut gaskets
- Easy application from aerosol can
- Can be used with rubber, cork, paper, metal, asbestos and similar gaskets
- Dries to form a highly tacky, elastomeric film
- Remains tacky indefinitely
- Holds gaskets in place during assembly, even when vertically oriented
- Improves gasket performance considerably
- Petrol, diesel, water, grease and oil-resistant
- Does not contain ozone-depleting solvents
- Very economical - one can is sufficient for multiple applications

IDH No.	Product Description	Pack Size	Box Qty
458645	LOCTITE MR 3020 High Tack - Gasket adhesive	400ml - workshop	12



Key Characteristics

Body Filler



TEROSON UP 110 Elastic Body Filler

- Elastic
- Outstanding flexibility
- Eliminates cracking and flaking
- Can repair dents, scratches, pinholes and imperfections
- Can be used for reshaping

IDH No.	Product Description	Pack Size	Box Qty
2268974	TEROSON UP 110 Elastic Body Filler	329g	6



TEROSON UP 120 Leak Fix

- All purpose filler
- Resistance to oil, water, most common chemicals and high temperatures
- Suitable for use on steel, aluminium, galvanized surfaces, glass fibre, copper and tin

IDH No.	Product Description	Pack Size	Box Qty
2268369	TEROSON UP 120 Leak Fix	326g	6



TEROSON UP 130 Chemical Metal

- Multi-purpose
- Sets hard like metal
- Resistance to water, salt water, oil, fuel and to most weak acids and chemicals

IDH No.	Product Description	Pack Size	Box Qty
2268398	TEROSON UP 130 Chemical Metal	321g	6
2268385		739g	



TEROSON UP 150 Glass Fibre Filler

- Unsaturated polyester body filler used for bridging and repairing holes.
- It can be used on steel, aluminum, galvanized surfaces and glass fiber.

IDH No.	Product Description	Pack Size	Box Qty
2268977	TEROSON UP 150 Glass Fibre Filler	332g	6
2246513		745g	



TEROSON UP 190 Hardener

- Peroxide hardener which is designed for TEROSON body fillers within the all-purpose and professional ranges.

IDH No.	Product Description	Pack Size	Box Qty
2293833	TEROSON UP 190 Hardener	15g	6



TEROSON UP 610 Marine Filler

- TEROSON® UP 610 is the universal unsaturated polyester body filler used for marine applications.
- It repairs transom/stern damages, stress cracks, keel and rudder surfaces, redundant holes, engine mountings, damaged and pitted propellers, cracks and holes on hulls and superstructures, damages caused by osmosis or crazing, gaps between hull and deck and worn and damaged superstructures.

IDH No.	Product Description	Pack Size	Box Qty
2269158	TEROSON UP 610 Marine Filler	341g	6
2246438		791g	



Key Characteristics

Body Filler



TEROSON UP 230 - Lightweight Easy Sand body filler

- Teroson® UP 230 is an easy-to-sand, lightweight unsaturated polyester body filler used for repairing dents, scratches, pinholes, imperfections and for reshaping. It can be used on steel, aluminium, galvanized surfaces and glass fibre.

IDH No.	Product Description	Pack Size	Box Qty
2246394	TEROSON UP 230 - Lightweight Easy Sand body filler	535g	6



TEROSON UP 270 Flowable Self Levelling Stopper

- Teroson® UP 270 is a super smooth and easy to spread unsaturated polyester body filler with low viscosity and self-leveling properties.
- It repairs scratches, pinholes and other imperfections. It can be used on steel, aluminium, galvanized surfaces and fibreglass.

IDH No.	Product Description	Pack Size	Box Qty
2263729	TEROSON UP 270 Flowable Self Levelling Stopper	558g	6



TEROSON VR 315 - Sprayable Filler/High Build Primer

- Teroson® VR 315 FILLER is a grey, fast-drying acrylic filler to even out small imperfections, scratches, and sanding marks, creating a smooth surface on filled substrates for subsequent painting.
- It is used on filled surfaces such as steel, galvanized steel, various plastics (PVC, PPO/PA, ABS, PC/PBT), wood and cured 2K filler.

IDH No.	Product Description	Pack Size	Box Qty
211834	TEROSON VR 315 - Sprayable Filler/High Build Primer	400ml	6



TEROSON UP 620 - Gelcoat Polyester Marine Filler

- Teroson® UP 620 is a gelcoat unsaturated polyester body filler used for restoring the original surface finish to boat hulls and glass fibre panels.
- It repairs osmosis blisters and minor surface damage. It can be used on glass fibre and gelcoat finishes.
- Once set, it is waterproof and may be overpainted if required.

IDH No.	Product Description	Pack Size	Box Qty
2269157	TEROSON UP 620 - Gelcoat Polyester Marine Filler	241g	6

CLEANERS



LOCTITE SF 7850 Citrus Pumice Workshop Hand Cleaner

- Natural extract base
- Free of mineral oils
- Biodegradable
- Contains premium skin conditioners
- Works with or without water
- Removes ground-in dirt, grease, grime, and oil

IDH No.	Product Description	Pack Size	Box Qty
2098250	LOCTITE SF 7850 Citrus Pumice Workshop Hand Cleaner	400ml Bottle	12
2098251		3l	4
1658212		10l	2



LOCTITE SF 7840 General Industrial Cleaner

- Biodegradable, can be applied via pressure washer
- Solvent free, non-toxic, and non-flammable
- Can be diluted with water
- Removal of grease, oil, cutting fluids and workshop grime

IDH No.	Product Description	Pack Size	Box Qty
1427770	LOCTITE SF 7840 General Industrial Cleaner	750ml	12
1427775		5l	4
1427776		20l	1



LOCTITE SF 7855 Paint, Resin and Adhesive Heavy Duty Hand Cleaner

- Biodegradable
- Non-toxic
- Excellent removal of paint, resin and adhesives from skin
- Conditioning components allow frequent use without affecting the skin

IDH No.	Product Description	Pack Size	Box Qty
1918668	LOCTITE SF 7855 Paint, Resin and Adhesive Heavy Duty Hand Cleaner	400ml Bottle	12
1918673		1.75l	1



LOCTITE SF 7063 Cleaner Aerosol

- Solvent-based general parts cleaner
- Recommended for use prior to adhesive bonding and sealing applications
- Leaves no residue
- Removal of greases, oils, lubrication fluids, metal cuttings and fines from all surfaces

IDH No.	Product Description	Pack Size	Box Qty
2098749	LOCTITE SF 7063 Cleaner Aerosol	400ml Can	1



Key Characteristics



Key Characteristics



LOCTITE SF 7200 Gasket Remover (Chisel) Aerosol

- Provides excellent removal of cured gaskets, both liquid sealants and traditional gaskets in 10 to 15 minutes
- Minimal scraping
- Usable on most types of surface

IDH No.	Product Description	Pack Size	Box Qty
2099006	LOCTITE SF 7200 Gasket Remover (Chisel) Aerosol	400ml Can	12



TEROSON VR 100 Glass Cleaner

- TEROSON® VR 100 glass cleaner is suitable for all surfaces of the vehicle, especially glass and plexiglass.
- It has been formulated with nano technology.
- This revolutionary technology protects the surface against adhesion of soil.
- The nano particles leave an invisible and anti droplet layer. So, the surface remains longer shining, clean and stripe free.
- Has an efficient degreasing action, and is self drying without leaving any spot on the cleaned surface.
- Application with a lint-free cloth.

IDH No.	Product Description	Pack Size	Box Qty
2012089	TEROSON VR 100 Glass Cleaner	1kg	12



LOCTITE 638 High Strength Retaining Compound (Sleeve and Bush)

- LOCTITE® 638 is designed for the bonding of cylindrical fitting parts, particularly with narrow bond gaps approaching 0.25 mm.
- The product cures when confined in the absence of air between close-fitting metal surfaces and prevents loosening and leakage due to shock and vibration.
- It not only works on active metals but also on passive substrates, exhibiting robust cure performance.
- The product offers high-temperature performance and good oil tolerance, and tolerates minor surface contaminants.

IDH No.	Product Description	Pack Size	Box Qty
1918981	LOCTITE 638 High Strength Retaining Compound (Sleeve and Bush)	10ml	12



LOCTITE 638 High Strength Retaining Compound (Sleeve and Bush)

- LOCTITE® 638 is designed for the bonding of cylindrical fitting parts, particularly with narrow bond gaps approaching 0.25 mm.
- The product cures when confined in the absence of air between close-fitting metal surfaces and prevents loosening and leakage due to shock and vibration.
- It not only works on active metals but also on passive substrates, exhibiting robust cure performance.
- The product offers high-temperature performance and good oil tolerance, and tolerates minor surface contaminants.

IDH No.	Product Description	Pack Size	Box Qty
1803365	LOCTITE 638 High Strength Retaining Compound (Sleeve and Bush)	50ml	12



LOCTITE 561 Pipe Sealant Stick Low Strength

- Cures rapidly to provide immediate low pressure sealing.
- Controlled lubricity prevents galling and protects mated threaded areas from rust and corrosion.
- Its creamy semi-solid consistency allows for optimum control during application.
- Applications: Exhaust bolts, Brake calliper bolts and steam valve threads.

IDH No.	Product Description	Pack Size	Box Qty
	LOCTITE 561 Pipe Sealant Stick Low Strength	19g Pack	15



LOCTITE LB 8065 Copper Antiseize Stick

- C5 -A Copper based anti-seize formula, now available with less mess in a convenient stick.
- Protects metal parts from rust, corrosion, galling and seizing to temperatures up to 980°C.
- Applications: Exhaust bolts, brake calliper bolts and steam valve threads.

IDH No.	Product Description	Pack Size	Box Qty
525380	LOCTITE LB 8065 Copper Antiseize Stick	20g Pack	15



LOCTITE LB 8065 Copper Antiseize Stick

- C5 -A Copper based anti-seize formula, now available with less mess in a convenient stick.
- Protects metal parts from rust, corrosion, galling and seizing to temperatures up to 980°C.
- Applications: Exhaust bolts, brake calliper bolts and steam valve threads.

IDH No.	Product Description	Pack Size	Box Qty
525392	LOCTITE LB 8065 Copper Antiseize Stick Blistercard	20g Pack	12



Key Characteristics



Key Characteristics



LOCTITE 248 Medium Strength Stick Blister Card (Loc and Seal)

- Convenient stick format prevents dripping
- Prevents loosening on vibrating assemblies, e.g. pumps, gear boxes or presses
- Works on all metals, including passive substrates (e.g. stainless steel, aluminium, plated surfaces)
- Proven to tolerate minor contamination by industrial oils, e.g. engine oils, corrosion prevention oils and cutting fluids
- Permits disassembly with hand tools

IDH No.	Product Description	Pack Size	Box Qty	
1715105	LOCTITE 248 Medium Strength Stick Blister Card (Loc and Seal)	9g	12	



Metal Magic Stick 3463 (2 Part steel filled Emergency repair putty)

- Steel-filled kneadable epoxy stick
- For the emergency repair of tanks, pipes and castings
- Operating temperature range -55 °C to +120 °C.

IDH No.	Product Description	Pack Size	Box Qty	
265628	Metal Magic Stick 3463 (2 Part steel filled Emergency repair putty)	114g Tube	1	



LOCTITE 401 Industrial Strength Instant Adhesive

- Surface Insensitive formulation creates a permanent bond with virtually any material
- Low viscosity instant cure
- Non-clog nozzle for easy, accurate application

IDH No.	Product Description	Pack Size	Box Qty	
1919341	LOCTITE 401 Industrial Strength Instant Adhesive	20g Pack	12	



LOCTITE 406 Rapid Plastic and Rubber Adhesive

- Creates a permanent bond with virtually any material Rapid bonding of plastic & rubber, including EPDM
- Low viscosity instant cure
- Non-clog nozzle for easy, accurate application

IDH No.	Product Description	Pack Size	Box Qty	
1919335	LOCTITE 406 Rapid Plastic and Rubber Adhesive	20g Pack	12	



LOCTITE 435 Toughened Clear Instant Adhesive

- Toughened It has high resistance to impact and shock loads, high peel strength and is suitable for bonding plastics, rubber, metals, porous and absorbent substrates and acidic surfaces. Good resistance in humid environments.
- Fast Curing adhesive
- Colourless and transparent
- Also for porous and absorbent substrates and acidic surfaces
- Low Viscosity

IDH No.	Product Description	Pack Size	Box Qty	
871787	LOCTITE 435 Toughened Clear Instant Adhesive	20g Pack	12	



LOCTITE 660 - Emergency Repair Quick metal (always recommend 7649 activator)

- LOCTITE® 660 is designed for the bonding of cylindrical fitting parts, particularly where bond gaps upto 1mm occurs without the need for remachining
- The product cures when confined in the absence of air between close-fitting metal surfaces and prevents loosening and leakage due to shock and vibration.
- LOCTITE 660 exhibits excellent gap cure characteristics and is also suitable for retaining shims.

IDH No.	Product Description	Pack Size	Box Qty	
267328	LOCTITE 660 - Emergency Repair Quick metal (always recommend 7649 activator)	50ml	12	



Super Glue Kit

- Universal high strength adhesive with aerosol accelerator
- Highly viscous formula
- Suitable for virtually all materials
- Accelerator cures excess adhesive for tack-free bond line

IDH No.	Product Description	Pack Size	Box Qty	
234470	Super Glue Kit	20g & 25ml	12	



LOCTITE 577 Medium Strength Brake and Airline sealant

- Medium-strength, general purpose thread sealant for sealing metal threads
- Suitable for all metals
- Instant low pressure seal
- Excellent chemical resistance
- Locks connection against vibration-induced loosening and other stresses
- Easy to apply
- Cures on active and inactive metals
- NSF P1 Reg. No. 123001
- DVGW Approval (EN 751-1): DVGW Reg. No. NG-5146CQ0312

IDH No.	Product Description	Pack Size	Box Qty	
2068186	LOCTITE 577 Medium Strength Brake and Airline sealant	50ml	12	



LOCTITE 243 Medium Strength Blue Threadlocker (Lock n seal)

- General purpose threadlocker that provides a medium strength bond allowing disassembly using everyday tools
- Works on all metals, including passive substrates such as stainless steel, aluminium and plated surfaces
- It is proven to be tolerant of minor contamination due to industrial oils, e.g., motor oils, corrosion prevention oils and cutting fluid
- Prevents loosening on any vibrating assemblies, e.g. pumps, gear boxes

IDH No.	Product Description	Pack Size	Box Qty	
1335884	LOCTITE 243 Medium Strength Blue Threadlocker (Lock n seal)	50ml	12	



LOCTITE 270 High Strength Threadlocker (Stud and Bearing)

- High strength
- Permanent locking removal by heat only
- No Health and safety labels
- Works on all metals, including passive substrates such as stainless steel, aluminium and plated surfaces
- Prevents loosening on any vibrating assemblies, e.g. pumps, gear boxes

IDH No.	Product Description	Pack Size	Box Qty	
1918245	LOCTITE 270 High Strength Threadlocker (Stud and Bearing)	10ml	12	



Key Characteristics



Key Characteristics



LOCTITE 574 Multi Gasket

- Makes any size or shape of gasket LOCTITE® 574 seals close-fitting joints between rigid metal faces and flanges. The product cures when confined in the absence of air between close-fitting metal surfaces. It provides resistance to low pressures immediately after assembly. Typically used as a form-in-place gasket on rigid flanged connections. The nature of LOCTITE 574 reduces the migration of liquid product after application to the substrate. It has a high oil tolerance and excellent water and glycol resistance.
- Seals flanges on all rigid metal parts
- 100% seal prevents leakage and corrosion and strengthens assembly

IDH No.	Product Description	Pack Size	Box Qty	
234534	LOCTITE 574 Multi Gasket	50ml	12	



LOCTITE 518 - Flange Sealant Pen

- LOCTITE® 518 cures when confined in the absence of air between close-fitting metal surfaces.
- It is an anaerobic gasketing material designed for use on rigid iron, aluminum, and steel flanged mating surfaces.
- LOCTITE 518 fills gaps up to 0.25mm and forms a flexible, chemical-resistant seal that will not tear or decay. Parts disassemble easily, even after extended service.
- Typical applications include sealing close-fitting joints between rigid metal faces and flanges.
- It is also used as a formed-in-place gasket on rigid flanged connections, e.g. transmissions and motor housings.

IDH No.	Product Description	Pack Size	Box Qty	
2392090	LOCTITE 518 - Flange Sealant Pen	25ml	12	



LOCTITE HY 4070 - 2k Universal Bonder

- LOCTITE® HY 4070 is a 2-part, clear to pale yellow cyanoacrylate/acrylic hybrid universal bonder that provides a fast fixture at room temperature in bond gaps up to 0.2 in (5 mm).
- Temp resistant to 120C
- It works well on various substrates including most plastics, rubbers and metals. It is used where complete cure of excess adhesive as well as temperature and moisture resistance is required.
- Best application results are achieved with LOCTITE cyanoacrylate mixing nozzle (to suit HY 4070 and LOCTITE 3090).

IDH No.	Product Description	Pack Size	Box Qty	
2237457	LOCTITE HY 4070 - 2k Universal Bonder	11g	12	



LOCTITE 3090 Fast Curing Clear gap fill instant adhesive

- LOCTITE® 3090 is a 2-component, fast curing, gap filling adhesive with excellent bonding characteristics, making it suitable for a variety of substrates incl. plastics, rubbers and metals. Typical applications, Plastic Lugs, Brackets, Alloy Wheel Repairs, can be sanded and painted
- It is designed for the assembly of parts with varying or undefined bond gaps up to 5 mm, or for applications where the complete cure of excess adhesive is a must.
- The gel consistency prevents adhesive flow even on vertical surfaces. Also suited to bonding porous materials such as wood, paper, leather and fabric.

IDH No.	Product Description	Pack Size	Box Qty	
1379599	LOCTITE 3090 Fast Curing Clear gap fill instant adhesive	11g	12	



LOCTITE Double Bubble 5 minute Epoxy

- LOCTITE® EA Double Bubble is an epoxy which bonds to a wide variety of materials (i.e. wood, metals, plastics and ceramics) and cures rapidly to give handling strength in approximately 5 minutes.
- Packed in a handy sachet and supplied complete with a mixing stick and pallet, this adhesive is readily suited to the rapid assembly of small components or to performing fast and effective repair work.

IDH No.	Product Description	Pack Size	Box Qty	
2015058	LOCTITE Double Bubble 5 minute Epoxy	3g	50	




Key Characteristics



TEROSON MS 9220 Universal Power Adhesive

- TEROSON® MS 9220 is a solvent- and isocyanate-free silane-modified adhesive/sealant with exceptional bonding and sealing properties for bonding of various substrates such as stainless steel, aluminium and other metals, plastics, wood and painted surfaces. Typical application areas, Spoilers, Skirts, Bodykits, Crash Bars. Does not shrink
- The skin formation time is 15 min.
- Use any type of professional manual or air dispensing tool with a piston rod for application;

IDH No.	Product Description	Pack Size	Box Qty	
2486102	TEROSON MS 9220 Universal Power Adhesive	310ml	12	



LOCTITE SF 7414 Torque Marque - Blue Tamper Proof Paste

- LOCTITE® SF 7414 is a blue, high viscosity, solvent-based fast drying paste used to visually detect any movement in the adjustment of parts.
- The product has been developed for use on compression fittings, studs, nuts, parts and assemblies after they have been set to the correct torque, tension or position, thus providing an inexpensive method for warranty protection.
- It demonstrates excellent adhesion to metals.

IDH No.	Product Description	Pack Size	Box Qty	
1269219	LOCTITE SF 7414 Torque Marque - Blue Tamper Proof Paste	50ml	48	



LOCTITE EA 3430 A&B 5 min 2 part Epoxy

- LOCTITE® EA 3430 is a five-minute, toughened 2-component epoxy adhesive that ensures an optically clear bond line.
- The product develops high strength on a wide range of substrates and is water resistant.
- This adhesive is a general purpose bonder and ideal for many DIY applications. Due to the very clear bond line, it is also the product of choice for bonding glass, decorative panels and display.
- The medium viscosity and fast fixture time at room temperature ensure easy application.

IDH No.	Product Description	Pack Size	Box Qty	
142517	LOCTITE EA 3430 A&B 5 min 2 part Epoxy	24ml	12	



LOCTITE EA 3450 2 Component Epoxy

- LOCTITE® EA 3450 is a two component epoxy adhesive which cures rapidly at room temperature after mixing.
- It is a metal bonding adhesive which develops high strength.
- The gap filling properties make this adhesive system suitable for rough and poorly fitting surfaces made from metal, ceramic, rigid plastics or wood.
- Applications include bonding aluminum window frames and GRP panels.

IDH No.	Product Description	Pack Size	Box Qty	
1897383	LOCTITE EA 3450 2 Component Epoxy	25ml	30	



LOCTITE 406 O-Ring Kit

- The LOCTITE® 406 O-RING Kit is an emergency repair kit for making replacement O-rings on the spot
- It is easy to handle and ready for use in just a few seconds. The integrated LOCTITE® 406 creates a strong bond line as strong as the rubber itself
- The kit contains five different sizes of nitrile rubber cord, a splicing jig, a safety knife and 20 g of LOCTITE 406. All you need!

IDH No.	Product Description	Pack Size	Box Qty	
480166	LOCTITE 406 O-Ring Kit	Kit	5	



Key Characteristics



LOCTITE SF 7063 Cleaner Aerosol

- Solvent-based general parts cleaner
- Provides excellent removal of cured gaskets, both liquid sealants and traditional gaskets in 10 to 15 minutes
- Leaves no residue
- Removal of most greases, oils, lubrication fluids, metal cuttings and fines from all surfaces

IDH No.	Product Description	Pack Size	Box Qty
2098749	LOCTITE SF 7063 Cleaner Aerosol	400ml Can	1



LOCTITE SF 7200 Gasket Remover (Chisel) Aerosol

- Provides excellent removal of cured gaskets, both liquid sealants and traditional gaskets in 10 to 15 minutes
- Minimal scraping
- Usable on most types of surface

IDH No.	Product Description	Pack Size	Box Qty
2099006	LOCTITE SF 7200 Gasket Remover (Chisel) Aerosol	400ml Can	12



LOCTITE LB 8018 Solvo Rust Universal Penetrating lubricant

- Multi-purpose solvo rust
- Clear mineral oil in an aerosol can
- Immediate penetration
- Freed parts remain lubricated and protected from corrosion
- Does not contain CFCs

IDH No.	Product Description	Pack Size	Box Qty
2101563	LOCTITE LB 8018 Solvo Rust Universal Penetrating lubricant	400ml Can	12



LOCTITE LB Freeze and Release 8040

Recommended for use on corroded or fused metal components Shock Freezing to -40c , releases rusted and corroded seized components. Wicks directly into corrosion via capillary action, released parts remain protected from corrosion

IDH No.	Product Description	Pack Size	Box Qty
760225	LOCTITE LB Freeze and Release 8040	400ml Can	12



Super Lube Multipurpose Synthetic lubricant

- Multi-purpose synthetic lubricant. Contains PTFE, for added lubricity, giving superior anti-wear performance over conventional greases and oils
- Odourless, clean and non-staining

IDH No.	Product Description	Pack Size	Box Qty
399419	Super Lube Multipurpose Synthetic lubricant	375ml	12



Super Lube Grease

- Multi-purpose synthetic grease lubricant. Contains PTFE, for added lubricity, giving superior anti-wear performance over conventional greases and oils
- Odourless, clean and non-staining

IDH No.	Product Description	Pack Size	Box Qty
399420	Super Lube Grease	85g	12



Key Characteristics



Super Grease

- Multi-purpose synthetic grease lubricant. Contains PTFE, for added lubricity, giving superior anti-wear performance over conventional greases and oils
- Odourless, clean and non-staining

IDH No.	Product Description	Pack Size	Box Qty
399421	Super Grease	400g	12



Super Lube Oil (Pen application)

- Multi-purpose synthetic grease lubricant. Contains PTFE, for added lubricity, giving superior anti-wear performance over conventional greases and oils
- Odourless, clean and non-staining

IDH No.	Product Description	Pack Size	Box Qty
399422	Super Lube Oil (Pen application)	7g	12



LOCTITE SF 7649 Activator (Activator for anaerobic threadlockers, gasketing and retaining products)

- Must be use with LOCTITE 660 quick metal
- LOCTITE® SF 7649 is designed to accelerate the curing speed of LOCTITE anaerobic threadlocking, retining and gasketing adhesives and sealants without any significant loss of joint strength.
- It is especially recommended for applications with passive metals or inert surfaces and with large bond gaps.
- LOCTITE SF 7649 offers good performance at low cure temperatures, and is recommended when the application temperature is below 15°C.

IDH No.	Product Description	Pack Size	Box Qty
142479	LOCTITE SF 7649 Activator (Activator for anaerobic threadlockers, gasketing and retaining products)	150ml	12



LOCTITE MR 3020 Red Gasket Dressing

- Adhesive Sealant for holding pre-cut gaskets in place during assembly
- Use with cut gaskets
- Easy application from aerosol can
- Can be used with rubber, cork, paper, metal, asbestos and similar gaskets
- Dries to form a highly tacky, elastomeric film
- Remains tacky indefinitely
- Holds gaskets in place during assembly, even when vertically oriented
- Improves gasket performance considerably
- Petrol, diesel, water, grease and oil-resistant
- Does not contain ozone-depleting solvents
- Very economical - one can is sufficient for multiple applications

IDH No.	Product Description	Pack Size	Box Qty
458645	LOCTITE MR 3020 Red Gasket Dressing	400ml	12



TEROSON VR 5000 Vehicle Body Contact Adhesive Spray

- TEROSON® VR 5000 is a styrene butadiene rubber (SBR)-based vehicle body contact adhesive spray.
- It is a pressure-sensitive, multi-purpose product with a high degree of initial strength.
- Typical applications include bonding of interior materials such as textiles, foams, rubber, insulating materials, PE films / sheets, leather, cardboard, metal, wood or polyester.
- Surface preparation with TEROSON® VR 10 is recommended.

IDH No.	Product Description	Pack Size	Box Qty
860240	TEROSON VR 5000 Vehicle Body Contact Adhesive Spray	400ml	12



Key Characteristics



TEROSON WX 215 Cavity Spray Wax

- TEROSON® WX 215 is a cavity spray wax and an anti-corrosion agent with excellent creeping qualities.
- It is ideal for treating small isolated areas and can be used on coatings based on PVC, PVC wax, bitumen/rubber and rubber/resin.
- The product is OEM specified. It is characterised by high temperature resistance.
- The extension spray tube provided with the can provides added reach into cavities, e.g. in doors and the engine compartment.

IDH No.	Product Description	Pack Size	Box Qty
794224	TEROSON WX 215 Cavity Spray Wax	500ml	12



LOCTITE LB 8201 Universal Lubricant

- LOCTITE® LB 8201 is a universal penetrating liquid which frees, lubricates, cleans, dries and prevents corrosion on all machinery.
- The product does not contain silicone. It is used to free seized or corroded parts such as threaded fasteners, hinges and cylindrical joints.
- It provides light lubrication and displaces moisture from damp electrical devices to leave a protective anti-corrosive film.
- The operating temperature range is -20 °C to +120 °C.

IDH No.	Product Description	Pack Size	Box Qty
2101118	LOCTITE LB 8201 Universal Lubricant	400ml	12



TEROSON SB 3120 - Aerosol Underbody Textured Rubber and Resin Coating Spray

- TEROSON® SB 3120 is a rubber- and resin- based underbody coating spray used for spot repairs such as the treatment of small areas and the touching-up of local spots after accident repairs.
- The product is overpaintable and PVC-compatible.
- It complements existing PVC and rubber- and resin-based protective coatings.

IDH No.	Product Description	Pack Size	Box Qty
803863	TEROSON SB 3120 - Aerosol Underbody Textured Rubber and Resin Coating Spray	500ml	12



TEROSON VR 4600 - Zinc Spray Mig and Spot weldable Primer

- TEROSON® VR 4600 is a rapid curing zinc-based sprayable primer used for vehicle body repair and maintenance.
- It provides optimal protection of iron and steel against corrosion.
- It also conducts electricity, wet as well as dry.
- The product is not overpaintable and exhibits a high temperature resistance.
- As a result of its „self-healing properties“, this coating product is able to close small lesions.
- The dry film bonds well to cleaned metal parts and features a high resistance to abrasive wear.

IDH No.	Product Description	Pack Size	Box Qty
333170	TEROSON VR 4600 - Zinc Spray Mig and Spot weldable Primer	400ml	12



TEROSON VR 315 - Aerosol High build Primer

- TEROSON® VR 315 FILLER is a grey, fast-drying acrylic filler to even out small imperfections, scratches, and sanding marks, creating a smooth surface on filled substrates for subsequent painting.
- It is used on filled surfaces such as steel, galvanized steel, various plastics (PVC, PPO/PA, ABS, PC/PBT), wood and cured 2K filler.

IDH No.	Product Description	Pack Size	Box Qty
211834	TEROSON VR 315 - Aerosol High build Primer	400ml	6



Unibond Power Tape Silver

- New tape technology - triple power, 100% weatherproof and super strong adhesive to offer up to 50% stronger adhesion than standard cloth tapes.
- For interior and exterior use.

IDH No.	Product Description	Pack Size	Box Qty
2675767	Unibond Power Tape Silver	50mm x 25m	8



Unibond Power Tape Black

- New tape technology - triple power, 100% weatherproof and super strong adhesive to offer up to 50% stronger adhesion than standard cloth tapes.
- For interior and exterior use.

IDH No.	Product Description	Pack Size	Box Qty
2675781	Unibond Power Tape Black	50mm x 25m	8



Unibond Duct Tape Silver

- Extra strong cloth tape for interior and exterior use.
- Fixes, binds, repairs, joins, seals, reinforces and protects.

IDH No.	Product Description	Pack Size	Box Qty
2675777	Unibond Duct Tape Silver	50mm x 50m	8



Unibond Duct Tape Silver

- Extra strong cloth tape for interior and exterior use.
- Fixes, binds, repairs, joins, seals, reinforces and protects.

IDH No.	Product Description	Pack Size	Box Qty
2675518	Unibond Duct Tape Silver	50mm x 25m	8



LOCTITE 5075 Insulating Sealing Wrap Red

- Self-fusing silicone rubber wrap for temporary repairs on flexible hoses and pipes.
- Resistant to UV light, salt water, fuels and acids. service temperature range of -54 to +260°C.

IDH No.	Product Description	Pack Size	Box Qty
1684617	LOCTITE 5075 Insulating Sealing Wrap Red	10 x 4.27m	10



LOCTITE 5075 Insulating Sealing Wrap Black

- Self-fusing silicone rubber wrap for temporary repairs on flexible hoses and pipes.
- Resistant to UV light, salt water, fuels and acids. service temperature range of -54 to +260°C.

IDH No.	Product Description	Pack Size	Box Qty
1808110	LOCTITE 5075 Insulating Sealing Wrap Black	10 x 4.27m	10



Key Characteristics



Key Characteristics



TEROSON VR 1000 - Double sided adhesive tape

• TEROSON® VR 1000 is a polyethylene foam tape coated on both sides with acrylic adhesive. One side is covered with a polyethylene film as a separating medium. It is used in particular for bonding and attachment of protective and decorative trims or insignias and fixing of PVC or PU integral skin foam panels. The tape is characterised by a high resistance to weathering and UV. Surface preparation with TEROSON® VR 10 recommended.

IDH No.	Product Description	Pack Size	Box Qty
93357	TEROSON VR 1000 - Double sided adhesive tape	12x12mmx10m	12



TEROSON VR 1000 - Double sided adhesive tape

• TEROSON® VR 1000 is a polyethylene foam tape coated on both sides with acrylic adhesive. One side is covered with a polyethylene film as a separating medium. It is used in particular for bonding and attachment of protective and decorative trims or insignias and fixing of PVC or PU integral skin foam panels. The tape is characterised by a high resistance to weathering and UV. Surface preparation with TEROSON® VR 10 recommended.

IDH No.	Product Description	Pack Size	Box Qty
93358	TEROSON VR 1000 - Double sided adhesive tape	8x19mmx10m	8



TEROSON VR 5080 - Fix and Repair Tape

• TEROSON® VR 5080 is a multi-purpose high-strength adhesive tape for emergency repairs. It is ideal for temporarily repairing, reinforcing, fixing, sealing or protecting parts. The product adheres to any dry, oil- and dust-free surface and exhibits 100% water resistance and temperature resistance up to 70°C. It is suitable for indoor and outdoor applications.

IDH No.	Product Description	Pack Size	Box Qty
801959	TEROSON VR 5080 - Fix and Repair Tape	25m	12



Key Characteristics



Key Characteristics

LOCTITE[®]
TEROSON[®]

Henkel Ltd
Wood lane End
Hemel Hempstead
Hertfordshire
HP2 4RQ
Tel: 01442 278100
www.henkel-adhesives.com.uk



Visit our YouTube channel
to see our latest videos!

