

DECLARATION OF PERFORMANCE
No. 01970 | 1213-CPR-9356

- | | |
|---|--|
| 1. Unique identification code of the product-type: | TEROSON FO 150 FOIL-TACK M+S |
| 2. Intended use/es: | Flexible sheets for waterproofing - Plastic and rubber sheets for roof waterproofing |
| 3. Manufacturer: | Henkel AG & Co. KGaA
D-40191 Düsseldorf |
| 4. Authorised representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | System 2+ |
| 6a. Harmonised standard/s: | EN 13956:2012 |
| Notified body/ies: | 1213 SKZ
Friedrich-Bergius-Ring 22, 97076 Würzburg |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified body/ies: | Not relevant |

7a. Declared performance/s:

Essential characteristics	Performance	Testing method	Harmonised technical specification
Reaction to fire	Class E	EN ISO 11925-2 EN 13501-1	EN 13956:2012
Thickness e_{ff}	100 μ m -5%/+10%	DIN EN 1849-2	
Watertightness	60 kPa / passed	EN 1928 Method B	
Shear resistance of joints	> 125 N/50 mm	EN 12317-2	
Resistance to impact	$\geq$ 150 mm (Method A) $\geq$ 500 mm (Method B)	EN 12691	
Tensile strength - Maximum force - Elongation	$\geq$ 250 N/50 mm $\geq$ 300 %	EN 12311-2 Method A	
Tear resistance - Maximum force - Elongation	$\geq$ 40 N/mm ² $\geq$ 120 %	EN 12311-2 Method B	
Resistance to static load	10 kg (tight) 15 kg (tight)	EN 12730 Method A EN 12730 Method B	
Foldability at low temperatures	$\leq$ -30 °C	EN 495-5	
Exposure to UV radiation	passed	DIN EN 1297	
Exposure to bitumen	passed	DIN EN 1548	
Hazardous substances	NPD*	-	

*NPD: No performance Determined

- | | |
|---|--------------|
| 8. Appropriate Technical Documentation and/or Specific Technical Documentation: | Not relevant |
|---|--------------|



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Phillip Balters
Head of Business Development
(name and function)

A handwritten signature in blue ink, appearing to read "P. Balters", written over a horizontal line.

(signature)

Michael Frank
Director Innovation Consumer & Construction
(name and function)

A handwritten signature in blue ink, appearing to read "Michael Frank", written over a horizontal line.

(signature)

Düsseldorf, 21.08.2026
(place and date of issue)

 1213	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 21 01708 1213-CPR-7640 TEROSON FO 150 FOIL-TACK M+S	
EN 13967:2012 Flexible sheets for waterproofing - Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet	
Reaction to fire	Class E
Shear resistance of joints	> 125 N/50 mm
Resistance to impact	≥ 150 mm (Method A) ≥ 500 mm (Method B)
Durability	
- against aging	passed
- against chemicals	passed
Hazardous substances	NPD
Henkel AG & Co. KGaA, D-40191 Düsseldorf 26 01970 1213-CPR-9356 TEROSON FO 150 FOIL-TACK M+S	
EN13956:2012 Flexible sheets for waterproofing – Plastic and rubber sheets for roof waterproofing	
Reaction to fire	Class E
Shear resistance of joints	> 125 N/50 mm
Resistance to impact	≥ 150 mm (Method A) ≥ 500 mm (Method B)
Tear resistance	≥ 40 N/mm ²
Foldability at low temperatures	≤ -30 °C
Exposure to bitumen	passed
Hazardous substances	NPD

