



## DECLARATION OF PERFORMANCE

No. 01708

- |   |   |
|---|---|
| 1. Unique identification code of the product-type:                      | TEROSON FO 150 FOIL-TACK M+S  |
| 2. Intended use/es:   | Flexible sheets for waterproofing –<br>Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet |
| 3. Manufacturer:  | Henkel AG & Co. KGaA<br>D-40191 Düsseldorf  |
| 4. Authorised representative:   | Not relevant  |
| 5. System/s of assessment and verification of constancy of performance: | System 2+   |
| 6a. Harmonised standard/s:  | EN 13967: 2012  |
| Notified body/ies:  | 1213 SKZ<br>Friedrich-Bergius-Ring 22, 97076 Würzburg   |
| 6b. European Assessment Document:                                       | Not relevant  |
| European Technical Assessment:  | Not relevant  |
| Technical Assessment Body:  | Not relevant  |
| Notified body/ies:  | Not relevant  |
| 7a. Declared performance/s:   | Waterproofing buildings (BA)  |

Essential characteristics	Performance	Testing method	Harmonised technical specification
Reaction to fire	Class E	EN ISO 11925-2 EN 13501-1	EN 13967:2012
Watertightness	60 kPa / passed	EN 1928	
Tear propagation resistance (Nail shank)	≥ 100	EN 12310-1	
Shear resistance of the seams	> 125 N/50 mm	EN 12371-2	
Resistance to impact	≤ 150 mm (method A) ≤ 500 mm (method B)	EN 12691	
Tensile strength - Maximum force - Extension	≥ 250 N/5mm ≥ 300 %	EN 12311-2 method A	
Resistance to static load	≤ 5 kg	EN 12730	
Durability - with artificial aging - to chemicals	passed / tight	EN 1296 EN 1928	
	Passed / tight	EN 1847 EN 1928	
Hazardous substances	NPD*	-	

\*NPD: No performance Determined




8. Appropriate Technical Documentation and/or Specific Technical Documentation:	Not relevant
---	--------------

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Vito Henning  
Head of Business / TEROSON WINTeQ Europe  
\_\_\_\_\_  
(name and function)


  
\_\_\_\_\_  
(signature)

Wolfgang Maier  
DIRECTOR PD EUROPE  
\_\_\_\_\_  
(name and function)

  
\_\_\_\_\_  
(signature)

\_\_\_\_\_  
Düsseldorf, 16.11.2021  
(place and date of issue)

Attachment

 <b>1213</b>	
<b>Henkel AG &amp; Co. KGaA, D-40191 Düsseldorf</b> <b>21</b> <b>01708</b>  <b>TEROSON FO 150 FOIL-TACK M+S</b>	
<b>EN 13967:2012</b>  <b>Flexible sheets for waterproofing</b> <b>Type A &amp; Typ T</b>	
Reaction to fire	Class E
Shear resistance of the seams:	> 125 N/50 mm
Resistance to impact:	≤ 150 mm (method A) ≤ 500 mm (method B)
Durability	
- against aging	passed
- against chemicals	
Hazardous substances	NPD