# LOCTITE<sup>®</sup> UR 3371<sup>TM</sup> A RELIABLE, FLEXIBLE ADHESIVE.



When you need a flexible, high-strength adhesive, LOCTITE<sup>®</sup> UR 3371<sup>TM</sup> provides great adhesion and sag resistance for expansive areas.

LOCTITE<sup>®</sup> UR 3371<sup>TM</sup> is a one component moisture cure polyurethane adhesive, that is easy to dispense. The skin-over time of 40 minutes and high initial tack provides time to align large parts and keep them in place once assembled. It adheres to most materials, such as glass, aluminum, metal, wood and concrete, without the need of a primer. The cured adhesive is flexible, durable and environmentally resistant.

## FEATURES OF LOCTITE<sup>®</sup> UR 3371™

One part moisture cure polyurethane Conveniently packaged in 300 ml cartridge & 20 oz. sausage pack

## **Handling Properties:**

- Non-sag
- Easy to apply
- High initial tack
- 40 minute skin over time

## **Cured Properties:**

- Colors
- Paintable
- Adheres without using a primer to most common substrates such as glass, aluminum, metal, wood and concrete
- Flexible
- Environmental resistance







LOCTITE UR 3371 PROPERTIES							
PACK SIZE*	ITEM NUMBER	COLOR	CHEMISTRY	SAG RESISTANCE	SKIN OVER/ TACK FREE	TENSILE SHEAR STRENGTH	ELONGATION AT BREAK
300ml Cartridge	2799582 2799581	White Grey	Polyurethane	<2.5 mm	Skin Over = 40 minutes	320 psi	500%
20 oz. Sausage Pack	2795475	White			Tack Free = 50 – 70 minu- tes		

\*Made to order drum and pail size available

## **RECOMMENDED DISPENSERS**



HD10 300 ML PNEUMATIC

**CARTRIDGE DISPENSER** 

IDH 1714379



SOFT PRESS 20 OZ. PNEUMATIC APPLICATOR IDH 250052

Henkel Corporation Engineering Adhesives www.next.henkel-adhesives.com

## U.S.A.

#### **Henkel Corporation**

Engineering Adhesives One Henkel Way Rocky Hill, Connecticut 06067 Tel: 1.800.LOCTITE (562.8483) Tel: 860.571.5100 Fax: 860.571.5465

## Canada

#### **Henkel Canada Corporation**

Engineering Adhesives 2515 Meadowpine Blvd. Mississauga, Ontario L5N 6C3 Tel: 1.800.263.5043 (within Canada) Tel: 905.814.6511 Fax: 905.814.5391



Henkel Adhesive Technologies

All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S., Germany and elsewhere. © 2024 Henkel Corporation. All rights reserved. DSGN0039678 (8/24)