



LOCTITE® HELPS BOND MODULAR BUILDINGS TOGETHER

LOCTITE® UR 3371 Polyurethane Adhesive/Sealant



Situation:

A manufacturer of modular buildings was grappling with the time and expense required to attach metal thresholds to their floors mechanically. Additionally, they faced a persistent issue with moisture buildup in the flooring. They needed a quicker and more cost-effective solution to install while also effectively preventing moisture accumulation.

LOCTITE® Solution:

The LOCTITE® Technical Sales Engineer recommended LOCTITE® UR 3371. The polyurethane sealant bonded the threshold to the flooring and delivered a flexible, high-strength bond with no additional materials needed. The sealant also reduced the moisture buildup, preventing damage.

Benefits:

LOCTITE® UR 3371 proved to be an effective new solution and replaced mechanically attaching the metal thresholds. Costs were cut, installation time was lowered, and production speed increased. The strong bond of LOCTITE® UR 3371 successfully increased the strength of the threshold and prevented moisture buildup.

Product	IDH	Size*	Color
LOCTITE® UR 3371	2799582	300 ml	White
	2799581	300 ml	Gray
	2795475	20 oz	White

*Representative images used to maintain customer confidentiality.

All marks are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S., Germany and elsewhere. © 2024 Henkel Corporation. All rights reserved. DSGN0039752 (8/24)

*Made to order drum and pail size available



Henkel Adhesive Technologies