

# LOCTITE®

## HENKEL SOLUTIONS FOR AUTOMOTIVE ELECTRONICS COMPONENTS

### LOCTITE® AA 5832

1k polyacrylate high strength potting for sealing ECU connectors



### CUSTOMER NEEDS

- **Easy to dispense and highly flowable** potting material to fully encapsulate connector pin arrays
- **Fast curable** solution to meet **high throughput** manufacturing requirements
- **Excellent adhesion** to enhance reliability and **protect** against leaks
- **High strength**, non-silicone solution to sustain **exposure** to harsh **automotive environments**



### HENKEL SOLUTIONS

- **1K Polyacrylate based; low viscosity** potting material
- **UV curable** system, **fast** processing
- Excellent **adhesion** over a variety of common connector plastic
- **Seal** performance from **-40°C to 150°C** immediately after cure
- Excellent **durability** in hot fluids such as **transmission fluids and engine oils**

CONTACT US TO LEARN MORE

Europe  
Germany  
Henkel AG & Co. KGaA (Headquarters)  
Henkelstraße 67, 40589 Düsseldorf

Asia-Pacific  
China  
Henkel (China) Co., Ltd.  
No. 928 Zhangheng Road, Pudong New District  
201203 Shanghai

Americas  
U.S.A.  
Henkel Corporation  
Madison Heights, 32100 Stephenson Highway  
Madison Heights, MI 48071



Henkel Adhesive Technologies



ECU CONNECTORS



[www.henkel-adhesives.com](http://www.henkel-adhesives.com)

The data contained herein is intended as reference only. Some products / package sizes may not be available in your country or may have a lead time. Please contact your local Henkel subsidiary for assistance and recommendation on specifications and applications of these products. © designates a trademark of HENKEL AG & Co. KGaA or its affiliates, registered in Germany and elsewhere  
© Henkel AG & Co. KGaA, 2023 (10/2023)