

# MANAGE WEAR & TEAR WITH LOCTITE® SOLUTIONS.

## SITUATION

A company needed an adhesive tough enough to bond sacrificial stainless steel wear plates inside commercial centrifuges. They wanted to minimize downtime to perform maintenance and to extend preventative maintenance to a minimum of six months.

## LOCTITE® SOLUTION

The LOCTITE® Technical Sales Engineer recommended LOCTITE® AA H3300™ structural adhesive. It minimized downtime to perform maintenance because it is easy to apply to the steel wear plates and fast curing. A mix nozzle ensures it is properly mixed. The adhesive is non-sag so it stays where it is applied. It cures fast so equipment is back in service quickly. LOCTITE® AA H3300™ extended preventative maintenance to a minimum of six months because it delivered excellent high impact and shear strength performance even in this aggressive operating environment.

## BENEFIT

This company documented over \$50,000 in cost savings when they implemented LOCTITE® AA H3300™ as a result of improved performance and reduced downtime.



Product	Size	IDH
LOCTITE® AA 3300™	50 ml cartridge	473132
	400 ml cartridge	398436

**U.S.A.**  
**HENKEL CORPORATION**  
 Engineering Adhesives  
 One Henkel Way  
 Rocky Hill, Connecticut 06067  
 Tel: 1.800.LOCTITE (562.8483)  
 Tel: 860.571.5100  
 Fax: 860.571.5465

**CANADA**  
**HENKEL CANADA CORPORATION**  
 Engineering Adhesives  
 2515 Meadowpine Blvd.  
 Mississauga, Ontario L5N 6C3  
 Tel: 1.800.263.5043 (within Canada)  
 Tel: 905.814.6511  
 Fax: 905.814.5391

\*Representative images used to maintain customer confidentiality.

The data contained herein are intended as reference only. Please contact Henkel Technical Support Group for assistance and recommendation on specifications for these products. Except as otherwise noted, all marks used above in this printed material are trademarks and/or registered trademarks of Henkel and/or its affiliates in US, Germany, and elsewhere. © Henkel AG & Co. KGaA, 2025 DSGN0046625 (09/2025)

