

# LOCTITE®

For hot, cold & drinking water, gas & heating.



## LOCTITE 55

The ideal choice for quick, easy and reliable seal. It is designed for locking and sealing of metal and plastic pipe fittings. Gives immediate full pressure seal.

### FAST AND EASY TO USE:

- Instant sealing performance
- Easy and quick application

### NEAT AND CLEAN APPLICATION:

- Clean application – for both, the user and the parts
- No product wastage on application
- No waste on site

### PIPE JOINTS CAN BE RE-ADJUSTED RELIABLY

- Re-adjusting up to 45° without any fear of leakage
- Higher flexibility on installation
- Saves extra time for cleaning and re-sealing

PTFE TAPE SHREDS  
AND JOINT LEAKS IF  
TURNED BACK



WITH LOCTITE 55, TURNING  
BACK IS SAFE: NO  
SHREDDING, NO LEAKING.



[www.henkel-adhesives.com/au/loctite55](http://www.henkel-adhesives.com/au/loctite55)

Henkel

## Fast, easy and clean to apply



1.

Roughen the thread with saw-blade or file.



2.

Wind onto one of the first pitches of the thread and continue in random cross pattern around the thread.



3.

Cut the LOCTITE 55 sealing cord with the incorporated cutting device and press the loose end of the thread.



4.

Screw on and fasten the joint with a pipe wrench. Reposition if necessary.

### One single pack of LOCTITE 55 will seal:

Pipe diameter	1/2"	3/4"	1"
Approximate number of joints sealed with 160 m pack	405	275	190
Approximate number of joints sealed with 50 m pack	125	85	60

### How PTFE tape compares to LOCTITE 55

PTFE TAPE LEAKS	LOCTITE 55 SEALS
<ul style="list-style-type: none"> <li>• No set application standard, number of wraps vary as per applicator</li> <li>• No adjustments can be made as the tape shreds on opening the pipe joint</li> <li>• Possibility of thread damage due to over-tightening</li> <li>• Gaps remain along the pipe joint threads, which leads to leaks</li> <li>• Tape shreds clog downstream filters</li> <li>• Susceptible to vibrational loosening</li> </ul>	<ul style="list-style-type: none"> <li>• Standard application as per different pipe sizes</li> <li>• Readjustments can be made as LOCTITE 55 cord does not shred</li> <li>• Controlled tightening torque maintains thread integrity</li> <li>• Gaps are completely sealed and mating threads are unitized against leakage</li> <li>• No shreds - no clogging</li> <li>• Prevents vibrational loosening</li> </ul>

## Approvals



Type Tested

### SAI Global

AS/NZS 4020:2018 Potable Water Approval  
Certificate no. PST25485



### AGA

Australian Gas Association (AGA)  
certificate no. 6007 to 2000 kPa Class III  
Domestic (Gas) up to 85°C

**Henkel Australia Pty Ltd**  
135-141 Canterbury Road  
Kilsyth VIC 3137  
Tel: 1300 885 556  
loctite.enquiries@henkel.com

**Henkel New Zealand Ltd**  
2 Allens Road  
East Tamaki 2013  
New Zealand  
Tel: +64 9 272 6710

