

LOCTITE® PC 7383™ **PROTECTING EQUIPMENT EXPOSED TO HIGH IMPACT CONDITIONS**

LOCTITE® PC 7383™ Impact, Abrasion and Chemical Resistant Rubber Repair Coating

Wear is one of the most common challenges a plant faces. Not protecting your equipment properly from the beginning can be costly. LOCTITE® PC 7383™ is a solvent-free, two-component, and ambient temperature cure polyurethane coating. Its properties allow thick coatings to be applied to vertical surfaces or the underside of horizontal surfaces without slumping or falling off. Apply on installation to protect equipment from wear or to repair worn surfaces.

Used in mines, oil & gas refineries, and power generation plants LOCTITE® rubber repair coatings are built for high impact resistance.

LOCTITE® PC 7383™ is ideal for high impact and abrasion environments such as those found in mines, pulp and paper mills, oil and gas refineries and power generation. Designed to protect rubber as well as metal, this coating is reliable, easy to use, and is backed by Henkel's sales and technical support.

LOCTITE® PC 7383™

- High Abrasion Resistance
- High Impact Resistance
- High Performance



FEATURES AND BENEFITS

- Easy application
 - Trowel-able (spreads easily) Highly durable,
 - Thixotropic: (horizontal & vertical application)
- High impact resistance
- Cure at ambient temperature
- High abrasion Resistance
- Non sag on vertical surfaces



TYPICAL APPLICATIONS

Ball and SAG Mills, Chutes, Slurry pumps, Hoppers, Elbows, Centrifuges, Hydrocyclone or any metal and rubber surfaces experiencing high impact and wear abrasion.

ADDITIONAL PRODUCTS	IDH	APPLICATION	SIZE
LOCTITE® ETCHING AGENT	235638	Enhances bond to rubber	3 fl. oz. bottle
LOCTITE SF 8220™ CLEANER	233307	Cleans and primes surfaces	4 fl. oz. can
TERESON® 8519 P™	2241589	For metal	100 ml bottle

LOCTITE® PC 7383™ PROPERTIES CHART

PRODUCT	LOCTITE® PC 7383™
APPEARANCE MIXED	Black Paste
OPERATING TEMPERATURE	-4° to 176°F° / -20° to + 80 °C
COVERAGE	6.4 ft @ 1/4"
SERVICE CURE TIME	24 hours
IMPACT / ABRASION RESISTANCE	Excellent
HARDNESS	90 Shore A
PART NO. / CONTAINER	2395759 / 10kg kit

Henkel Corporation
Engineering Adhesives
henkel-adhesives.com/mro
www.loctite.com

U.S.A.
Henkel Corporation
Engineering Adhesives
One Henkel Way
Rocky Hill, Connecticut 06067
Tel: 1.800.LOCTITE (562.8483)
Tel: 1.860.571.5100
Fax: 860.571.5464

Canada
Henkel Canada Corporation
Engineering Adhesives
2515 Meadowpine Blvd.
Mississauga, Ontario L5N 6C3
Tel: 1.800.263.5043 (within
Canada)
Tel: 905.814.6511
Fax: 905.814.5391

All marks are trademarks and/or registered trademarks of Henkel and/or its affiliates in the US and elsewhere.
© = registered in the U.S. Patent and Trademark Office. © 2025 Henkel Corporation. All rights reserved. DSGN0046359 (08/25)

