

LOCTITE®



PC 4400™

PROTECTS AND RESTORES PAINT

MAKING YOUR VEHICLE LOOK LIKE-NEW AND EXTENDING ITS LIFE

THE PROBLEM

Industrial and work vehicles spend a lot of time exposed to harsh conditions and environmental elements. This leads to:

- Accelerated corrosion
- Dulling / fading of vehicle paint
- Increase cleaning costs
- More frequent repaint cycles



BEFORE



AFTER

THE LOCTITE® SOLUTION

LOCTITE PC 4400™ is a one-part clear coating that can be applied directly over existing paint on a vehicle to extend its life and restore it to look like new. It can be spray applied or wiped on with a pad applicator, offering excellent flow and leveling. LOCTITE PC 4400™ one-component coating also eliminates the lost time and quality risks associated with mixing two-component coatings.

Using LOCTITE PC 4400™ on vehicles offers:

- **Better Protection from Corrosion:** Protects paint and reduces repaint cycles and surface maintenance with industry leading scratch, UV, abrasion, salt and chemical resistance to extend paint life up to 10 years*
- **Paint Restoration:** When applied to faded or oxidized paint, PC 4400™ makes the old paint look like new again
- **Easy to Clean and Repellency:** With both hydrophobic and oleophobic properties, PC 4400™ repels water, dirt, oil and algae keeping a vehicle clean with quicker wash cycles
- **Overall Better Appearance:** Promote brand image better with a cleaner flawless look. A better appearance will also improve resale value.

Key Vehicle Applications:

- Agricultural
- Construction
- Mining
- Utility Vehicles
- Salt / Plow Trucks
- Buses
- Rail
- Military
- Forestry
- Freight / Delivery Trucks
- Garbage Haulers
- Specialty Fleet Vehicles

LOCTITE® PC 4400™ - Paint Protect & Restore Coating

Product	Item Number	Pack	Pencil Hardness [ASTM D3363]	Abrasion Resistance [ASTM D4060]	QUV Resistance [ASTM D4587]	MEK Resistance [ASTM D4752]	Tack Free Time	Dry Hard Time
PC 4400™	2573885 2573975	1.1 L Bottle 3.8 L Jug	4H	8.4 mg loss	99%	>1500	30 – 40 Minutes At 72°F (22°C), 50% R.H.	24 Hours At 72°F (22°C), 50% R.H.

Additives for LOCTITE® PC 4400™

Product	Description	Item Number	Pack Size	Mix Ratio
PC 4401™ – Matte Additive	Matting effect and increases hardness of coating from 4H to 7H	2573869	1.1 L	10 – 30% mix ratio by volume
PC 4402™ – Accelerator Additive	Accelerate dust & tack free times of PC 4400™	2573973	120 ml	1 – 2% mix ratio by volume

*Results may vary based on conditions. See TDS for usage and limitations.



To learn more about LOCTITE® PC 4400™, contact your local LOCTITE® Representative, or visit exploreloctite.com

Henkel Corporation
Engineering Adhesives
www.na.henkel-adhesives.com/aam
www.loctite.com

U.S.A.
Henkel Corporation
Engineering Adhesives
One Henkel Way
Rocky Hill, Connecticut 06067
Tel: 1.800.LOCTITE (562.8483)
Tel: 860.571.5100
Fax: 860.571.5465

Canada
Henkel Canada Corporation
Engineering Adhesives
2515 Meadowpine Blvd.
Mississauga, Ontario L5N 6C3
Tel: 1.800.263.5043 (within Canada)
Tel: 905.814.6511
Fax: 905.814.5391