



TECHNICAL DATA SHEET

Revision: 10/01/2022
Supersedes: 01/08/2014
Ref. #: 253991



LEPAGE® Polyfilla® Brickfix® Brick Mortar Filler

DESCRIPTION

LEPAGE® Polyfilla® Brickfix® Brick Mortar Filler is a superior quality re-pointing compound designed to repair displaced mortar, and fill cracks between brickwork. It is specially formulated to be durable, weather resistant, and fast curing.

Available as:

Item #	Package	Size
394003	Paper Cartridge	300 mL

FEATURES & BENEFITS

- Weather resistant
- Low odour for interior and exterior use
- Fast curing to prevent reworking due to washing away of uncured product

RECOMMENDED FOR

Repair displaced mortar or fill cracks between exterior brickwork. Can also be used for interior, non-structural mortar work around imitation brick.

LIMITATIONS

- Not recommended for cementing bricks together
- Do not use as a structural adhesive
- Do not use if rain or freezing temperature is forecasted within 12 hours of application
- Not recommended for high temperature applications i.e., inside a fireplace or chimney

TECHNICAL DATA

Typical Uncured Physical Properties		Typical Application Properties	
<u>Color:</u>	Grey	<u>Application Temperature:</u>	Apply and cure above 10°C (50°F) to 30°C (85°F)
<u>Appearance:</u>	Paste	<u>Odor:</u>	Low
<u>Base:</u>	Acrylic	<u>Clean-up:</u>	Soap and water
<u>pH:</u>	7.5 to 8.5	<u>Lot Code Explanation:</u>	YYDDD YY = Last two digits of year of manufacture DDD = Day of manufacture based on 365 days in a year 22061 = 61 st day of 2022 = March 2, 2022
<u>Specific Gravity:</u>	1.67	<u>Example:</u>	
<u>% Solids:</u>	79.1%		
<u>Viscosity:</u>	500 to 800 Mcps @ 5 rpm		
<u>VOC Content:</u>	0.51% by weight CARB		
<u>Shelf Life:</u>	18 months from the date of manufacture (unopened)		

Typical Cured Performance Properties

<u>Color:</u>	Grey	<u>Water Resistant:</u>	Yes
<u>Cured Form:</u>	Hard solid		



TECHNICAL DATA SHEET

Revision: 10/01/2022
Supersedes: 01/08/2014
Ref. #: 253991

DIRECTIONS

Tools Typically Required:

Caulking gun, long and thin tool to puncture cartridge seal, tooling device.

Safety Precautions:

Wear gloves, safety glasses, and wash hands after use.

Preparation:

Use above 10°C (50°F). Remove loose grout. Joints or cracks must be clean, dry, and free of frost, grease, dust, and other contaminants. Puncture inner seal and place in caulking gun to extrude.

Application:

Apply with steady pressure, filling joint, then smooth or tool joint to match surrounding mortar. Wet tool or finger to facilitate tooling.

Clean-up:

Uncured filler should be clean up immediately with warm soapy water. Cured filler may be sanded or scraped away.

STORAGE & DISPOSAL

DAMAGED BY FREEZING. Store above freezing. Product should not be washed down the drain or sewers. Use an approved hazardous waste transfer facility.

LABEL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes.

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



LEPAGE® Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Canada Corporation - Professional & Consumer Adhesives Headquarters - Mississauga, ON L5N 6C3
www.henkel-northamerica.com



For Technical Assistance call: 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET
www.lepage.ca