



Technical Data Sheet



Glue Remover

Technical Data Sheet
Ref: LO22000
Issued: 25.10.2022
Number of pages: 02

CHARACTERISTICS

LOCTITE® Glue Remover is a solvent based product, designed for the removal of instant adhesives.

It is designed for home use and removes cured Super Glue from stained or badly bonded objects. It is also effective on many other types of glue. LOCTITE® Glue Remover is a powerful solvent for cured Super Glue (cyanoacrylate) residues, yet does not attack most surfaces, plastics and materials.

LOCTITE® Glue Remover is suitable for use on vertical surfaces, non-porous surfaces. It can also be effective in removing marker or ink stains.

INSTRUCTIONS FOR USE

1. Perform a test in an inconspicuous area to ensure suitability.
2. Apply sufficient LOCTITE® Glue Remover to cover the glue residue or stain.
3. Place a pad of absorbent material/tissue on top of the Remover. If the residue/stain is on fabric, place a tissue on both sides of the material.
4. Leave for several hours or preferably overnight.
5. Remove and discard the absorbent pad/tissue, which will now contain the dissolved glue residue.
6. Wipe the area with a clean cloth. Rinse with water and allow to dry.
7. Repeat the process if required.

For use on bonded skin:

1. Apply LOCTITE® Glue Remover to bonded area.
2. Allow several minutes for glue to soften.
3. Very slowly and carefully peel bonded area apart, allowing the Remover to penetrate and break down the bond. Do not be impatient as this will result in skin damage.
4. After debonding, wash thoroughly with soap and water. Avoid prolonged contact with skin. Never use in or around the eye area.





TECHNICAL DATA

| | |
|----------------------|---------------------------------|
| Composition | Propylene carbonate |
| Appearance | Clear gel |
| Density | 1.209 g/cm ³ @ 20 °C |
| Viscosity | Non-drip gel |
| Pack | 3g tube |
| Safety | See Safety Data Sheet |
| Shelf Life at 20 °C | 24 months unopened |
| Shelf Life at 2-8 °C | 24 months unopened |

LIMITATIONS

- Do not use on painted or varnished surfaces.
- Not suitable for use on some hard plastics e.g. ABS.
- Test on a hidden area before use if in any doubt.
- When used on skin, for external use only. Avoid contact with eyes.

STORAGE

Store in a cool, dry place, out of reach of children.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 59 39 33

email: technical.services@henkel.co.uk

Internet: www.henkel.co.uk