

LOCTITE® 3035™ POLYOLEFIN BONDER


LOCTITE® 3035[™] Polyolefin Bonder is an easy-to-use, 1:1 mix product that can be stored at room temperature and works where traditional low surface energy bonders often fail. LOCTITE® 3035[™] Polyolefin Bonder offers the highest in reliability and consistency of performance.

- Bonds low surface energy plastics with no surface preparation.
- Fixture time of less than 15 minutes boosts productivity.
- Bonds a wide variety of plastics and metals.
- 1:1 mix ratio ensures consistant mixing.
- Room temperature storage saves on energy & equipment costs.
- Eliminates the need for primers or surface treatments.

KEY APPLICATIONS INCLUDE:

- Plastic pipes
- Plastic storage tanks
- Appliances
- ATVs
- Outdoor power equipment
- Toys
- Outdoor furniture
- Watercraft and marine accessories

LOCTITE[®] 3035[™] TYPICAL PERFORMANCE



Low Surface Energy Plastics



ENGINEERED ADHESION TO LOW SURFACE ENERGY SUBSTRATES

Polyolefin plastics, such as polyethylene and polypropylene, are increasingly being incorporated into part design due to their unique properties and cost effectiveness. The challenge for design engineers is how to assemble parts that incorporate these low surface energy plastics. Mechanical fasteners are impractical and, up until now, most adhesive technologies fail to provide more than modest bond strengths and usually require a significant surface preparation or use of a chemical primer.

UNCURED PROPERTIES		
Mix Ratio	1:1	
Viscosity	Part A 7500cP Part B 60000cP	
Color	Pale Yellow	

CURING PROPERTIES		
Work Life	2-4 minutes	
Fixture	10-15 minutes ¹	

SHEAR STRENGTH (PSI)				
Polyolefins	HDPE	1658		
	LDPE	632		
	PP	239		
Metals	Steel to HDPE	657		
	Aluminum	423		
Plastics	Ероху	1045		
	PC	726		
	PVC	1237		

PACKAGE DESCRIPTION	ITEM NO.
50 ml dual cartridge	1677288
400 ml dual cartridge	1677877

¹ HDPE.





Henkel Corporation
Engineering Adhesives
www.henkeladhesives.com/LOCTITEAA3035

U.S.A.
Henkel Corporation
Engineering Adhesives
One Henkel Way
Rocky Hill, Connecticut 06067
Tel: 1-855-HENKEL4
Fax: 860.571.5465

Canada
Henkel Canada Corporation
Engineering Adhesives
2515 Meadowpine Blvd.
Mississauga, Ontario L5N 6C3
Tel: 1.800.263.5043
(within Canada)
Tel: 905.814.6511
Fax: 905.814.5391



All marks used are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere. ® = registered in the U.S. Patent and Trademark Office. © 2025 Henkel Corporation. All rights reserved. DSGN0046727 (09/2025)

