



Technical Data Sheet



Technical Data Sheet
Ref: TA1 000
Issued: 22.11.2023
Number of pages: 3

UniBond Carpet Tape

CHARACTERISTICS

High strength, double sided, fabric reinforced permanent carpet tape.

For fixing carpets and carpet tiles onto smooth and uneven floors.

Prevents carpets from slipping or creasing.

Suitable for high traffic areas.



APPLICATION FIELD

- For permanently adhering carpets and carpet tiles with all backings to range of floor surfaces including floorboards, plywood, bitumen, vinyl, concrete, metal, tile.

INSTRUCTIONS FOR USE

Application



1. Place on clean, dry floor. Unroll the tape and stick around the edges of the floor. For firmer fixing, apply further lengths crossways.
2. Remove lining paper and firmly press the carpet into position **Important:** tape is not repositionable.
3. For carpet tiles, start from the centre of the room, lay tape in criss-cross pattern to hold adjacent tiles.

Important: tape is not repositionable.



TECHNICAL DATA

Colour	Yellow
Carrier material	Polyester fabric
Liner	80 g/m ² two sides siliconized paper
Adhesive	Synthetic rubber resin – solvent free
Width	48mm
Length	10m
Total thickness (without liner)	Approx. 180µm
Total weight	185 g/m ²
Tensile strength	Approx. 30 N/cm
Elongation at break	15 %
180°Peel adhesion on steel (PSTC-1)	10 N/cm
Shelf life	12 months from date of manufacture, stored in cool, dry conditions

LIMITATIONS

*Not suitable for fixing carpets onto staircases.

Storage

Store in a dry place between 15 C° and 25 °C. Protect product from direct sunlight.

Packaging

48mm x 10m roll with 3" cardboard core packed in a cardboard cuff

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ
Phone: +44 (0) 1606 593 933



Internet: www.henkel.co.uk
e.mail: technical.services@henkel.co.uk