



# TECHNICAL DATA SHEET

Revision: December 15, 2022  
Supersedes: March 23, 2018  
Ref. #: 736421

## FOAM AND APPLICATOR CLEANER



# FOAM CLEAN

FOR USE WITH QUAD WINDOW & DOOR SYSTEM

## DESCRIPTION

OSI Foam Clean is a pressurized cleaning solvent used to dissolve uncured, or fresh, polyurethane foam sealant. It is designed for easy cleaning of foam spills and fitted with a collar and adapter for cleaning the OSI Foam Gun.

### Available As:

Item #	Size	Color
2874891	12 oz. (340 g)	Colorless

## FEATURES & BENEFITS

- Removes uncured polyurethane foam
- Use to clean OSI® Foam Applicator Gun
- Evaporates quickly
- Use with OSI® QUAD® Foam Window & Door Installation Foam

## RECOMMENDED FOR

Use with OSI® QUAD® Foam Window & Door Installation Foam Sealant to remove uncured polyurethane foam and to clean the OSI® Foam Applicator Gun.

## LIMITATIONS

- Will not dissolve cured foam sealant
- Do not use can in horizontal position

## TECHNICAL DATA

### Typical Product Properties

<u>Color:</u>	Colorless	<u>Odor:</u>	Strong Solvent Odor
<u>Appearance:</u>	Liquid	<u>Flashpoint:</u>	1.4°F (-17°C)
<u>Base:</u>	Acetone	<u>Specific Gravity:</u>	0.793
<u>VOC Content:</u>	0% by weight 0 g/l	<u>Shelf Life:</u>	24 months from date of manufacture (unopened)
	CARB SCAQMD		

## DIRECTIONS

### Safety Precautions:

Wear impervious gloves, chemical goggles, and work clothes during use. Use mechanical ventilation to maintain exposure below TLV. If TLV is exceeded, use an appropriate NIOSH / MSHA approved respirator.

### Preparation:

Shake can well before spraying or attaching to the OSI® Foam Applicator Gun. Insert red spray activator onto valve stem of can. Do not use in horizontal position; always spray in a vertical position.

### Application:

With arrow pointing toward the surface to be cleaned, slowly depress red activator to spray solvent.



# TECHNICAL DATA SHEET

Revision: December 15, 2022  
Supersedes: March 23, 2018  
Ref. #: 736421

## DIRECTIONS

### **Foam Applicator Gun Cleaning:**

Follow above instructions, if necessary, to remove fresh foam from OSI® Foam Applicator Gun coupling and nozzle before attaching can. Hold red spray activator to one side and screw OSI® Foam Clean can onto gun coupling until it will go no farther. Do not over-tighten. Carefully pull gun trigger until solvent extrudes from nozzle. Release trigger and let solvent soak in gun for two minutes. Pull trigger and dispense solvent into suitable container (can, box, etc.). If necessary, repeat procedure two or three times, or until only clear solvent appears from nozzle.

Refer to OSI® Foam Applicator Gun instructions for complete information.

## STORAGE & DISPOSAL

Store in a cool, dry area. Do not expose to open flame or temperatures above 120°F (49°C). Excessive heat can cause premature aging of components resulting in a shorter shelf life. To dispose of empty containers, carefully vent off any excess pressure. Dispose of empty containers in compliance with all applicable household waste regulations.

## LABEL PRECAUTIONS

**DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRES! VAPOR HARMFUL. EYE, SKIN AND RESPIRATORY TRACT IRRITANT. CONTENTS UNDER PRESSURE.**

**DANGER!** Contains acetone. **EXTREMELY FLAMMABLE.** Vapors may ignite explosively. Do not use or store near heat, sparks, or open flame. Do not smoke when using this product. Extinguish all flames and pilot lights and turn off all sources of ignition, including stoves, heaters, and electric motors during use and until all vapors are gone. Use in a well-ventilated area. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Avoid breathing vapors. Avoid contact with eyes and skin. Prolonged or repeated exposure may affect the nervous system causing dizziness, headache, or nausea. If you experience eye watering, headache, or dizziness, leave the area to obtain fresh air. **CONTENTS UNDER PRESSURE.** Prolonged exposure to sunlight or heat from radiators, stoves, hot water, and other heat sources may cause bursting. Do not puncture, incinerate, or burn. Do not store above 120°F. **FIRST AID:** For eye contact flush with water for 15 minutes. Call a physician if irritation develops or persists. For skin contact, wash thoroughly with soap and water. Get medical attention if irritation develops or persists. If affected by inhalation, remove to fresh air, and contact a physician. If swallowed, do not induce vomiting. Call a physician or Poison Control Center. **KEEP OUT OF REACH OF CHILDREN.**

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver and kidney damage or may cause cardiac arrhythmia. **INTENTIONAL MISUSE BY DELIBERATELY INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.**

Refer to the Safety Data Sheet (SDS) for further information

## DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



# TECHNICAL DATA SHEET

Revision: December 15, 2022  
Supersedes: March 23, 2018  
Ref. #: 736421

## LIMITED WARRANTY

This product is warranted to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty, express or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This limited warranty gives you specific legal rights, which vary from state to state. Henkel may be contacted at 1.800.624.7767 M-F 9:00 am to 4:00 pm ET for warranty assistance.



**OSI Tougher than the Elements. For Professional Use Only. The Battle will be Fierce.**

OSI works side by side with residential builders, contractors and remodeling professionals who use our products every day on their jobsites. OSI combines this deep understanding with the sophisticated global innovation and manufacturing excellence of Henkel to make the world's best professional-grade caulks, sealants, and adhesives.

**For Technical Assistance call: 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET**

[www.ositough.com](http://www.ositough.com)



OSI Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

**Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067**

[www.henkelna.com](http://www.henkelna.com)