



# LOCTITE® PC 7350™ CONVEYOR BELT REPAIR

Improved Performance in Rubber Repair Technology

**LOCTITE® PC 7350™**, a premium rubber repair compound designed for conveyor belts and other rubber parts, is fast curing and self-leveling – making it an excellent choice for on-site repairs. Offering outstanding adhesion and abrasion resistance, repairs will have the same durability and flexibility as the rubber, increasing reliability and overall efficiency. Additional applications include but are not limited to repairing or rebuilding liners in mills, pumps, feeder bowls, hoppers, chutes, and repairing cast urethane screens and liners.

## FEATURES

- ✓ Excellent abrasion resistance
- ✓ Outstanding adhesion to metal and rubber
- ✓ Excellent elongation and flexibility
- ✓ Good impact-resistance properties
- ✓ Easy to apply in both cartridge and container kit
- ✓ When correctly applied, will not interfere with belt scrapers
- ✓ Solvent-free

## BENEFITS

- ✓ Reduces costly downtime
- ✓ Eliminates replacement inventory
- ✓ On-site and in-situ repairs - minimizes repair costs
- ✓ Increased repair life
- ✓ Prevents premature wear of belt splices



Reduce  
Cost



Increase  
Efficiency




Increase  
Reliability



Improve  
Safety

Henkel



TECHNICAL DATA	
Package Type & Size	400 ML CARTRIDGE, IDH# 2073202 800g can, IDH# 2084201
Color	Black
Coverage (in.2 at 1/4 in. depth)	400 ml cartridge = 88 800g can = 200
Maximum Operating Temperature	176°F, 80°C
Minimum Operating Temperature	-20°F/-29°C
Working Time (minutes) at 23°C/73°F*	5
Functional Cure (hours) at 23°C/73°F*	2
Mix Ratio by Volume (resin: hardener)	1:1

\*higher temperatures will reduce time and lower temperatures will increase time

CURED DATA	
Hardness, Shore A, ASTM D2240	95
Tensile Strength, ISO 527-2 (psi)	1,600
Elongation, %, ISO 527-2	250
Lap Shear Strength, ISO 4587 (psi) Grit blasted mild steel	900
Lap Shear Strength, ISO 4587 (psi) Rubber	96.7

ADDITIONAL PRODUCTS	
LOCTITE® ETCHING AGENT	Enhances bond to rubber. 3 fl. oz. bottle IDH# 235638
LOCTITE® SF 8220™ CLEANER	Cleans and primes surfaces. 4 fl. oz. can IDH# 233307
EQUIPMENT	
DISPENSING GUN	Required for use with 400 ml cartridge of LOCTITE® PC 7350™ Conveyor Belt Repair. IDH# 1372751
STATIC MIXER	Packaged 10/bag - for mixing and dispensing in a 400 ml cartridge. 10/bag IDH# 720177

## U.S.A.

### Henkel Corporation

Engineering Adhesives  
One Henkel Way  
Rocky Hill, Connecticut 06067  
Tel: 1.800.LOCTITE (562.8483)  
Tel: 860.571.5100  
Fax: 860.571.5465

## Canada

### Henkel Canada Corporation

Engineering Adhesives  
2515 Meadowpine Blvd.  
Mississauga, Ontario L5N 6C3  
Tel: 1.800.263.5043 (within Canada)  
Tel: 905.814.6511  
Fax: 905.814.5391