



# LOCTITE® PC 7350™ CONVEYOR BELT REPAIR

## IMPROVED PERFORMANCE IN RUBBER REPAIR TECHNOLOGY

LOCTITE® PC 7350™, a premium rubber repair compound designed for conveyor belts and other rubber parts, is fast curing and self-leveling – making it an excellent choice for on-site repairs. Offering outstanding adhesion and abrasion resistance, repairs will have the same durability and flexibility as the rubber, increasing reliability and overall efficiency. Additional applications include but are not limited to repairing or rebuilding liners in mills, pumps, feeder bowls, hoppers, chutes, and repairing cast urethane screens and liners.

### FEATURES

- Excellent abrasion resistance
- Outstanding adhesion to metal and rubber
- Excellent elongation and flexibility
- Good impact-resistance properties
- Easy to apply in both cartridge and container kit
- When correctly applied, will not interfere with belt scrapers
- Solvent-free

### BENEFITS

- Reduces costly downtime
- Eliminates replacement inventory
- On-site and in-situ repairs - minimizes repair costs
- Increased repair life
- Prevents premature wear of belt splices



**Reduce  
Cost**



**Increase  
Efficiency**



**Increase  
Reliability**



**Improve  
Safety**



### TECHNICAL DATA

Package Type & Size	400 ML CARTRIDGE, IDH# 2073202 800g can, IDH# 2084201
Color	Black
Coverage (in.2 at 1/4 in. depth)	400 ml cartridge = 88 800g can = 200
Maximum Operating Temperature	176°F, 80°C
Minimum Operating Temperature	-20°F/-29°C
Working Time (minutes) at 23°C/73°F*	5
Functional Cure (hours) at 23°C/73°F*	2
Mix Ratio by Volume (resin: hardener)	1:1

\*higher temperatures will reduce time and lower temperatures will increase time

### CURED DATA

Hardness, Shore A, ASTM D2240	95
Tensile Strength, ISO 527-2 (psi)	1,600
Elongation, %, ISO 527-2	250
Lap Shear Strength, ISO 4587 (psi) Grit blasted mild steel	900
Lap Shear Strength, ISO 4587 (psi) Rubber	96.7

### ADDITIONAL PRODUCTS

LOCTITE® ETCHING AGENT	Enhances bond to rubber. 3 fl. oz. bottle IDH# 235638
LOCTITE® SF 8220™ CLEANER	Cleans and primes surfaces. 4 fl. oz. can IDH# 233307

### EQUIPMENT

DISPENSING GUN	Required for use with 400 ml cartridge of LOCTITE® PC 7350™ Conveyor Belt Repair. IDH# 1372751
STATIC MIXER	Packaged 10/bag - for mixing and dispensing in a 400 ml cartridge. 10/bag IDH# 720177

**Henkel Corporation**  
Engineering Adhesives  
[henkel-adhesives/mro](mailto:henkel-adhesives@mro)

**U.S.A.**  
**Henkel Corporation**  
Engineering Adhesives  
One Henkel Way  
Rocky Hill, Connecticut 06067  
Tel: 1-855-HENKEL4  
Fax: 860.571.5465

**Canada**  
**Henkel Canada Corporation**  
Engineering Adhesives  
2515 Meadowpine Blvd.  
Mississauga, Ontario L5N 6C3  
Tel: 1.800.263.5043  
(within Canada)  
Tel: 905.814.6511  
Fax: 905.814.5391

All marks used are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere. ® = registered in the U.S. Patent and Trademark Office. © 2025 Henkel Corporation. All rights reserved. DSGN0046997 (09/2025)

