



LOCTITE® PC 9020™ NORDBAK® BACKING COMPOUND



Superior Performance, Low Odor

LOCTITE® PC 9020™ Nordbak® Backing Compound has significantly reduced odor and is far more user-friendly than traditional epoxy backing systems.

Features:

- Low odor
- High compression strength
- High impact resistance
- Color-changing technology assures product is fully mixed
- Low shrinkage
- Convenient kit size and durable metal cans
- On-site application support
- Global availability

**LOCTITE® PC 9020™ Nordbak® Backing Compound
is the only product you need!**

ONE PRODUCT

**LOCTITE® PC 9020™ Nordbak®
Backing Compound**

- 1694850 – 2 gallon kit
- 1694859 – 5 gallon kit

Replaces All of These!

LOCTITE® Nordbak® Backing Material
• 1324545 – 2 gallon
• 1324543 – 5 gallon

LOCTITE® Nordbak® High Performance
Backing Material
• 98072 – 2 gallon
• 98075 – 5 gallon

LOCTITE® Nordbak® High Impact
Backing Material
• 1372804 – 2 gallon



Henkel



Henkel Values Sustainability

Customer feedback and Henkel's proactive approach to increased health and safety and improved sustainability led to this innovative solution in crusher backing technology. This one product will deliver the performance you need with the increased worker safety and convenience you want.

LOCTITE® PC 9020™ Technical Data

PRODUCT	ITEM #	CONTAINER	COVERAGE CUBIC IN. @ 1/4" THICKNESS	MIXED COLOR	MAX. OPERATING TEMPERATURE (°F)	COMPRESSIVE STRENGTH (psi)	HARDNESS SHORE D	WORKING TIME AT 77°F (minutes)	FUNCTIONAL CURE AT 77°F (hours)
LOCTITE® PC 9020™ Nordbak® Backing Compound	1694850	2 gallon	340	Blue	220	19,000	90	20	8
	1694859	5 gallon	850						



Henkel Corporation
Engineering Adhesives
www.henkelna.com/mro

U.S.A.
Henkel Corporation
Engineering Adhesives
One Henkel Way
Rocky Hill, Connecticut 06067
Tel: 1.800.LOCTITE (562.8483)
Tel: 860.571.5100
Fax: 860.571.5465

Canada
Henkel Canada Corporation
Engineering Adhesives
2515 Meadowpine Blvd.
Mississauga, Ontario L5N 6C3
Tel: 1.800.263.5043 (within Canada)
Tel: 905.814.6511
Fax: 905.814.5391

