



LOCTITE 5884

Next Generation Cured-in-Place Polyacrylate Gasket (CIPG)

With LOCTITE 5884, Henkel provides the automotive industry with a high performance liquid dispensed polyacrylate compression gasket. This polyacrylate is especially suitable for powertrain applications such as engine and transmission components and can be cured within seconds at room temperature.





LOCTITE 5884 represents the next generation of cured-in-place liquid gasketing technology, designed specially to withstand modern powertrain conditions.

Henkel's dedicated technical resources provide assembly solutions on site to improve your product and productivity by offering:

- Design specification and testing
- > Process setup and optimization
- > Application equipment and system integration

Benefits

- > Improved process reliability
- > Automatically pre-applied on part
- > No tooling costs
- > Fast process: Ready-to-use in seconds
- > User- and eco-friendly
- > Improved compression set after 1000h aging (<50%)
- > Cures at room temperature (no external energy necessary)
- > Excellent oil resistance on transmission fluids and engine oils
- > Excellent gas permeation resistance
- > No oil foaming

Typical Applications of LOCTITE 5884

Original part

onto the part.

LOCTITE cured-in-place liquid gasket is dispensed

LOCTITE cured-in-place liquid gasket is cured using UV light.

After seconds of curing, the part is ready to use.

- > Engine covers
- > Oil pans
- > Timingbelt covers
- > Oil pump
- > Intake manifold

Process to integrate the

gasket onto parts

Technical Data	
Product family	Polyacrylate
Color	Transparent yellow/light amber
Tensile strength (N/mm²)	6.3
Elongation at break	> 200 %
Elongation at break after 1000h aging in oil	> 150 %
Operating temperature	-40°C – 150°C
Hardness (Shore A)	55 - 65
Engine oil resistance	Excellent
ATF and gear oil resistance	Excellent
Gas permeation resistance	Excellent (up to 10 times better than silicone)

For full technical details please refer to the Technical Data Sheet.

Europe Germany Henkel AG & Co. KGaA (Headquarters) Henkelstraße 67 40589 Düsseldorf Germany Phone: (+49) 211 797-0 Asia-Pacific China Henkel (China) Co. Ltd. No. 928 Zhang Heng Road Pu Dong 201203 Shanghai China Phone: (+86) 21 2891 8000 Americas U.S.A. Henkel Corporation Madison Heights 32100 Stephenson Highway Madison Heights, MI 48071 United States Phone: (+1) 248 583 9300



www.henkel-adhesives.com/gasketing

The data contained herein are intended as reference only. Please contact Henkel AG & Co. KGaA for assistance and recommendation on specifications for these products. (a) designates a trademark of Henkel AG & Co. KGaA or its affiliates, registered in Germany and elsewhere (c) Henkel AG & Co. KGaA, 2018