

TECHNOMELT®



TECHNOMELT PUR 9720 and XPO 1050

The next generation of lamination adhesives for interior trim parts

Both adhesives have adapted adhesion to plastic parts for light weight interior parts and enable adhesion to plastic parts.

Henkel

TECHNOMELT PUR 9720 and TECHNOMELT XPO 1050 represent a new product generation for bonding and lamination applications in interior trim parts

Henkel's dedicated technical resources provide support on site to improve your product and productivity by offering:

- > Support for design specification and testing
- > Preparation of tests and approvals
- > Process setup and continuous process improvement

Benefits

TECHNOMELT PUR 9720

- > high green strength
- > good resistance against plasticizers
- > improved adhesion to plastics
- > short setting time for fast processes

TECHNOMELT XPO 1050

- > adhesion to ABS & PP without pretreatment
- > long reactivation time
- > low consumption
- > label free

Technical Data		
Product family	PUR 9720	XPO 1050
Application temperature	130 – 150°C	130 – 150°C
Reactivation time	4 hours	up to 8 hours
Adhesion on plastics	ABS	ABS & PP
Curing time	3 days	5 – 7 days

For full technical details please refer to the Technical Data Sheet.

Typical Applications

Lamination of door panels with plastic films like PVC and TPO on carriers based on plastics like PP and ABS or renewable natural fibers.

Europe
Germany
Henkel AG & Co. KGaA
(Headquarters)
Henkelstraße 67
40589 Düsseldorf
Germany
Phone: (+49) 211 797-0

Asia-Pacific
China
Henkel (China) Co. Ltd.
No. 928 Zhang Heng Road
Pu Dong
201203 Shanghai
China
Phone: (+86) 21 2891 8000

Americas
U.S.A.
Henkel Corporation
Madison Heights
32100 Stephenson Highway
Madison Heights, MI 48071
United States
Phone: (+1) 248 583 9300

www.henkel-automotive.com



The data contained herein are intended as reference only. Please contact Henkel AG & Co. KGaA for assistance and recommendation on specifications for these products.
® designates a trademark of Henkel AG & Co. KGaA or its affiliates, registered in Germany and elsewhere
© Henkel AG & Co. KGaA, 2012