

IMPROVING PUMP RELIABILITY

LOCTITE®



Prevent fretting corrosion while securing bearings with **LOCTITE 638 Retaining Compound**



Make any size gasket with **LOCTITE 518 Flange Sealant**



Protect pump against chemical attack and erosion with **LOCTITE PC 7117**, brushable 2K epoxy



Prevent rust and seizure of power end bolts with **LOCTITE LB 8023 Marine Grade Anti-Seize**



Rebuild and protect worn volutes with **LOCTITE PC 7218**, brushable ceramic-filled 2K epoxy



Prevent corrosion in pump housing and on impeller vanes; restore surface afterwear and cavitation with **LOCTITE PC 7227**



Prevent key wallow with **LOCTITE 243 Medium Strength Threadlocker**

Repair key wallow with **LOCTITE 660 Retaining Compound**



Prevent corrosion and seizure of gland assembly nuts, and seizure of the impeller to the shaft with **LOCTITE LB 8023 Marine Grade Anti-Seize**



Prevent set screws from working loose with **LOCTITE 222 Threadlocker** or **LOCTITE 243 Threadlocker** (depending on fastener size)



Rebuild worn shafts with **LOCTITE EA 3478 Superior Metal**



Lock and seal housing bolts to prevent leakage between oils seals and housing with **LOCTITE 243 Medium Strength Threadlocker** or **LOCTITE 248 Medium Strength Threadlocker Stick**



Seal and lock drain screws with **LOCTITE 577 Thread Sealant**



Seal threaded fittings with **LOCTITE 572 Thread Sealants**



Prevent corrosion and secure casing bolts and adapter bolts with **LOCTITE 243 Medium Strength Threadlocker**



Keep mounting bolts tight with **LOCTITE 290 Wicking Grade Threadlocker**