



Technical Data Sheet



Technical Data Sheet
Ref: SE13000
Issued: 11.10.24
Number of pages: 2

Sellotape Just Paper Tape



CHARACTERISTICS

- Strong kraft paper based self-adhesive packaging tape ideal for sealing parcels and boxes
- Easy to tear by hand
- Suitable for sealing boxes up to 5kg

PRODUCT DESCRIPTION

Paper-based tape produced from FSC certified kraft paper coated with strong pressure sensitive adhesive. Perfect for sealing parcels and boxes.

Sellotape Just Paper Tape is easy to unwind and tear by hand, with sufficient strength to secure parcels and boxes up to 5kg.

Bonding Speed: Immediate when applied to substrate with hand pressure

INSTRUCTIONS FOR USE

1. Ensure all surfaces to be bonded are clean, dry and free from dust
2. Unroll desired length of tape from roll
3. Tear tape by holding tape between thumb and forefingers and applying tearing action across the width of the tape
4. Apply to surfaces taking care not to twist or crease the tape
5. Apply hand pressure over the tape to ensure good adhesion



TECHNICAL DATA

Composition	FSC kraft paper coated with strong, solvent free synthetic rubber pressure sensitive adhesive
Appearance	Light brown
Peel adhesion (stainless steel)	≥4N/cm
Total thickness	Approx. 130µm
Tensile strength	≥40N/cm
Elongation at break	≥5%
Shelf Life at 20 °C	At least 18 months from date of manufacture
Roll dimension	48mm x 50m
Core dimensions/ construction	" 3" ", 76.7mm internal diameter, 3mm thick recycled cardboard

LIMITATIONS

Do not use on dusty, dirty, unstable, fibrous, damp or wet surfaces
Not suitable for sealing heavy weight cartons

STORAGE

Store in a cool, dry place

PACKAGING

Roll: Cardboard cuff
Shipping carton: SRP (Shelf Ready Pack) of 5 rolls

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire HP2 4RQ
Phone: +44 (0) 1606 593 933
Internet: www.henkel.co.uk
e.mail: technical.services@henkel.co.uk