



Technical Data Sheet



Technical Data Sheet
Ref: SE7000
Issued: 01.11.24
Number of pages: 3

Sellotape Original Golden Tape



CHARACTERISTICS

Sellotape® Original Golden Tape is a premium, strong, easy to tear by hand self adhesive tape designed for office and domestic applications involving bonding of paper or card, e.g. wrapping presents, school work, crafts, sealing lightweight boxes

Bonding Speed: Immediate when applied to substrate with light finger pressure

INSTRUCTIONS FOR USE

1. Ensure all surfaces to be bonded are clean, dry and free from dust
2. Unroll desired length of tape from roll
3. Tear tape by holding tape between thumb and forefingers and applying sharp tearing action across the width of the tape:



4. Apply to surfaces taking care not to twist or crease the tape:





5. Apply light finger pressure onto the applied tape in order to ensure good adhesion:



TECHNICAL DATA

Composition	Biaxially orientated polypropylene (BOPP) film coated with strong, solvent free acrylic pressure sensitive adhesive	
Appearance	On roll:	Light golden roll of tape
	Unwound:	Clear tape
Peel adhesion (stainless steel)	$\geq 2.5\text{N/cm}$	
Total thickness	Approx. $50\mu\text{m}$	
Tensile strength	$\geq 15\text{N/cm}$	
Elongation at break	$\geq 20\%$	
Shelf Life at 20°C	At least 24 months from date of manufacture	

ROLL SIZES

1" Plastic core:

18mm x 25m

3" Cardboard Core

18mm x 40m

18mm x 66m

24mm x 35m

24mm x 50m

24mm x 66m

LIMITATIONS

- Do not use on dusty, dirty, unstable, fibrous, damp or wet surfaces
- Not suitable for sealing heavy weight cartons

STORAGE

Store in a cool, dry place

HEALTH AND SAFETY

This product is safe to use for the intended application

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except



Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

e.mail: technical.services@henkel.co.uk