

LOCTITE[®]
TEROSON[®]

HENKEL'S SOLUTIONS FOR **VEHICLE REPAIR & MAINTENANCE**

A Single Source for all Car Repair and
Maintenance Solutions




Henkel

Henkel Adhesive Technologies

PIONEERS AT HEART FOR THE GOOD OF GENERATIONS

VEHICLE REPAIR & MAINTENANCE

HENKEL, A TRUSTED SOLUTIONS PARTNER



A SINGLE SOURCE FOR ALL CAR REPAIR AND MAINTENANCE SOLUTIONS

Henkel continuously develops adhesive and sealant solutions together with leading automotive manufacturers in the field of vehicle repair & maintenance.

Our current developments in this regard are directly incorporated into repair and maintenance solutions. This leads to innovative products, which offer you efficient solutions for tackling your daily challenges at the workshop.

Improvements have long since focussed on more than just product performance. For Henkel, health-related concerns in terms of handling and treating products, compliance with the strictest regulations, ensuring the most environmentally friendly applications and disposal are key topics during product development. And you as the user benefit from all of this, too.

PRODUCT FINDER

From the Range of Application to the Product

END-USER TRAINING	VALUE-ADDED PARTNERSHIP	GLOBAL LEADERSHIP	SUPERIOR PRODUCT PERFORMANCE	COST SAVINGS AND RELIABILITY
We provide professional training programs to customers that help them identify opportunities for improving process efficiency, quality and costs.	Our large, experienced team of engineers provide documented design and application support.	LOCTITE & TEROSON are the global technology leaders with wide product range sold through an extensive sales and distributor network.	LOCTITE adhesives and TEROSON sealants are recognized as the best performing products in the industry.	LOCTITE & TEROSON solutions are more cost effective compared to conventional mechanical methods.



1	WINDSCREENS	<ul style="list-style-type: none"> ■ Glass / Windshield Sealant 6 - 7 	1
2	BODY REPAIR	<ul style="list-style-type: none"> ■ Seam Sealant 8 - 9 	2
3	EXTERIOR FINISH	<ul style="list-style-type: none"> ■ Polishing Compound 10 - 11 	3
4	BODY PROTECTION	<ul style="list-style-type: none"> ■ Underbody Coating 12 - 13 	4
5	MECHANICAL REPAIR	<ul style="list-style-type: none"> ■ Threadlocking 14 - 15 ■ Thread Sealing 16 - 17 ■ Retaining 18 - 19 ■ Gasketing 20 - 21 	5
6	SMALL & SMART REPAIR	<ul style="list-style-type: none"> ■ Instant Adhesives 22 - 23 	6
7	CLEANING PRE-TREATMENT	<ul style="list-style-type: none"> ■ Lubricants & Cleaners 24 - 15 	7
8	EQUIPMENT & ACCESSORIES	<ul style="list-style-type: none"> ■ Equipment & Accessories 26 - 27 	8

GLASS / WINDSHIELD SEALANT

Conform with Highest Safety Standards



For the overall structure of the car body, the windshield is a very important component.

Windscreens serve to improve the structural stiffness of the car and provide better protection to passengers. Both functions depend on the only means of holding the windshield to the car body: the adhesive. Windscreen adhesives increase the torsional stiffness up to 40%.

Benefit from Professional Solutions:

Henkel direct glazing adhesives offer high safety standards as a result of many years of active research and OEM experience.

- Tested according to the most stringent European crash test standard
- Lightweight construction and torsional stiffness (improve structural rigidity by up to 40%)
- Certified by the TÜV Rheinland test authority (including production process)

All premium direct glazing products from the TEROSON range are proven by realistic crash tests and certified by the TÜV Rheinland test authority.

TEROSON PU 8590 DGX



- **Application Areas:** Bonding Front, Rear, and Side glass
- Product base: 1K polyurethane
- Good sag resistance
- No stringing
- OEM specified
- Excellent UV resistance
- Glazing time: 20 min.
- Drive away time: 8-12 hours

IDH	Pack Size
1574212	KIT


TEROSON BOND 180



- **Application Areas:** Bonding Front, Rear, and Side glass
- Product base: 1K polyurethane
- Primerless system
- Built-in UV stability
- Glazing time: 25 min.
- Drive away time: 3 hours

IDH	Pack Size
2789092	310 ML
2796237	600 ML


LOCTITE SF 7649 PRIMER



- **Application Areas:** Glass and Metal only, Metal rear-view mirror brackets to windcreens
- Solvent-based activator
- Low temperature curing
- For applications with passive metals or inert surfaces and with large bond gaps

IDH	Pack Size
849297	100 ML

LOCTITE AA 326



- **Application Areas:** Glass and Metal only, Metal rear-view mirror brackets to windcreens
- Product base: modified acrylic ester + activator mesh
- Fixture time: 1 min.
- Service temperature range: up to +120°C

IDH	Pack Size
231560	50 ML

GLOBAL NCAP CRASH TEST STANDARD

Improved crash test standard

(64 km/h 40 % overlap) = 40 % of the width of the widest part of the car (not including wing mirrors)





SEAM SEALANT

Reproduce Standard and Special OEM textures

2

BODY REPAIR



Joining methods in car bodies range from bolting, riveting, spot-welding, and clinching to bonding. Most of the joints are additionally sealed by the OEM to avoid water ingress.

In vehicle body repair, it is crucial to reproduce the same quality and visual appearance provided by the original OEM seams to avoid corrosion caused by environmental factors. Our wide range of sealing products meets high quality aspects and the demand for economic repair. With this selection of TEROSON products, Henkel enables fast reproduction of standard beads as well as reproduction of special OEM textures.


The Whole Variety of Seam Sealing from Henkel

Our sealing technologies allow you reproduce even advanced flat and widestream (acoustic) beads:

TRADITIONAL TEXTURED BEADS	RIBBED BEADS	STANDARD BEADS
Spray seam sealing and spray surface coating	Flatstream beads and widestream (acoustic) beads	Brush texture seams and standard seams

TEROSON MS 930	TEROSON RB 273	TEROSON PU 93 WHITE	TEROSON MS 9320 SF																															
<ul style="list-style-type: none"> Application Areas: Passenger compartment floor, Rear Panel, Wheel housing OEM texture refinish for all vehicles Excellent sag resistance Isocyanate-free, solvent-free 	<ul style="list-style-type: none"> Application Areas: In-between sealing, Spacing, Overlapping joints Multi-Purpose Round Sealing Cord Serves as a vibration damper, prevents dust entry 	<ul style="list-style-type: none"> Application Areas: Passenger compartment floor, Rear panel Product base: 1K polyurethane Overpaintable after skin formation Skin formation time: approx. 20-25 min. Easy to spread and smooth for brush texture 	<ul style="list-style-type: none"> Application Areas: Passenger compartment floor, Rear panel Product base: silane modified polymer Sprayable and brushable 																															
<table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1656499</td> <td>310 ML</td> <td>White</td> </tr> <tr> <td>1656500</td> <td>310 ML</td> <td>Grey</td> </tr> </tbody> </table>	IDH	Pack Size	Color	1656499	310 ML	White	1656500	310 ML	Grey	<table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>2065420</td> <td>5x15x120M</td> </tr> <tr> <td>1574129</td> <td>5X2.5X10M</td> </tr> </tbody> </table>	IDH	Pack Size	2065420	5x15x120M	1574129	5X2.5X10M	<table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>2853047</td> <td>310 ML</td> </tr> </tbody> </table>	IDH	Pack Size	2853047	310 ML	<table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1358059</td> <td>300 ML</td> <td>Ochre</td> </tr> <tr> <td>1357960</td> <td>300 ML</td> <td>Grey</td> </tr> <tr> <td>1358054</td> <td>300 ML</td> <td>Black</td> </tr> </tbody> </table>	IDH	Pack Size	Color	1358059	300 ML	Ochre	1357960	300 ML	Grey	1358054	300 ML	Black
IDH	Pack Size	Color																																
1656499	310 ML	White																																
1656500	310 ML	Grey																																
IDH	Pack Size																																	
2065420	5x15x120M																																	
1574129	5X2.5X10M																																	
IDH	Pack Size																																	
2853047	310 ML																																	
IDH	Pack Size	Color																																
1358059	300 ML	Ochre																																
1357960	300 ML	Grey																																
1358054	300 ML	Black																																

TEROSON PU 9108F WHITE							
<ul style="list-style-type: none"> Application Areas: Passenger compartment floor, Rear Panel, Wheel housing Product base: 1C polyurethane Good adhesion to most substrates Good sag resistance Superior painting performance 							
<table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>2095618</td> <td>280 ML</td> </tr> <tr> <td>2095289</td> <td>600 ML</td> </tr> </tbody> </table>	IDH	Pack Size	2095618	280 ML	2095289	600 ML	
IDH	Pack Size						
2095618	280 ML						
2095289	600 ML						





POLISHING COMPOUND

For all your paintwork refinishing



3

EXTERIOR FINISH

Polishing Compounds to Maintain, Repair and Rework your Vehicle Bodies.

With the introduction of our new TEROSON Polishing Compounds the Henkel product portfolio now covers another integral element in meeting automotive maintenance and repair needs. Developed for you as automotive aftermarket professionals, it helps you to achieve perfect paintwork maintenance, repair and restoration for an as-new shine every time.

The right products for your needs:



Added value through customer-specific solutions (different lines for different needs).



Optimized polishing process saves up to 30% in time in comparison to traditional polishing systems and **complies with industrial standards.**



Right first time thanks to step-by-step colour code system and easy application.



Safer working environment due to silicone-free products with negligible dust emission and VOC conform.

TEROSON WX 150 FAST CUT



- Rubbing Compound
- Highly effective cutting compound
- Stable grain, Silicone-free
- Suitable for eliminating signs of wear and tear, overspray and grit 2000 sanding marks

IDH	Pack Size
1675020	1 L

TEROSON WX 157 HP HEAVY CUT



- Rubbing & cutting compound
- Diminishing grain
- Removes 1500-2000 grit sanding marks
- Silicone-free
- For eliminating signs of wear and tear, overspray

IDH	Pack Size
1675017	1 KG

TEROSON WX 175 HP GLAZE



- Haze & swirl marks remover
- Universal machine glaze
- Diminishing grain
- Silicone-free
- Highly effective polishing liquid
- Ensures perfect finishing

IDH	Pack Size
1675022	1 L

TEROSON WX 180 POLISH



- Contains carnauba wax
- Solvent-based
- Long-term protection and high gloss
- Makes dull surfaces shiny
- Provides a deep shine
- Easy to apply by machine

IDH	Pack Size
796923	1 L

TEROSON WX 183



- Transparent Ceramic Coating
- Protects your car against UV light, oxidation, rust and acid attacks
- Maintains original paint color
- Provides a mirror like finish and makes your car shine brighter

IDH	Pack Size
2139793	50 ML

TEROSON WX151 RUBBING



- Haze & swirl marks remover
- Universal machine glaze
- Diminishing grain
- Silicone-free
- Highly effective polishing liquid
- Ensures perfect finishing

IDH	Pack Size
2605208	100 G

TEROSON WX181 WAX



- Contains carnauba wax
- Solvent-based
- Long-term protection and high gloss
- Makes dull surfaces shiny
- Provides a deep shine
- Easy to apply by machine

IDH	Pack Size
2605161	100 ML

TEROSON ET 194 KNITTED LAMBSWOOL PAD



- Premium wool fibres
- Suitable for rotary polishing machines
- Low heat buildup
- Speedy removal of deep scratches and imperfections

IDH
1943313



UNDERBODY COATING

Additional Service for Your Customers




Used and vintage cars often need extra protection from corrosion.

With our Henkel product range for body protection you can offer your customers extra service and build trust. Technologies for underbody coating, stone chip protection and cavity conservation contribute to the long-term maintenance of car value and increase lifetime and resale value. Furthermore, corrosion protection means additional safety for passengers.

Benefits:

- High abrasion resistance
- Additional sound dampening properties
- PVC compatible



TEROSON RB 2010



- **Application Areas:** Underbody, Wheel house, Front and rear aprons, Door sills
- Product base: Rubber and resin
- Skin formation time: 10 - 15 min

IDH	Pack Size	Color
2269326	1 KG	Black
2269712	1 KG	Grey
2269323	1 KG	White

TEROSON WT 450 AQU



- **Application Areas:** Underbody, Doors, Pillars, Sills, Engine compartments
- Can be used on coatings based on PVC, PVC wax, bitumen/rubber and rubber/resin
- Good creeping qualities
- VOC-free, no unpleasant solvent odour

IDH	Pack Size
1335488	1 L

PRESERVING AND COMPLEMENTING EXISTING UNDERBODY COATING

www.henkel-adhesives.com/in



THREADLOCKING

Secure Fastening Against Vibration and Shock Loads



Bolted connections are the most important detachable connections, which are used in engineering, installation and repair. They are an integral part of the connection technology. A securing against loosening and unscrewing prevents the failure of bolted joints.

Choose the Right Product:

LOCTITE threadlockers are available in varying viscosities and strengths and can be used for a wide range of applications:

- Low-Strength
- Medium-Strength
- High-Strength
- Wicking
- Non-Liquids (Semi-Solid)

LOCTITE threadlocking products prevent self-loosening and secure any threaded fastener against vibration and shock loads. They are easy-flowing liquids which completely fill the gaps between mating threads. LOCTITE threadlockers permanently secure threaded assemblies and eliminate fretting corrosion by creating a unitised assembly.

Advantages of LOCTITE Threadlockers

- Prevent unwanted movement, loosening, leaks, and corrosion
- Resist vibration
- Single-component – clean and easy to apply
- Can be used on all sizes of fasteners
- Seal threads – allow through-hole tapping
- Work on all metals, including passive substrates (e.g. stainless steel, aluminium, plated surfaces)
- Specified by Automotive OEMs

ACTIVE SURFACES Primer optional - LOCTITE SF 7649 PRIMER

Brass, Copper, Bronze, Iron, Steel, Nickel

INACTIVE SURFACES Primer required - LOCTITE SF 7649 PRIMER

Aluminum, Stainless Steel, Magnesium, Zinc, Black Oxide, Cadmium, Titanium

Clear all the threads with LOCTITE SF 7070 ODC Free Cleaner and Degreaser and apply LOCTITE SF 7649 PRIMER.

LOCTITE 243 THREADLOCKER



- **Application Areas:** Screws, Collars pulleys, Tool holders and controllers
- Colour: Blue
- Max. thread size: M20
- Medium strength
- General purpose

IDH	Pack Size
2381943	0.5 ML
1367282	50 ML

LOCTITE 262 THREADLOCKER



- **Application Areas:** Screws, Collars pulleys, Tool holders and controllers
- Medium to High strength
- Suitable for all metal fasteners
- Resistant to vibration
- Suitable for all metal fasteners

IDH	Pack Size
531709	50 ML

LOCTITE 270 THREADLOCKER




- **Application Areas:** Screws, Collars pulleys, Tool holders and controllers
- Colour: Green
- Max. thread size: M36
- High strength
- Permanent locking
- Suitable for all metal threaded assemblies

IDH	Pack Size
848060	50 ML

**EXPERIENCE THE NEW
LOCTITE THREADLOCKING
ADHESIVES RANGE HERE**

www.tryloctite.in



THREAD SEALING

Steady Prevention of Leaks



Pipes must remain leak-free under the severest vibration, chemical attack, heat or pressure surges.

LOCTITE thread sealants, available in liquid form or as a sealing cord, prevent leakage of gases and liquids. Designed for low- and high-pressure applications, they fill the space between threaded parts. When fully cured, they seal to the burst strength of most pipe systems.

The Right LOCTITE Gasket for Your Application

The substrates to be sealed are a key criterion. When choosing a thread sealant, plastic threads usually require a different sealant than metal threads.

- Anaerobic
- Silicone

Advantages of LOCTITE Thread Sealants

- Can be used on any size of pipe fitting
- Replace all types of tape and hemp/paste sealants
- The seal resists vibration and shock loads
- Do not creep, shrink or block systems
- Protect mated threaded areas against corrosion
- Grades with several approvals, e.g. LOCTITE 55 Sealing Cord: Potable water (KTW) and Gas (DVGW) approvals

LOCTITE 542 THREAD SEALANT



- **Application Areas:** Hydraulic threaded fittings, Small pneumatic fittings up to R $\frac{3}{4}$ "
- Thread: Metal; Colour: Brown
- Max. thread size: M26/R $\frac{3}{4}$ "

IDH	Pack Size
2382630	0.5 ML
848735	50 ML
848736	250 ML

LOCTITE 577 THREAD SEALANT



- **Application Areas:** Air line fittings, Pneumatic systems
- Thread: Metal; Colour: Yellow
- Max. thread size: M80/R3"
- Medium strength
- General purpose
- For coarse threads

IDH	Pack Size
848742	50 ML
848741	250 ML

LOCTITE 55 PIPE SEALING CORD



- **Application Areas:** Air line fittings, Pneumatic systems
- Thread: Plastic and Metal
- Colour: White
- Max. thread size: R4"
- Immediate full pressure sealing
- Allows reliable re-adjustments
- Immediate full pressure sealing

IDH	Pack Size
1752446	160 M

LOCTITE 55

For locking and sealing of metal and plastic pipe fittings: quick, easy and reliable!

For hot, cold & drinking water, gas & heating.








www.tryloctite.in

RETAINING

Secures Parts Against High Loads and Corrosion



LOCTITE retaining compounds secure bearings, bushes and cylindrical parts into housings or onto shafts.

The Following Parameters are Key when Choosing a Retainer:

- Gap size between parts
- Temperature resistance
- Bond strength
- Cure speedthreads

They achieve maximum load transmission capability as well as uniform stress distribution and eliminate fretting corrosion.

Advantages of LOCTITE Retaining Compounds

- High-strength products can carry high loads
- Fill all voids to prevent corrosion and fretting
- 100% contact-load and stress is distributed evenly over the joint
- Higher load transmission and performance in combination with shrink fits or press fits

LOCTITE 638 NEW RETAINER



- **Application Areas:** Shafts, Gears, Pulleys
- For high strength assemblies
- Fills clearance in repaired parts upto 0.25mm

IDH	Pack Size
2382498	0.5 ML
1865160	50 ML
1865048	250 ML

LOCTITE 648 NEW RETAINER



- **Application Areas:** Splined shafts, Bearings, Steering systems components, Gearings, Cylindrical parts
- Max.gap size: 0.15mm
- High strength
- High temperature resistance

IDH	Pack Size
1865163	50 ML
1865164	250 ML

LOCTITE 641 RETAINER



- **Application Areas:** Shafts, Gears, Pulleys
- Medium strength
- Ideal for parts that need subsequent dismantling, i.e. retention of bearings on shafts and in housings

IDH	Pack Size
848752	50 ML

**FAST FIXTURING,
RESISTING HIGH TEMPERATURES**


www.tryloctite.in





GASKETING

Provides Long-lasting Seals



Gaskets are used to prevent leakage of fluids or gases by forming impervious barriers.

For successful gasketing, the seal must remain intact and leak-free over a long period of time. The gasket must be resistant to fluids and/or gases, and withstand the operating temperatures and pressures to which it is subjected. A low-pressure seal is formed immediately on assembly, with full cure in 24 hours giving a joint that will not shrink, crack or relax.

The Right LOCTITE gasket for Your Application


Many factors influence gasket choice. Henkel offers a variety of gasketing materials:

- Anaerobic Products for Rigid Flanges
- Silicone Products for Flexible Flanges

Advantages of LOCTITE Gasketing Products

- Single-component – easy and clean to apply
- Replace conventional gaskets – reduce inventory
- Fill all voids
- No need for re-torquing
- Immediate low pressure seal
- High resistance to solvents
- Resist high pressure when fully cured
- Maximum face-to-face contact eliminating flange face corrosion


LOCTITE SI 5910



- **Application Areas:** Oil Sump, Valve cover, Inlet manifold, Transmission cover, Differential cover
- Best for flexible flange
- Resistance to oil, water and glycol
- For flanges with permanent oil contact

IDH	Pack Size
1752556	50 ML


LOCTITE 574



- **Application Areas:** For sealing rigid and semi rigid metal flange
- Colour: Orange
- Max. gap size: 0.25mm
- High oil resistance
- Excellent water and glycol resistance

IDH	Pack Size
848739	50 ML
848734	250 ML


LOCTITE 515



- **Application Areas:** For sealing rigid flanges with less than 0.39 mm gap. Applicable on flanges that move in service or aluminum flanges
- Better able to withstand vibration
- Adapts to flange surfaces and scratches upto 0.39mm

IDH	Pack Size
833769	50 ML


LOCTITE SI 24 SUPERFLEX



- **Application Areas:** Oil Sump, Gearboxes, Pumps, Timing belt covers
- Neutral cure with no harmful odor
- Minimal/No Shrinkage
- Excellent resistance to automotive engine oils
- Non sagging, Non-corrosive

IDH	Pack Size	Color
1616705	25 G	Grey
1616799	85 G	Grey
1616707	25 G	Red
1616706	85 G	Red
1616702	25 G	White
1616704	85 G	White
2642131	25 G	Black
2642107	85 G	Black
2642783	25 G	Blue
2641849	85 G	Blue
2642785	15 G	Clear
2642129	25 G	Clear
2642124	85 G	Clear

LOCTITE SI 587 BLUE



- **Application Areas:** Valve covers, Rocker covers, Oil pans, Water pumps, End seals
- Best for flexible flange
- Gap filling of upto 0.24"
- Resistance to oil, water and glycol
- For flanges with permanent oil contact

IDH	Pack Size
1266356	95 G





INSTANT ADHESIVES

Proven Solutions for Common Repair Jobs

SMALL & SMART REPAIR



Many small repair tasks can be solved quickly with smart solutions from Henkel.

For little parts to be fixed fast and easily LOCTITE instant adhesives are of big help. There are low viscous products to wick into the smallest cavities as well as gel formulated ones to repair porous materials. Also high temperature applications up to 120°C are no problem.

SPEED FASTER SOLUTIONS

- Rapid assembly within 15 seconds
- Applicable for steel, aluminum, paper, ABS, PVC, polycarbonate, nitrile rubber, balsa wood and phenolic

VERSATILITY SUPERIOR SOLUTIONS

- Superior performance in demanding applications
- Low odor/low bloom, flexible and gap-filling products to minimize blooming

PERFORMANCE ENGINEERED SOLUTIONS

- Superior resistance to impact, vibration and peel forces
- Surface priming liquids increase adhesion low surface energy plastics



LOCTITE 401



- **Application Areas:** Rubber, Plastic, Wood, Metal, Ceramics
- General purpose
- Max. gap size: < 0.15mm
- Fixture time: 3 to 10 sec.
- Service temperature range: -40°C to +120°C
- Colour: Colourless transparent

IDH	Pack Size
1669715	20 G


LOCTITE 406



- **Application Areas:** Plastic, Rubber, including EPDM
- Low viscosity
- Max. gap size: < 0.15mm
- Fixture time: 2 to 10 sec.
- Service temperature range: -40°C to +80°C
- Colour: Colourless transparent

IDH	Pack Size
1669713	20 G


LOCTITE 4070



- **Application Areas:** Metal, Plastic, Rubber
- 2-component, fast fixturing, cyanoacrylate/acrylic hybrid adhesive
- Fast fixturing
- Temperature resistance from -40 to +100°C
- Gap filling up to 5 mm

IDH	Pack Size
2143579	11 G


LOCTITE 4090



- **Application Areas:** Metal, Plastic, Rubber
- Good moisture, chemical, temperature (up to 150°C) and impact resistance
- Non-flammable, non-corrosive
- Fast fixture time of 3-5 minutes - reduce repair time and work-in-process (WIP)

IDH	Pack Size
2123344	50 G

SUPERWIZ



- **Application Areas:** Rubber, Plastic, Wood, Metal, Leather
- Low to Medium Viscosity
- Fixture time: 10 to 60 sec.
- Color: Colorless transparent
- General purpose adhesive
- Fast handling properties

IDH	Pack Size
2715251	0.5 G
2332260	4 G

BONDS NEARLY ANYTHING. IN AN INSTANT.

www.tryloctite.in



LUBRICANTS & CLEANERS

For the Right Surface Preparation



CLEANING / PRE-TREATMENT



When choosing a cleaner or degreaser, the major factors to consider are drying time, residue, odour, and substrate compatibility.

Residue is a particularly important concern: if there is any secondary processing of the part, e.g. painting or bonding, a residue could interfere with that process. Substrate compatibility is a common concern when dealing with plastics and solvent-based cleaners.

The HENKEL Cleaner Portfolio Especially for the Vehicle Repair Market:

- Cleaning of components before applying adhesives or sealants
- Cleaning and degreasing of workshops and parts
- Cleaning of harsh dirt on hands

<p>LOCTITE SF 7737 RUST BUST</p>  <ul style="list-style-type: none"> ▪ Application Areas: Nuts, Bolts, Hinges, Rust Prone joints ▪ Rust treatment ▪ Moisture displacement ▪ Protection & Lubrication ▪ Leaves a thin film that lubricates and prevents rust <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>1909755</td> <td>315 G</td> </tr> <tr> <td>1644275</td> <td>70 G</td> </tr> </tbody> </table>	IDH	Pack Size	1909755	315 G	1644275	70 G	<p>LOCTITE SF 7735 BRAKE & CLUTCH CLEANER</p>  <ul style="list-style-type: none"> ▪ Application Areas: Brake Cable, Liners, Pads, open gears ▪ Efficient brake & clutch parts cleaner ▪ Residue removal ▪ Brake efficiency & effectiveness improvement <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>1644278</td> <td>350 G</td> </tr> <tr> <td>1911513</td> <td>70 G</td> </tr> </tbody> </table>	IDH	Pack Size	1644278	350 G	1911513	70 G	<p>LOCTITE LB 8035 SYNTHETIC GREASE</p>  <ul style="list-style-type: none"> ▪ Application Areas: Bearing, Valves, Door Hinges, Open Gears, moving parts ▪ Non dripping, non staining lubricant ▪ Instant maintenance and Protection ▪ Long lasting lubricating film <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>1644283</td> <td>350 G</td> </tr> </tbody> </table>	IDH	Pack Size	1644283	350 G	<p>LOCTITE SF 3013 WELD THRU PRIMER</p>  <ul style="list-style-type: none"> ▪ Application Areas: Welded Joints, Silencer Coating ▪ Rust inhibitor primer ▪ Temperature resistance up to 250°C ▪ Protective coating without flaking ▪ Works as a silencer coating <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>1673787</td> <td>300 G</td> </tr> </tbody> </table>	IDH	Pack Size	1673787	300 G
IDH	Pack Size																						
1909755	315 G																						
1644275	70 G																						
IDH	Pack Size																						
1644278	350 G																						
1911513	70 G																						
IDH	Pack Size																						
1644283	350 G																						
IDH	Pack Size																						
1673787	300 G																						
<p>LOCTITE SF 7262 CARB & THROTTLE CLEANER</p>  <ul style="list-style-type: none"> ▪ Application Areas: Throttle Body, Carburetor Jets, Automatic Chokes ▪ Carburetor & Throttle parts cleaner ▪ Efficient residue removal ▪ Engine efficiency improvement <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>1788108</td> <td>315 G</td> </tr> <tr> <td>1644282</td> <td>70 G</td> </tr> </tbody> </table>	IDH	Pack Size	1788108	315 G	1644282	70 G	<p>LOCTITE SF 790 CHISEL</p>  <ul style="list-style-type: none"> ▪ Gasket Remover ▪ Ideal for removing gasket residues without scratching the surface ▪ Removal of silicon or anaerobic gaskets <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>135544</td> <td>510 G</td> </tr> </tbody> </table>	IDH	Pack Size	135544	510 G	<p>LOCTITE SF 7840 NATURAL BLUE</p>  <ul style="list-style-type: none"> ▪ Application Areas: Engines, motors, castings, valves, bearings, carpets, seats, tanks, concrete floors ▪ Product base: water based ▪ Cleaner & degreaser ▪ Contains surfactants and conditioners <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>789065</td> <td>5 L</td> </tr> <tr> <td>789705</td> <td>20 L</td> </tr> </tbody> </table>	IDH	Pack Size	789065	5 L	789705	20 L	<p>LOCTITE SF 7039 ELECTRICAL CONTACT CLEANER</p>  <ul style="list-style-type: none"> ▪ Application Areas: Electrical Circuit, Bars, Cables, Relay, Coupler ▪ Solvent-based ▪ Short evaporation time ▪ Does not affect insulating varnishes ▪ Leaves a water repellent residue <table border="1"> <thead> <tr> <th>IDH</th> <th>Pack Size</th> </tr> </thead> <tbody> <tr> <td>1727806</td> <td>400 ML</td> </tr> </tbody> </table>	IDH	Pack Size	1727806	400 ML
IDH	Pack Size																						
1788108	315 G																						
1644282	70 G																						
IDH	Pack Size																						
135544	510 G																						
IDH	Pack Size																						
789065	5 L																						
789705	20 L																						
IDH	Pack Size																						
1727806	400 ML																						

7

EQUIPMENT & ACCESSORIES

Find the Right Equipment for Your Application Needs




EQUIPMENT & ACCESSORIES

NAME		DESCRIPTION	IDH	PACK SIZE
TEROSON ET SOFTPRESS AIR PRESSURE GUN		<ul style="list-style-type: none"> Controlled flow from the cartridge Integrated pressure regulator Hand-held unit for 600 ml cartridges Quick pressure relief to minimize run-on effect 	250052	1 Piece
TEROSON ET STAKU HAND GUN		<ul style="list-style-type: none"> Durable equipment Dispenses standard material from cartridges for standard beads Easy to handle Easy to maintain and clean For aluminium and plastic cartridges No run-on 	142240	1 Piece
TEROSON ET POWERLINE II AIR PRESSURE GUN		<ul style="list-style-type: none"> High air pressure gun Patented system to avoid blasting of cartridges For low- to very high-viscosity material Constant material flow Adjustable operating pressure Integral pressure manometer Ergonomically designed hand grip Extrusion by piston rod 	960304	1 Piece
TEROSON ET MULTIPRESS TELESCOPIC AIR PRESSURE GUN		<ul style="list-style-type: none"> For dispensing low- to middle-viscosity sealants and adhesives For spray textures of low-viscosity sealing material Recommended for bead, spray seam and spray coating (UBC) application Extrusion by telescopic piston rod Compact dimensions 	142241	1 Piece
PU CUTTER		<ul style="list-style-type: none"> High-quality tool Can be used as label scraper and for removing PUR residues 	149380	1 Piece
PUR-SCRAPER & REPLACEMENT BLADES		<ul style="list-style-type: none"> Replacement of Scraper blades 	197818	1 Piece

NAME		DESCRIPTION	IDH	PACK SIZE
TEROSON ET UBC AIR PRESSURE GUN		<ul style="list-style-type: none"> Low-pressure application Adjustable nozzle for creating different textures Ideal for creating (reproducing) improved textures from very rough to fine For basic underbody coating applications For processing UBC, wax and stone chip compounds from 1 litre cans 	1585815	1 Piece
WIRE NEEDLE		<ul style="list-style-type: none"> Wire insertion tool with a brass knob for applying the right pressure when piercing the PU adhesive The needle made of high-grade tool steel is pointed and sharp so that it can easily pierce through the PU adhesive 	149362	1 Piece
TEROSON CARTRIDGE OPENER		<ul style="list-style-type: none"> TEROSON Cartridge Opener is used to open 310 ml. cartridges Easy tool to remove the bottom seal and pop the top No damage to the bottom of the cartridge ring No need to get seam sealer on your tools Safer than stabbing at the cartridge 	395397	1 Piece
VACUUM LIFTERS [PAIR]		<ul style="list-style-type: none"> High-quality lifters for glass To be employed for changing automobile glass 	149365	1 Piece
TEROSON DOOR EDGE NOZZLE		<ul style="list-style-type: none"> Especially developed nozzle to guide sealing beads, e.g. for door sealing applications 	782222	1 Piece
CUTTING WIRE HOLDERS [PAIR]		<ul style="list-style-type: none"> Windshield cutting wire handles Specifically designed to eliminate the discomfort caused by enfolding wire around hands Holds the windshield cut-out wire through the center shaft of the handle Durable handles for years of auto glass windshield cutting 	149361 149364	1 Piece

LOCTITE® TEROSON®



GET IN TOUCH WITH US

Henkel Adhesives Technologies India Private Limited

Mumbai Corporate Office

L & T Seawoods, Grand Central,
401, B Wing, 4th Floor, Tower 1,
Seawoods, Navi Mumbai - 400 706,
Maharashtra, India.
Phone : +91 22 7130 1300

Chennai

Arunodayam, No. 14 & 16,
Raman Street, North Boag Road,
T. Nagar, Chennai - 600 017,
Tamil Nadu, India.
Phone : +91 44 7199 7000

Pune

Survey No. 234, 235 and 245,
India Land Global Industrial Park,
Phase 1, Hinjewadi, Pune - 411 057,
Maharashtra, India.
Phone : +91 20 7199 7000

Delhi

74, Industrial Corporation,
Mehrauli Gurgaon road,
Gurgaon - 122 001,
Haryana, India.
Phone : +91 0124 509 7000

Factory

D3/D4, MIDC Industrial Estate,
Jejuri, Purandhar, Pune - 412 303,
Maharashtra, India.
Phone : +91 2115 718 000

www.henkel.in

www.henkel-adhesives.com/in

www.tryloctite.in

www.linkedin.com/company/henkel-adhesives

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regards to the provided information in this brochure or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention. The information is protected by copyright. In particular, any reproductions, adaptations, translations, storage and processing in other media, including storage or processing by electronic means, enjoy copyright protection. Any exploitation in whole or in part thereof shall require the prior written consent of Henkel AG & Co. KGaA. Except as otherwise noted, all marks used in this document are trademarks and/or registered trademarks of Henkel and/or its affiliates in the US, Germany, and elsewhere.

© Henkel AG & Co. KGaA, 2023