

Loctite® FUN-TAK® Mounting Putty



DESCRIPTION

Loctite® FUN-TAK® Mounting Putty is a reusable, removable adhesive that is a convenient alternative for tape, tacks, staples, and magnets in the home, school, and office. No more holes in walls or chipped, peeled paint. It is ideal for hanging any lightweight item to a smooth or hard surface. Loctite® FUN-TAK® Mounting Putty is unaffected by moisture and will not dry out. For interior use only.

Available as:

Item #	Package	Size
1087306	Carded Blister – Mounting Putty	2.0 ounce
1865809	Carded Blister – Mounting Putty Tabs	2.0 ounce tabs

FEATURES & BENEFITS

- Non-toxic Safe for children
- Free of food products No risk of potential allergens
- Re-usable Minimizes waste
- Removable Excellent for temporary mounting
- Eliminates producing holes in walls Helps prevent wall repair
- Will not dry out Long-lasting

RECOMMENDED FOR

- Bonding items to most smooth surfaces including blackboards, wood, plaster, brick, glass, tile, metal, Formica, porcelain, linoleum, and concrete
- Hanging children's artwork on the refrigerator, attach memos to the phone, stick recipes, party decorations, and greeting cards to the wall
- Stopping vibrations of rattling windows, secure candlesticks, paper tablecloths, shelf paper and drawer linings, secure desk blotters and accessories

LIMITATIONS

DO NOT USE FOR:

- Hanging heavy objects, such as mirrors and framed pictures
- Sticking items to textured wall surfaces, flocked or paper wall coverings, on peeling or newly painted surfaces
- Mounting costly artwork and posters
- Exterior applications

TECHNICAL DATA

Typical Physical Properties		Typical Application Properties	
<u>Color:</u>	Blue	<u>Application Temperature:</u>	For best performance use and maintain at room temperature
<u>Appearance:</u>	Putty	<u>Specifications:</u>	Conforms to ASTM D4236
<u>Base:</u>	Synthetic Rubber	<u>Odor:</u>	Minimal

DIRECTIONS

Preparation:

Surfaces must be clean and dry.

Application:

Tear off enough Loctite® FUN-TAK® Mounting Putty for the job and knead the putty into a soft ball. Place a small amount between surfaces to be fastened and press. **IMPORTANT:** When using Mounting Putty Tabs, use 4 tabs per 1 lb. of weight.

IMPORTANT: Test first on absorbent surfaces. If uncertain, test in an inconspicuous area for 24 hours. May leave oily stain on some papers and flat painted surfaces. To remove, gently peel away items from mounting surface. Do not pull the putty off painted wall surfaces. Should any putty particles remain, simply roll more FUN-TAK® over area until clean.

Clean up:

To remove any excess putty residue, roll additional mounting putty over the surface area to pick up any remaining particles. Dry cleaning fluid may assist in removal of oily stains.

STORAGE & DISPOSAL

Not damaged by freezing. Dispose of unwanted putty with trash.

LABEL PRECAUTIONS

Children under 6 years of age should be supervised when using

Refer to the Material Safety Data Sheet (MSDS) for further information

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



Trusted Performance. Proven Results.

For over 50 years, LOCTITE Brand adhesives and sealants have taken on the toughest jobs. Used in race cars, airplanes, and even in the space-shuttle, LOCTITE provides solutions for the most demanding industrial, professional and consumer applications. LOCTITE gives you the specialization, power, and performance to not only get your job done, but to get it done right.

For Technical Assistance call : 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET
www.loctiteproducts.com



LOCTITE Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067
www.henkel-northamerica.com