



TITEFOAM™ Window & Door Insulating Foam Sealant

DESCRIPTION

LOCTITE® TITEFOAM™ Window & Door is an innovative polyurethane-based insulating foam sealant that expands to fill, seal, and insulate around window & door jambs. It is a polymer foam based on purified & concentrated ingredients that deliver premium durability. TITE FOAM Window & Door is a specialized formula that expands with low pressure so that it does not bow or warp window or door frames. It is easy to use and apply with its attached straw applicator. Strong adhesion and flexibility allow for a durable seal to keep air and moisture out.

Available As:

Item #	Package	Size	Color
2243625	Metal Canister	340 g (12 fl.oz.)	White

FEATURES & BENEFITS

- No Bow Formula – Will not bow or warp window & door frames.
- High Density Foam – Uniform cell structure seals out air, moisture, and pests
- Flexibility – High flexibility withstands building material movement
- UV Resistance – High resistance to the elements without becoming brittle
- Strong Adhesion – Bonds to most building materials; wood, metal, stone, brick, PVC
- Bright white color
- Tack free in 8 minutes, trim in 50 minutes

RECOMMENDED FOR

Loctite TITEFOAM Window & Door is suitable for interior and exterior projects. It has excellent adhesion to most building materials including wood, metal, stone, brick and PVC. Use for filling gaps, insulating, and sealing around window and door jambs.

LIMITATIONS

- TITEFOAM Window & Door is not a fire stopping material and SHOULD NOT be used in areas that require fireproof or fire stopping materials.
- Despite significantly higher UV resistance, it is still recommended to protect the foam from UV radiation. Exposed foam should be coated with a protective covering or coating.
- Do not store product on its side
- Does not bond polyethylene, polytetrafluoroethylene (PTFE)/Teflon® or siliconized surfaces
- For cold weather application, product should be stored at room temperature at least 12 hours before application
- In dry conditions, it is recommended to fill gaps in several layers by application of smaller foam strings (up to 1.6 inches thickness)
- Certain materials such as rubbers and plastics may have bonding difficulties. Test before use.

COVERAGE

A 340g (12fl. oz.) can will extrude a 3/8" bead approximately 80 ft. (24.4 m).

Note: Yields shown are based on theoretical calculations, for comparison purposes, and will vary depending on ambient conditions and particular application conditions and particular application.

TECHNICAL DATA**Typical Uncured Physical Properties:**

Color:	White	Specific Gravity	1.0
Appearance:	Polymer foam	VOC Content:	19.28 % by weight (CARB) 211.6 g/l (SCAQMD rule 1168)
Base:	Single component polyurethane	Flash Point:	-155.2°F (-104°C)
Odor:	Slight ether	Shelf Life:	15 months from date of manufacture (unopened)

Lot Code Explanation: MM/DD/YYYY (bottom of cannister)

MM/DD/YY (on box)

MM = month of Manufacture

DD = month of Manufacture

YYYY = Year of manufacture

Example: 10/31/2018 = October 31, 2018**Typical Application Performance Properties:**

Application Temperature:	Ambient conditions should be between 41°F (5°C) and 95°F (35°C). Can temperature must be between 41°F (5°C) and 86°F (30°C).		
Tack-Free Time:	For use at colder conditions, product should be stored at room temperature for at least 12 hours. 6-8 minutes* At 23°F and 50% relative humidity	Cure Time*:	Approx. 24 hours*
Cut Time:	50-70 minutes*	Clean Up:	*Time is dependent on temperature, humidity, and depth of sealant applied. Clean up uncured foam residue with acetone. Scrape away cured sealant using a sharp-edged tool. Follow solvent manufacturer's precautions for using solvents.
Repositioning Time:	15-20 minutes*		

Typical Cured Performance Properties:

Color:	White	Sandable:	Yes
Cured form:	Flexible solid	Paintable:	Yes
Water Resistant:	Yes	Service Temperature:	-40°F(-40°C) to 176°F(80°C) Long-term exposure -40°F(-40°C) to 212°F(100°C) Short-term exposure
Dimensional Stability:	< ±5% (TM 1004-2012)	Maximum Joint Width:	1.2 inch (3.0 cm) (TM 1006-2011 @ 41°F)
Movement Capability:	>25% (TM 1013-2013)	Shear Strength:	10.9 psi (75 kPa) (TM 2012-2011)

DIRECTIONS**Tools Typically Required:**

Utility knife, painter's tape, or foil for protecting surfaces.

Safety Precautions:

Always wear eye protection, gloves and proper work clothes when using Loctite TITEFOAM Window & Door after use. Cured foam is difficult to remove from skin, clothing and other substrates. May discolor skin. When transporting odd cans by passenger car leave the container wrapped in a cloth in the trunk, never in the passenger compartment.

Surface Preparation:

Ensure all surfaces are clean and free from dirt, dust, oil and other contaminants likely to impair adhesion. Surfaces can be moist but not frosted

DIRECTIONS

or iced. Cover surfaces not intended to be foamed. To ensure full and even curing of the foam on porous substrates (i.e. brickwork, concrete), moisturize surfaces with water spray before application.

General Preparation:

The temperature of the working area should be between 41°F (5°C) and 95°F (35°C). The temperature of the product should be between 5°C (41°F) and 30°C (86°F). When working in cold conditions, can should be stored at room temperature for at least 12 hours before use. Shake can vigorously before use for 30 seconds (15-20 times minimum). Screw the foaming straw to the valve.

Application:

Holding can upside down, press the trigger which controls outflow rate of the foam. Dispense the foam sparingly, filling the joint initially by half to avoid excessive overflows. Shake can regularly during use. Slight misting with water can speed cure. Foam can be trimmed with a knife after an hour. Foam will be fully cured in approximately 24 hours. It is recommended foam be protected from UV radiation by a protective covering or coating such as paint, plaster, mortar, etc.

Note: Ambient temperature and humidity can affect foam curing and maximal joint width. In dry conditions, to get the best foam structure and properties, it is recommended to fill gaps and joints in several layers by the application of smaller foam strings (up to 1.2 inches thick). At very dry conditions, the foam may be brittle after hardening. This brittleness is a temporary effect and disappears after a while or by warming.

Clean-up:

Clean tools and uncured foam residue immediately with acetone. Cured foam must be carefully cut away with a sharp-edged tool.

STORAGE & DISPOSAL

Product must be stored vertically, not horizontally on its side.

Note: When storing foam dispensing applicators with foam cans attached, be sure to store the tool with the can valve pointing downwards. Storing the can upright may cause propellant to leak and the foam applicator to become inoperative.

Store in a cool, dry place. For maximum performance and shelf life, store between 45°F (7°C) and 77°F (25°C). The product can be stored for a maximum of 1 week at -4°F (-20°C). Do not store below -4°F (-20°C), below this temperature product valve may spontaneously open resulting in leakage.

Containers are under pressure. Do not expose to open flame or temperatures above 120°F (49°C). Do not store under direct sunlight. Excessive heat can cause bursting and premature aging of components resulting in shorter shelf life. When containers are empty, vent off any excess pressure. DO NOT discard empty can in garbage compactor. DO NOT incinerate. DO NOT puncture, cut or weld container.

Recommended method of disposal for unused product: Vent off excess pressure and dispose of in an appropriate waste receptacle. Dispose of according to provincial and federal governmental regulations.

LABEL PRECAUTIONS

DANGER! EXTREMELY VAPOR MAY CAUSE FLASH FIRE. VAPOR AND SPRAY MIST HARMFUL, OVEREXPOSURE MAY CAUSE LUNG DAMAGE. MAY CAUSE ALLERGIC RESPIRATORY AND SKN REACTION. CONTENTS UNDER PRESSURE.

DANGER! Contains polyurethane prepolymer, methylenediphenyldiisocyanate, dimethylether and hydrocarbon propellant mixture. Do not use near sparks, heat, or open flame. Vapors will accumulate readily and may ignite explosively. Ventilate area during use and until all vapors are gone. **DO NOT SMOKE.** Extinguish all ignition sources. If burned, dried foam may release hazardous decomposition products. Dried foam may be combustible if exposed to flame or temperatures above 240°F. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other sources of heat that may cause bursting. Do not puncture, incinerate, burn, or store above 120°F. Do not discard empty can in garbage compactor. Gives off harmful vapor of solvents and isocyanates. Do not use if you have chronic lung or breathing problems, or if you have ever had a reaction to isocyanates. Use with adequate ventilation. Use appropriate respiratory protection when potential to exceed exposure limits exists. If you have breathing problems during use, leave the area and get fresh air. If symptoms develop or persist, call a doctor or obtain medical treatment; have this label with you. **EYE AND SKIN IRRITANT.** Avoid contact with eyes and skin. Prolonged or repeated skin contact may lead to sensitization and dermatitis. Wash hands after using. Do not swallow. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

FIRST AID: For eye contact flush with water for 15 minutes. Call a physician if irritation develops and persists. For skin contact, wipe off excess uncured foam with a clean rag or paper towel immediately. Get medical attention if irritation develops and persists. If affected by inhalation, remove to fresh air and contact a physician. If swallowed, do not induce vomiting. Call a physician or Poison Control Center immediately. **KEEP OUT OF REACH OF CHILDREN.**



WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

Refer to the Safety Data Sheet (SDS) for further information

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

LIMITED WARRANTY

This product is warranted by Henkel Corporation to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty – express or implied – including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact



Trusted Performance. Proven Results.

For over 50 years, Loctite Brand adhesives and sealants have taken on the toughest jobs. Used in race cars, airplanes, and even in the space-shuttle, Loctite provides solutions for the most demanding industrial, professional and consumer applications. Loctite gives you not the specialization, power and performance to not only get your job done, but to get it done right.

For Technical Assistance call : 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET
www.loctiteproducts.com



Loctite Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067
www.henkelna.com