



Technical Data Sheet



Technical Data Sheet
Ref: NRPTX67000TDS
Issued: 17.04.20
Number of pages: 3



Pattex Concentrated Wallpaper Remover

CHARACTERISTICS

- Water based surfactant solution for fast and effective removal of most wallpapers/ wallcoverings
- Concentrated – dilute with water
- Excellent penetration of paper and non-woven (paste the wall) wallpapers
- High efficiency
- Easy to use

APPLICATION FIELD

Removes wallpaper including washables, vinyls*, painted wallpapers and woodchip.

INSTRUCTIONS FOR USE

Preparation

1. Protect surrounding area and furniture with polythene sheeting
2. *Remove decorative face of vinyl wallpaper
3. Score face of wallpaper with wire brush or wallpaper scoring tool taking care not to damage the wall



INSTRUCTIONS FOR USE (cont.)

Application

1. To remove up to 40m² of wallpaper, mix as follows in a clean plastic bucket:

Wallpaper type	Remover	Cold water	Mix ratio
Standard wallpapers (including vinyls*)	100ml (2.5 cap doses)	4 litres	1:40
Painted and heavy wallpapers (including woodchip)	200ml (5 cap doses)	4 litres	1:20

2. Apply a liberal, even coat over the wallpaper using a brush or sponge. Wipe off accidental splashes immediately with a damp cloth
3. Leave to soak 10 to 15 minutes
4. Scrape off softened wallpaper with a scraper
5. Repeat application for multi-layer and stubborn wallpaper
6. Wash down wall with detergent and water to remove traces of adhesive

Important:

Wear rubber gloves & safety goggles

Do not allow wallpaper stripper to come into contact with electrical fittings, furniture and painted surfaces

TECHNICAL DATA

Composition	10 – 15% non ionic surfactants, preservative, defoamer
Appearance	Clear liquid
pH value	Approx. 8.5 – 10.5
Odour	Slight detergent
Mixing ratio	1:20/ 1:40 depending on wallpaper
Working temperature	Recommended application temperature +18°C to +22°C Do not use below +10°C or above +30°C
Consumption (mixed)	Approx. 100ml/m ²
Coverage (mixed)	Approx. 10m ² /litre for single application
Shelf Life	12 months From date of production. In unopened bottle when stored in cool, dry conditions (+5°C to +25°C), protected from sunlight
Residence time	10 – 15 minutes depending on wallpaper
Durability of mixed solution	Up to 48 hours when stored in cool, dry conditions (+5°C to +25°C) in covered bucket



LIMITATIONS

This product may be used for the removal of wallcoverings hung using any type of reversible wallpaper paste only

Impermeable surfaces, such as vinyl wallpapers, must be perforated first

Do not allow wallpaper stripper to come into contact with electrical fittings, furniture and painted surfaces

Do not use in combination with a steam stripper

Cleaning tools: Clean buckets and tools immediately with warm water

Storage: Avoid frost and extreme temperatures - store in dry conditions, +5°C to +25°C

Product disposal: Dispose of waste and residues in accordance with local authority requirements
Use packages for recycling only when totally empty

PACKAGING

500ml bottle with dosing cap

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel Norden AB

Box 151 22

Gustavslundsvägen 151A

SE-167 15 Bromma, Sweden