

**TECHNOMELT®**



**That's ME!**

TECHNOMELT PUR ME

# **MICRO EMISSION PUR HOTMELT ADHESIVES FOR PROFILE WRAPPING**

- › Profile wrapping of wooden based profiles
- › In combination with decorative laminates, treated plastics and paper foils
- › All in proven and regularly monitored Micro Emission quality



**Henkel**

Henkel Adhesive Technologies

## MICRO EMISSION PUR HOTMELT ADHESIVES FOR PROFILE WRAPPING

Our TECHNOMELT PUR Micro Emission products contain less than 0,1% diisocyanates. They are free of hazard labels, and are exempt from the restrictions arising from REACH Annex 17. They therefore make a major contribution to occupational health and safety in the production of our customers.

Every PUR Micro Emission adhesive from Henkel is regularly tested for its diisocyanate content to ensure that it meets the legal requirement.

**So that you can be sure to do the utmost for your staff. Promised!**



### TAILORED SOLUTIONS TO FULFILL YOUR NEEDS

Product	Basis	Viscosity, Brookfield mPas-s @ 130°C	Recommended working temperature		Characteristics
			in glue pot	on roller/nozzle	
<b>TECHNOMELT PUR 6202 ME</b>	PUR Micro Emission	25,000 – 48,000	120 – 160°C	120 – 160°C	Universally applicable, fast setting.
<b>TECHNOMELT PUR 6208 ME</b>	PUR Micro Emission	25,000 – 45,000	120 – 150°C	120 – 150°C	Universally applicable. Hybrid with high initial tack.
<b>TECHNOMELT PUR 6350 ME</b>	PUR Micro Emission	25,000 – 45,000	120 – 140°C	120 – 140°C	Universally applicable, fast setting, good initial tack.

GET IN CONTACT WITH US

Henkel AG & Co. KGaA  
Henkelstraße 67  
40589 Düsseldorf

[www.furniture-building-components.com](http://www.furniture-building-components.com)  
[wood@henkel.com](mailto:wood@henkel.com)

