



# Technical Data Sheet



## UniBond Grout Reviver (Triple Protection Anti-Mould)

Water-based coating to refresh old grout lines

### CHARACTERISTICS

UniBond Grout Reviver is a water-based, ready-to-use coating with excellent mould resistance suitable for use in sanitary applications.

The product is applied directly from an applicator pen, as a coating over existing grouts to improve their appearance.

UniBond Grout Reviver cures at room temperature to form a durable, long-lasting coating.

UniBond Grout Reviver contains a fungicide to ensure long-term mould resistance:

- Excellent adhesion on existing old grout lines
- Suitable for vertical grout joints
- No need to remove existing grout before use
- Low odour
- Easy clean-up: Fresh product can be removed with water

### APPLICATION FIELD

UniBond Grout Reviver is intended for narrow joints on walls. Recommended for refreshing grout joints between ceramic and porcelain tiles in bathrooms, toilets, laundry rooms, kitchens etc.

Technical Data Sheet  
Ref: UB3000  
Issued: 17.11.2022  
Number of pages: 3





## TECHNICAL DATA:

<b><u>Uncured product</u></b>		
Base:	Water-based dispersion	
Odor:	Slight	
Application temperature:	+5°C to +40°C (substrate and ambient)	
Consistency:	Viscous liquid	
Density:	~ 1.45 – 1.55 g/ml	
Skin formation time:	~ 30 minutes	(23°C, 50% r.h.)
Drying time:	Approximately 60 minutes	(23°C, 50% r.h., film 2 mm)
<b><u>Cured product</u></b>		
Appearance:	Matt white surface	
Odour:	Odourless	
Service temperature:	+5°C to 80°C	

## INSTRUCTIONS FOR USE

### Preparation:

The grout line to refresh must be intact, sound, clean, dry and free from contaminants likely to impair adhesion. Where necessary, treat the existing grout joint with a propriety mould remover to eradicate mould contamination

### Application:

Shake the tube well. Remove the cap and depress nib several times until grout reviver begins to flow. Apply sparingly to the joint in an even coat. Remove excess before it has dried with a damp cloth. If necessary, re-apply after 1 hour.

In case of vertical joints, it is advisable to apply UniBond Grout Reviver with Anti-Mould for narrow joints on walls starting from the base of the grout line.

Remove excess grout reviver before it has dried with a damp cloth.

Clean applicator after use with water and replace the cap.

### Drying time:

Allow to dry at least 60 minutes before allowing water contact.

### Limitations

Only for use on ceramic and porcelain grout joints. May damage other tile types

Not suitable for areas of constant immersion or areas of permanent damp.

## GENERAL INFORMATION

### Storage

24 months from date of production if stored in an unopened pack, in dry conditions and protected from direct sunlight at temperatures between +5°C and +30°C.

Opened containers should be used up within 6 months.

**Consumption**

The consumption depends on the applied coating thickness; however, up to 60 linear meters can be used as an approximate guide.

**Packaging**

7ml tube with applicator and cap

**Colors**

White

**HEALTH AND SAFETY**

Before using the product please see related Material Safety Data Sheet that is available to download from [mymds.henkel.com](http://mymds.henkel.com).

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

**Henkel Limited**

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: [www.henkel.co.uk](http://www.henkel.co.uk)

e.mail: [technical.services@henkel.co.uk](mailto:technical.services@henkel.co.uk)