



Technical Data Sheet



Technical Data Sheet
Ref: US19000
Issued: 30.03.23
Number of pages: 3

Bath & Kitchen Sealant Anti-Mould Easy Pulse Dispenser

CHARACTERISTICS

- 100% Silicone.
- Waterproof .
- Mould resistant.
- Adheres to most common sanitary fixings such as glass, tiles, ceramics, aluminium, stainless steel, uPVC.
- Low modulus.
- Neutral cure.
- Suitable for sensitive surfaces such as mirrors.
- Resistant to conventional cleaning products.
- Easy Pulse air powered dispenser – no cartridge gun required.

APPLICATION FIELD

A one component, ready-to-use, neutral curing silicone sealant for sealing joints in warm, humid environments where there is a likelihood of mould growth.

Suitable for use in:

- Sanitary joints: baths, toilets, wash basins, showers, kitchens, worktops
- Tiling joints

STANDARDS

BS EN 15651-3	product type S: sealant for sanitary applications
BS EN 13501-1	reaction to fire: class E
ISO 846-B	microbiological growth: level 0
ISO 11600	class F-25LM and G-25LM
DIN 18540 (Germany)	pass internal tests





TECHNICAL DATA

Before curing	
Type of silicone	Alcoxy
Appearance	Paste
Density (ISO 2811-1)	~ 1,04 g/ml
Resistance to flow (ISO 7390)	~ 0 mm

Curing	
Skin formation time (+23 °C / 50% RH)	~ 30 min.
Curing speed (+23°C, 50% RH, cross-section of joint 20x10mm)	~ 2.5 mm / day
Application temperature	+ 5°C to + 40°C

After curing	
Shore A hardness (ISO 868)	~ 20
Movement capability (ISO 11600)	25%
Max. joint width	30 mm
Change of volume (ISO 10563)	~ 6%
Temperature Resistance	- 50°C to + 120°C

Mechanical properties	
Elastic recovery (ISO 7389-A)	~ 90%
Modulus at 100% elongation (ISO 8339-A)	~ 0.3 N/mm ²
Elongation at break (ISO 8339-A)	~ 250 %

INSTRUCTIONS FOR USE

Bath & Kitchen Sealant Anti-Mould is supplied ready-to-use and can be applied from the original packaging with no special pre-treatment.

Surface preparation

All surfaces must be clean, dry and free from contaminants likely to impair adhesion.

To get the best sealing results, it is recommended to mask edges of the joints with a tape before application of the sealant mass.

Sealant application

The sealant should be applied ensuring that the joint is completely filled. Smooth off the sealant with a smoothing tool to ensure good contact between the sealant and the bonding surfaces. Immediately remove masking tape (if using) and excess sealant with white spirit

Cleaning tools

Fresh sealant can be cleaned with a cloth dampened with white spirit

Cured sealant can only be removed by mechanical means (e. g. knife or razor blade)

Drying time

The sealant will be touch dry in 30 mins and fully dry in approx. 24 hours*

**Curing speed is dependent on temperature, air humidity and on the dimensions of the joint. Low temperatures, high air humidity or big joint dimensions require longer curing times.*

**Please note**

To maintain a mould free sealant bead, it is necessary to have a regular cleaning regime in place

LIMITATIONS.

Only for use as a sanitary sealant in areas where a hygienic seal is required

Not recommended for joints that are in direct food contact.

For interior use only. Not suitable for areas of constant immersion or permanent damp (e.g. Aquariums or swimming pools).

Sealant cannot be over painted

Not suitable for use on natural stone (e.g. marble, granite)

If in doubt, contact our technical helpline for further assistance

GENERAL INFORMATION**Storage**

Store in a cool, dry place between +5 °C and +25 °C. Shelf life is 12 months in an unopened dispenser after date of manufacture (the expiry date is shown on the dispenser).

Packaging

Easy Pulse pressure pack – 104g and 208g

Colours

Transparent

White

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

email: technical.services@henkel.co.uk