



Technical Data Sheet



UniBond No More Nails Permanent Strips

CHARACTERISTICS

UniBond No More Nails Permanent Strips are double-sided mounting strips with high holding power and high adhesion. UniBond No More Nails Permanent Strips have high initial tack and designed for most indoor and outdoor applications.

APPLICATION FIELD

- UniBond No More Nails Permanent Strips can be used to fix objects on many different smooth surfaces such as wood, ceramic tiles, metal, brick, stone, plaster and many plastics*.
*not for the use on PE, PP, PTFE (Teflon)
- For interior and exterior applications, waterproof.
- Ideal for mounting applications of hooks, signs, numbers, pictures, car number plates etc.
- Not recommended for applications on delicate surfaces such as wallpaper, load-bearing or dirt-repellent surfaces.

INSTRUCTIONS FOR USE

Application

Ensure surfaces to be bonded are clean and free of dust, grease or oil. Surfaces should not be load-bearing (Clean surface with alcohol, cleaning benzene or acetone).

Apply strip ensuring no air-bubbles are trapped beneath the tape and remove red protective liner. Press firmly into place.

Avoid application temperatures below 10 °C. Maximum holding power of up to 3kg per strip will be reached under ideal conditions: mounting of flat objects (thickness <10mm) to smooth glass or metal surfaces. Direct contact with water can reduce holding power. Final strength is reached after 24h. On surfaces other than glass or metal, holding power can be reduced. For mounting of objects with a thickness >10mm, holding power is reduced.

Technical Data Sheet

Ref: UC5000

Issued: 15.11.2022

Number of pages: 3





TECHNICAL DATA

| | |
|-------------------------|-----------------------------------|
| Colour / Appearance | White foam / double-sided tape |
| Carrier material | Polyethylene foam |
| Adhesive | Synthetic rubber |
| Liner | red Polyethylene/Propylene |
| Width | 20mm |
| Length | 40mm |
| Gap bridging capacity | Max. 0,8mm |
| Temperature resistance | Up to -40°C to +90°C (short term) |
| Application temperature | 10°C to 35°C |
| Shelf life | 24 months |

LIMITATIONS

Storage

Store in a dry, dust free place between 10 C° and 30 °C.

Important Remark

Delicate surfaces can be damaged when removing the tape. UniBond No More Nails Permanent Strips are **not recommended** for use on wallpaper or load bearing or dirt-repellent surfaces. If in doubt the tape must be tested in an inconspicuous place.

Not recommended for mirrors.

Disposal

Household waste

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”



Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

e.mail: technical.services@henkel.co.uk