



Technical Data Sheet



Technical Data Sheet
Ref: UB36000
Issued: 02.12.2022
Number of pages: 2

UltraForce Wall Tile Grout (White, Grey, Black, Beige)



CHARACTERISTICS

- Ready to use wall tile grout
- Waterproof
- Easy to apply
- For grouting porcelain, glazed ceramic, and mosaic tiles
- Triple Protection mould resistance – Repels, kills, lasts
- Lifetime guarantee

APPLICATION FIELD

A mould resistant, ready mixed wall tile grout for porcelain, glazed ceramic, and mosaic wall tiles (up to 8mm joint width). Contains an enhanced mould protect system.

TECHNICAL DATA

Composition:	A filled acrylic copolymer emulsion, with fungicide added.
Appearance:	Coloured paste.
Cure type:	Water evaporation
Odour:	Slight odour whilst drying.
Density: (g/cm²)	1.5
pH:	Typically 7.5 - 9.0
Viscosity:	Typically 20,000 - 40,000 poise
Application temperature range:	From +5°C to +35°C
Coverage:	approx. 8m ² /1.38kg
Shelf life:	At least 24 months in original sealed packaging.

Composition and properties of the mixture at 23°C and 50% R.H.

Open time:	Approximately 30 minutes.
Thermal:	Suitable for service temperature up to 70°C.
Fire:	Class F.



LIMITATIONS

Only for use with porcelain, fully glazed ceramic, or mosaic wall tiles. Do not use with other tile types such as unglazed, satin, matt, or metallic detailed tiles.

For interior use only. Not suitable for areas of constant immersion or permanent damp.

If in doubt, contact our technical helpline for further assistance.

STORAGE

Store in cool dry conditions. Protect from frost. Shelf life is at least 24 months in original sealed packaging.

HEALTH AND SAFETY

Before using the product, please see related Material Safety Data Sheet that is available to download from mymds.henkel.com.

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

email: technical.services@henkel.co.uk