



**DECLARATION OF PERFORMANCE OF CONSTRUCTION PRODUCT**  
**in accordance with Regulation No. RD-02-20-1/05.02.2015**

**No 013/01.11.2019**

1. Unique identification code of the product type:  
**Ceresit CT 85**
2. National requirements (order by the Minister of Regional Development and Public Works, national legislation), technical specification (national standard, Bulgarian technical approval) applicable to the construction product:  
**BDS EN 998-1:2016**
3. Intended use(s) of the construction product in accordance with the national requirements, as indicated by the manufacturer:  
**Base coat for thermal insulation boards made of expanded polystyrene (EPS)**
4. Name, registered trade name or registered trade mark, contact address of the manufacturer and place of manufacture:  
**Henkel Bulgaria Operations EOOD, Building Materials Plant  
1289 Mirovyane, Sofia, BULGARIA**
5. Name and contact address of the authorised representative (where applicable):  
**not applicable**
6. Name of national conformity assessment body (where applicable):  
**RESEARCH INSTITUTE OF BUILDING MATERIALS: Test Report No 082/31.01.2008**
7. Declared performance characteristics of the construction product:

Characteristic parameter	Performance	Test/determination method
Compressive strength after 28 days	14.9 MPa	EN 1015-11
Bending strength after 28 days	4.5 MPa	EN 1015-11
Adhesion to concrete	0.9 MPa	EN 1015-12
Adhesion to EPS	0.12 MPa (cohesive break)	EN 1015-12
Capillary water absorption	0.005 kg/(m <sup>2</sup> .min <sup>0.5</sup> )	EN 1015-18
Water vapour transmission coefficient	3.1.10 <sup>-4</sup> g/(m.d.Pa)	EN 1015-19

**Notes:**

- Column 1 contains a list of the characteristics as defined in the national requirements under point 2 for the intended use(s) indicated under point 3.
- Column 2 contains the declared performance in terms of levels or classes, or as a description of each corresponding characteristic listed in column 1.
- Column 3 contains the dated reference to the method used to test/calculate/determine the performance declared in column 2.

8. The performance characteristics of the construction product under point 1 are as declared under point 7.
- This Declaration of Performance of the construction product is issued entirely under the responsibility of the manufacturer under point 4 or the authorised representative under point 5.

Signed on behalf of the manufacturer (authorised representative):

Sofia, 01.11.2019

Quality Manager:

(Dr. An. Gerasimov)