



DECLARATION OF PERFORMANCE

No. 00053

- 1. Unique identification code of the product-type: Ceresit CM 77 UltraFlex
- 2. Intended use/es: Improved reaction resin adhesive with reduced slip
- 3. Manufacturer: Henkel AG & Co. KGaA; Henkelstraße 67; D-40589 Düsseldorf
- 4. Authorised representative: n/a
- 5. System/s of assessment and verification of constancy of performance: System 3, Reaction to fire System 4
- 6a. Harmonised standard/s: EN 12004:2007 + A1:2012
Notified body/ies: Materialprüfungsamt NRW, Marsbruchstr. 186, 44287 Dortmund (NB 0432)
- 6b. European Assessment Document: n/a
European Technical Assessment: n/a
Technical Assessment Body: n/a
Notified body/is: n/a
- 7. Declared performance/s:

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 4	EN 12004:2007 + A1:2012
Initial shear adhesion strength	≥ 2 N/mm ²	System 3	
Shear adhesion strength after water immersion	≥ 2 N/mm ²		
Shear adhesion strength after thermal shock	≥ 2 N/mm ²		
Open time: tensile adhesion strength after not less than 20 min.	≥ 0,5 N/mm ²		
Slip	≤ 0,5 mm		
Release of dangerous substances	See SDS		

- 8. Appropriate Technical Documentation and/or Specific Technical Documentation: n/a

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Wolfgang Maier,
Head PD/ACB Tiling Wall Floor ETICS

(signature)

Stephan Auer
Senior Manager AC PD Mineral Based Technology

(signature)

Düsseldorf, 26.08.2019