



LOCTITE

AMERICAS

UNITED STATES
Henkel Corporation
14000 Jamboree Road
Irvine, CA 92606
United States
Tel: +1.888.943.6535
Fax: +1.714.368.2265

Henkel Corporation
20021 Susana Road
Rancho Dominguez, CA 90221
United States
Tel: +1.310.764.4600
Fax: +1.310.605.2274

Henkel Corporation
18930 W. 78th Street
Chanhassen, MN 55317
United States
Tel: +1.952.835.2322
Tel: +1.800.347.4572
Fax: +1.952.835.0430

BRAZIL

Henkel Brazil
Av. Prof. Vernon Kriebler, 91
06690-070 Itapevi, Sao Paulo
Brazil
Tel: +55.11.3205.7001
Fax: +55.11.3205.7100

ASIA-PACIFIC

CHINA
Henkel Management Center
Building 7, No. 99 Jiang Wan Cheng Road
Shanghai 200438,
China
Tel: +86.21.2891.8000
Fax: +86.21.2891.8952

ABLESTIK (Shanghai) LIMITED
No. 332 Meigui South Road
WaiGaoQiao Free Trade Zone, Pu Dong
Shanghai 200131,
China
Tel: +86.21.2702.5888
Fax: +86.21.5048.4169

JAPAN

Henkel Japan Ltd.
27-7, Shin Isogo-cho
Isogo-ku Yokohama, 235-0017
Japan
Tel: +81.45.286.0161
Email: jp.ae-csdesk@henkel.com

KOREA

Henkel Korea Co Ltd.
18th Floor of tower B, BYC High City Bldg
Gasan Digital 1-ro, Geumcheon-gu,
Seoul, 08506
South Korea
Tel: +82.2.6150.3000
Fax: +82.2.6947.5203

SINGAPORE

Henkel Singapore Pte Ltd.
401, Commonwealth Drive
#03-01/02 Haw Par Technocentre,
Singapore 149598
Tel: +65.6266.0100
Fax: +65.6472.8738 / +65.6266.1161

TAIWAN

Henkel Taiwan Ltd.
10F, No. 866, Zhongzheng Road,
Zhonghe District, New Taipei City, 23586
Taiwan
Tel: +866.2.2227.1988
Fax: +866.2.2226.8699

Except as otherwise noted, all marks are trademarks and/or registered trademarks of Henkel and/or its affiliates in the U.S. and elsewhere.
© 2019 Henkel Corporation. All rights reserved. 14764/ LT-6742 (10/19) A4

LOCTITE

**Materials for
MICRO-ELECTRO-MECHANICAL SYSTEMS (MEMS)**



EUROPE


BELGIUM
Henkel Belgium N.V.
Nijverheidsstraat 7
B-2260 Westerlo
Belgium
Tel: +32.1457.5611
Fax: +32.1458.5530

UNITED KINGDOM

Henkel Ltd.
Adhesives Limited Technologies House
Wood Lane End
Hemel Hempstead
Hertfordshire HP2 4RQ
United Kingdom
Tel: +44.1442.278000
Fax: +44.1442.278071

Across the Board,
Around the Globe. 
henkel-adhesives.com/electronics


Henkel



MEMS Application Overview

Microphones, Pressure Sensors


Henkel has a full portfolio of proven materials for a range of processes from die attach to underfill to lid attach and glob top. And Henkel's global support structure ensures quick delivery of Henkel materials around the globe for just about any MEMS application.



MEMS Application Overview

Accelerometers, Gyroscopes, Magnetometers


Henkel provides multiple materials for quick evaluation and testing. This, combined with Henkel's global infrastructure, ensures expert on-site worldwide technical support.



MEMS Henkel Advantage

When one considers the average smartphone contains approximately eight to 10 MEMS – a number which is projected to grow in the coming years – one gets a sense for the breadth of MEMS applications. The ability to design, test and commercialize new MEMS devices quickly is critical to a MEMS manufacturer's market competitiveness. In order to meet the average three-to-six month cycle time, MEMS manufacturers need to leverage proven materials solutions that are market-ready, market-tested and supported globally to facilitate multi-site design and manufacturing.

For trusted, proven MEMS materials, a full-solutions approach, quick materials delivery for fast production ramp-up, supply chain simplification, global support and capability, along with an expert, knowledgeable team, Henkel is the obvious – and only – choice.



Henkel's MEMS Material Portfolio

Application	Products	Description	Modulus at 25°C (MPa)	Modulus at 250°C (MPa)	
ASIC Attach or MEMS Attach	Non-Conductive Paste	LOCTITE® ABLESTIK QM1536NB	Low stress and low moisture absorption, no bleed	300	76
		LOCTITE ABLESTIK QM1538NB		100	30
		LOCTITE ABLESTIK ABP 8142B	Ultra low stable modulus across reflow temperature	2.8	3
	Non-Conductive Paste Print B-Stage	LOCTITE ABLESTIK 8006NS	B-stageable, wafer backside coating, fillet control	4,400	70
LOCTITE ABLESTIK 6202CX		B-stageable, printed BOC, fillet control	900	6	
ASIC Attach	Non-Conductive Film B-Stage	LOCTITE ABLESTIK ATB F125E	DDAF, compatible with non-UV and UV dicing tape, very good laser / SDBG performance, suitable for < 3 mm x 3 mm die	5,256	185
		LOCTITE ABLESTIK ATB 120HA	Low modulus DDAF, laser & stealth dice able, suitable for > 3 mm x 3 mm die	2,299	8.3
ASIC Attach or MEMS Attach	Conductive Paste	LOCTITE ABLESTIK ABP 8060T	High thermal and electrical conductivity, high die shear strength	6,230	1,730
		LOCTITE ABLESTIK 8290	High reliability and good adhesion on different surfaces	3,034	117
Lid or Cap Attach	Non-Conductive Paste	LOCTITE ABLESTIK 3128	Low cure temperature and good adhesion on different surfaces including LCP	3,900	N/A
		LOCTITE ABLESTIK 8387B	High adhesion, fast cure, low weight loss	1,400	53
Lid or Cap Attach	Conductive Paste	LOCTITE ABLESTIK CE3920	Sn compatible, stable adhesion after 5X reflow, low weight loss	5,000	110
		LOCTITE ABLESTIK ABP 2032S	High adhesion on Au and steel, low temperature curable	4,600	150
		LOCTITE ABLESTIK 84-1LMISR4	Good adhesion on different surfaces	3,900	300
Lid or Cap Attach	Conductive Paste Print B-stage	LOCTITE ABLESTIK 8007	Stencil printable, B-stageable, good thermal and electrical conductivity	5,792	272
		LOCTITE ABLESTIK 8008MD		3,880	440
Lid or Cap Attach	Solder Paste	LOCTITE GC 10	Pb-free, no-clean, halogen-free, RT storage, long term stability	N/A	N/A
Glob Top	Non-Conductive Liquid	LOCTITE ECCOBOND FP 4802	Good flow, 260°C compatible	13,000	N/A
		LOCTITE STYCAST EO 1058	High T _g , low CTE	4,800	N/A
Underfill	Non-Conductive Liquid	LOCTITE ECCOBOND UF 8830S	Good flow with self filleting, bleeding control, 260°C compatible	11,500	350
	Non-Conductive Paste	LOCTITE ECCOBOND FP 5201	Self fluxing, high T _g , low CTE	5,800	N/A