


# Watertite CL 252

## Sealing tape

Sealing tape for the waterproof bridging of expansion and connection joints

### CHARACTERISTICS

- ▶ Waterproof
- ▶ Flexible
- ▶ Permanent bond
- ▶ Tearproof
- ▶ Non-ageing



### SCOPE OF USE

For waterproof bridging of expansion and edge joints, pipe entries, floor drains and room corners in combination with waterproof flexible sealing products Watertite CL 252 under ceramic tile coverings.

For indoor and outdoor use.

For use on floors and walls.

### APPLICATION

First, apply a layer of the selected sealing product, embed the sealing tape or sealing collar – with expansion joints form a loop, press and spread a sealant layer on top (do not cover the entire surface area).

### PLEASE NOTE

Store the above-mentioned products only in dry conditions and at temperatures of +5°C to +40°C. Observe the warnings-, safety- and waste advice given in the safety data sheet.



TDS\_Watertite CL 252\_GCC\_0519

1

### SHELF LIFE

Unlimited if stored in a dry place.

### SUPPLY

Watertite CL 252 100mm x 50m

### TECHNICAL DATA

Base	Polypropylen vlies
Dimensions (mm):	100
Temperature resistance:[°C]	30-100



**Henkel Polybit Industries Ltd.;** PO Box: 293, Umm Al Quwain, UAE  
Tel: +971(6)76 70 777; Fax: +971(6)76 70 197; [henkelpolybit@henkel.com](mailto:henkelpolybit@henkel.com)  
**Henkel Polybit Industries Ltd.;** PO Box: 5911, Dammam-31432, KSA  
Tel: +96613808 4061 / 62, Fax: +966 13 812 1164; [polybitdammam@henkel.com](mailto:polybitdammam@henkel.com)  
[www.henkelpolybit.com](http://www.henkelpolybit.com)

**Quality for Professionals**