LOCTITE.

LOCTITE[®] DRI 2250-W Pre-Applied Anaerobic Threadlocker

LOCTITE[®] DRI 2250-W is a medium to high strength pre-applied threadlocker specifically designed to meet automotive fastener specifications to prevent loosening of threaded fasteners. The pre-applied film is dry-to-the-touch and remains an inert coating until assembly. During assembly, microcapsules which are contained within the coating, are crushed thereby releasing an active ingredient which initiates the curing process. When cured, this product will also act as a thread sealant as well as a threadlocker.



Benefits

- Can be applied using a flow-coat system for high throughput
- High performance thread lock and seal for all fastener types including stainless steel and zinc-flake plated fasteners
- High temperature resistance > 200°C
- Low coefficient of friction (CoF)
- Excellent chemical resistance
- Suitable for small fastener applications < M2



Sustainability Value

- Water-based chemistry
- Contains no solvents
- Contains no halogen
- Environmentally friendly





LOCTITE.

Areas of application

Transmission / Gearbox / PTU

- Gearbox and transmission fasteners
- Oil pan and side cover fasteners

Differentional / Axle

• Case and cover fasteners

Engine

- Oil pan and cover fasteners
- Any critical fastener

Others

- Seat fasteners
- Electronic fasteners- M2 and smaller
- Any critical fastener subject to high vibration to prevent loosening

Technical Data

Product family	Methacrylate Ester
Color	Green
On Torque, M10 (ISO 10964)	≤ 0.15 N-m
Breakaway Torque, M10 (ISO 10964)	≥ 17.7 N-m
Prevail Torque, M10 (ISO 10994)	≥ 12.4 N-m
Coefficient of Friction, M10 (DIN 16047)	0.10 – 0.16
Operating temperature (°C)	200 +
Fixture time (min)	3 – 5
Chemical Resistance	Excellent

CONTACT US TO LEARN MORE

Europe

Germany Henkel AG & Co. KGaA (Headquarters) Henkelstraße 67, 40589 Düsseldorf

Asia-Pacific

China Henkel (China) Co., Ltd. No. 928 Zhangheng Road, Pudong New District 201203 Shanghai

Americas U.S.A.

Henkel Corporation t Madison Heights, 32100 Stephenson Highway Madison Heights, MI 48071



The data contained herein is intended as reference only. Some products / package sizes may not be available in your country or may have a lead time. Please contact your local Henkel subsidiary for assistance and recommendation on specifications and applications of these products. @ designates a trademark of Henkel AG & Co. KGaA or its affiliates, registered in Germany and elsewhere © Henkel AG & Co. KGaA, 2015

