

TECHNOMELT®

TECHNOMELT® PUR 9350

PUR HOTMELT

High performance, low fogging black reactive polyurethane hot melt adhesive. This adhesive develops a high initial strength shortly after application and is used for headlamp bonding and assembly of interior components for the automotive industry.



Benefits

- Outstanding long-term performance and durability
- Good adhesion on plastic substrates
 - › High initial strength
- High heat resistance
- Excellent sealing properties against moisture
- Low fogging



Areas of application

Lamp bonding

- Headlamp bonding of lens to body
- Interior components
- Structural bonding

Performance Characteristics



Fast cycle time



Proven reliability beyond the standards

Technical Data

Product family	PUR Hotmelt
Color	Black
Viscosity (Brookfield) at 130°C (mPa.s)	12500 ± 3500
Softening Point, DIN 52011 (°C)	65
Service temperature (°C)	-40 - 120
Shear strength on beech wood (MPa)	9

CONTACT US TO LEARN MORE

Europe

Germany
Henkel AG & Co. KGaA (Headquarters)
Henkelstraße 67, 40589 Düsseldorf

Asia-Pacific

China
Henkel (China) Co., Ltd.
No. 928 Zhangheng Road, Pudong New District
201203 Shanghai

Americas

U.S.A.
Henkel Corporation
Madison Heights, 32100 Stephenson Highway
Madison Heights, MI 48071



The data contained herein is intended as reference only. Some products / package sizes may not be available in your country or may have a lead time. Please contact your local Henkel subsidiary for assistance and recommendation on specifications and applications of these products. © designates a trademark of Henkel AG & Co. KGaA or its affiliates, registered in Germany and elsewhere © Henkel AG & Co. KGaA, 2022 DSGN0022136 (7/2022)

Henkel