

Ring Attach to Glass

Ring Attach Materials

LOCTITE ECCOBOND DS 3318LVT

LOCTITE STYCAST PC 40-UMF

Properties	Units	LOCTITE ECCOBOND DS 3318LVT	LOCTITE STYCAST PC 40-UMF
Appearance		Clear	Clear
Viscosity (cps)	mPa.s	142	250
Glass Transition Temperature (Tg)	°C	96	94
Modulus @ RT	N / mm ²	408	1,493
Recommended Cure		15 sec. @ 100 mW / cm ²	10 sec. @ 600 mW / cm ² + RT cure

Henkel AG & Co. KGaA Henkelstraße 67 40589 Düsseldorf | Germany Phone: +1 952 486 6313 E-mail: electronics@henkel.com www.henkel-adhesives.com/electronics



The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to the above information is protected by copyright. In particular, any reproductions, adaptations, storage and processing in other media, including storage or processing by electronic means, enjoy copyright protection. Any exploitation in whole or in part thereof shall require the prior written consent of Henkel AG & Co. KGaA. Except as otherwise noted, all marks used in this document are trademarks and/or registered trademarks of Henkel and/or its affiliates in the US, Germany, and elsewhere. © Henkel AG & Co. KGaA, oz/2018